

This is Why



- ▶ 60" (152.5 CM) DIAGONAL SCREEN SIZE
- ▶ 1.920 X 1.080 RESOLUTION IN DOTS
- ▶ UV2A TECHNOLOGY
- ▶ CONTRAST 4.000:1
- ▶ LED, EDGE LIT
- ▶ 24 / 7 OPERATION

Amply sized and attractively designed, Sharp's PN-R603 professional LCD monitors have the thin profile, high brightness, and low power consumption to accomodate a wide range of indoor digital signage applications. Exceptionally thin and lightweight, this streamlined monitor makes for easy, eye-pleasing installations and can be counted on for realiable, energy-efficient operation. Thanks to the Edge-lit LED backlighting on the PN-R603; this monitor consumes roughly only 32.5/50% which is less energy than the conventional CCFL-backlight displays.

▶ LCD Type: UV²A LCD

➤ Screen Size (mm): 1,525 mm
➤ Native Resolution: Full-HD 1920 x 1080 pixel

▶ Display Colours: 1.06 billion colours

▶ Brightness: 700 cd/m² Contrast Ratio: 4.000:1 ▶ Bezel H / V (mm): 19/19

▶ Panel Response Time (ms): 6 grey to grey

▶ Viewing Angle: H/V 176°

▶ DVI-D in/out: **DVI-I: in/DVI-D: out**

▶ HDMI: ✓

▶ 15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr): ✓

CONTROL TERMINALS

▶ RS232C: **✓** ▶ I AN: ✓

VIDEO / COLOUR STANDARDS

▶ PAL 60/N/M: **✓/**✓/✓

▶ SECAM:

▶ NTSC (MHz) 3.58/ 4.43: ✓/✓

▶ DTV 480i/480p/540p: **✓**/**✓**/× ▶ 576i/576p: ✓/✓▶ 720p/1.035i: ✓/✓

▶ 1080i/1080p: **✓/**✓ ▶ 1080/24p: **✓/**✓

ACCESSORIES

▶ Remote Control / Owners Manual (CD-ROM): ✓/✓

▶ Power Cable / PC Cable: <!>

PC-INPUT

▶ Full-HD (1920x1080): ✓

▶ UXGA 1600x1200: ▶ SXGA+ 1400x1050: ✓

SXGA 1280x1024:

► WXGA 1280x800 / 1360x768 / 1366x768: ✓

▶ XGA 1024x768: < ▶ SVGA 800x600: ✓

▶ Mac Compatible:

VIDEO TERMINALS

▶ DVI-D / DVI-I: ✓/✓

▶ HDMI: **✓**

▶ HDCP Compatible: ✓

AUDIO TERMINALS

▶ Mini Jack (3.5 mm) in/out: ✓/✓

▶ Via HDMI-Terminal:

Speaker Output (W RMS): Internal 10 x 10W

INSTALLATION

▶ Portrait / Landscape: ✓/✓

▶ Mounting Pitches (mm): VESA 6 points 200 mm, holding 4 points 200

▶ Special Features: slim and light weight

▶ Picture-in-Picture (PiP):

▶ Multi screen function:

▶ DSPA (Data Signal Power Auto): ✓

▶ Power supply (V) / power consumption, standard (W) / power consumption, ECO (W) / stand-by (W): 100-240V/200W

▶ Heat Dissipation (BTU / h): ECO-IMode / Standard: 682.89

▶ Dimensions in mm (W x H x D): 1378 x 794 x 39.4

▶ Weight (kg): 32

▶ Power consumption standby (W), IEC 62301 Ed. 1.0: 0.5

▶ Presence of lead: ✓





SHARP BUSINESS SYSTEMS UK PLC. 4 FURZEGROUND WAY STOCKLEY PARK UXBRIDGE, MIDDLESEX UB11 1EZ. TEL. 0208 734 2000