

A3 Colour MFP

# MX-8081

Ease of use meets professional productivity



- Fast 80ppm speed in colour and black & white with a maximum paper capacity of 8500 sheets
- Wide variety of finishing options, including saddle stitch finishing, manual stapling, and stapleless stapling
- Easy UI mode on tiltable 10.1-inch colour LCD touchscreen
- 300-sheet DSPF with double-feed detection scans documents at 240 ipm\* and handles paper up to 220 gsm thick
- Accommodates standard paper sizes up to SRA3/A3 wide (13" x 19"), custom sizes up to 330 x 488 mm (13" x 19.2"), and paper thicknesses up to 300 gsm
- Industry-leading, advanced security solutions for ultimate system/data protection and access control, including firmware self-recovery
- Embedded Fiery® Print Server for job and workflow management in busy on-demand environment
- Print Release function enables printout from any compatible networked MFP\*\*
- Superior image quality with Developer Refresh System
- Sharp OSA (Open Systems Architecture) allows integration with network and cloud-based applications (option)
- Application Portal\*\*\* offers apps for downloading and installing onto MFP
- Easy access to public cloud services via single sign-on (option)

\*Originals per minute; when feeding A4 (8 1/2" x 11") sheets. \*\*Contact a Sharp customer representative for details on the recommended maximum number of connectable MFPs. \*\*\*Contact a Sharp customer representative for details.

# Specifications

## GENERAL

Engine speed: A4 Colour (ppm)	80
Engine speed: A4 B/W (ppm)	80
Engine speed: A3 Colour (ppm)	37
Engine speed: A3 B/W (ppm)	37
Paper size: Min.-Max.	A5R - SRA3
Paper weight (g/m <sup>2</sup> )	55-300
Paper capacity: Std. (sheets)	3100
Paper capacity: Max. (sheets)	8500
Warm Up Time (sec.)	55
Memory general: Min./Max. (GB)	6
Harddisk	STD
Harddisk capacity (GB)	1000
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220-240V, 50 / 60Hz
Power consumption (kW)	3,84
Dimensions (mm)	845 x 844 x 1249
Weight (kg)	209

## DOCUMENT FEEDER

Original capacity (sheets)	300
----------------------------	-----

## DOCUMENT FILING

Document filing capacity: main & custom folders (pages)	35000
Document filing capacity: quick file folder (pages)	10000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick file folder, main folder, custom folder (max. 1000)
Confidential storage	•

## FAX

Fax (Standard / Option)	OPT
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3 / G3
Transmission time (sec.)	Less than 3
Modem speed (bps)	33,600 - 22,400
Transmission resolution (dpi)	203.2 x 97.8 / 406.4 x 391
Document size: Min.	A5R
Document size: Max.	A3
Memory (MB)	1024
Grey scale (levels)	256

## WIRELESS LAN

Wireless LAN (Standard / Option)	STD
Compliant regulation	IEEE802.11n / g / b
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP

## COPIER

Original paper size: Max.	A3
First copy out time: Colour (sec.)	5,6
First copy out time: B/W (sec.)	4,0
Continuous copy (Max. copies)	9999
Scan resolution: B/W (dpi)	600 x 600, 600 x 400
Scan resolution: Colour (dpi)	600 x 600
Print resolution (dpi)	1200 x 1200, 600 x 600, 9600 x 600
Gradation: Colour (equivalent levels)	256
Zoom range (%)	25-400
Preset copy ratios	10 (5R / 5E)

## SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	•
Push scan resolution (dpi)	100, 150, 200, 300, 400, 600
Pull scan resolution (dpi)	100, 150, 200, 300, 400, 600, 50-9600
File formats	TIFF, PDF, PDF / A-1, PDF / A-1b, encrypted PDF, XPS, compact PDF, JPEG, XPS, searchable PDF, Office Open XML, (pptx, xlsx, docx), txt (TXT), rich text (RTF)
Scan destination: Desktop	•
Scan destination: FTP, Email	•
Scan destination: Network folder	•
Scan destination: USB memory	•

## PRINTER

Resolution (dpi)	1200 x 1200, 600 x 600, 9,600 (equivalent) x 600
Interface: Std./Opt.	Std USB 2.0, 10Base-T / 100Base-TX-1000Base-T
Supported OS: Std.	Windows 8.1, 10. Windows Server 2012, 2012R2, 2016, 2019. Mac OS 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15
Network protocols	TCP / IP
Printing protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP, SMB, WSD
PDL: Std./Opt.	Std PCL6, Genuine Adobe PS3
Available fonts	80 (PCL), 139 (PS3)

## FINISHING

Output capacity: Max. (sheets)	4250
Staple capacity: Max. (sheets)	100
Saddle stitch	OPT
Off-set shifting	STD
Hole punch	OPT

## TONER YIELD

Black (pages at 5% coverage)	70000
Cyan (pages at 5% coverage)	50000
Magenta (pages at 5% coverage)	50000
Yellow (pages at 5% coverage)	50000



Design and specifications are subject to change without prior notice. Fiery is a registered trademark of Electronics for Imaging, Inc. in the US and/or certain other countries. Microsoft, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Gmail is a trademark of Google LLC. Mac is a trademark of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett-Packard Company. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe in the US and/or other countries. Intel and Pentium are trademarks of Intel Corporation or its subsidiaries in the US and/or other countries. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners. ©Sharp Corporation September 2020. Ref: MX-8081 Datasheet. All trademarks acknowledged. E&OE.