





- PRINT, COPY, SCAN, FAX
- ▶ PAGES PER MINUTE: 20 B/W
- ▶ PAPER CAPACITY: STD 600 MAX 1100 SHEETS
- ► FULL COLOUR A3 SCANNING
- STANDARD DUPLEX AND E-SORT FUNCTION
- OPTIONAL DOCUMENT FEEDER FOR INCREASED PRODUCTIVITY
- OPTIONAL NETWORK PRINTING/SCANNING
- SCAN TO USB MEMORY

Keep up with today's fast-paced business communications with one easy-to-use, compact solution that has all your basic office needs covered. The MX-M202D is packed with an extensive range of superb performance functions, delivering efficient copying, printing and brilliant colour scanning. Thanks to Sharp Printer Language with Compression (SPLC), print speeds are kept to a maximum even on complex jobs. Copying is just as fast, and handy features such as Electronic Sorting, for creating multiple sets of sorted documents without the need for a bulky page collator, will increase productivity. A Single Pass Feeder (SPF) for single-sided documents or a Reversing Single Pass Feeder (RSPF) for double-sided originals can be specified for easier double-sided scanning and copying. Certified for Energy Star and with Pre-heat and Auto Power Shut off modes proves the MX-M202D is energy efficient and environmentally-friendly. And with options available for powerful network printing/scanning and Super G3 faxing, the MX-M202D even has the functionality to grow with your business.

GENERAL

- ▶ Engine speed B/W ppm (A4): 20 ▶ Engine speed B/W ppm (A3): 11 Paper size: Min.-Max.: A6 - A3
- ▶ Paper weight (g/m2): 56-90 (Bypass 56-200)
- Paper capacity:Std (sheets): 600 Paper capacity: Max. (sheets): 1,100
- Warm Up Time (sec.): 25
- Memory general min/max (MB): 128 ▶ Memory printer min/max (MB): 128/256
- Duplex: STD
- Power requirements rated local AC voltage (Hz): 220-240V, 50/60Hz
- Power consumption (kW): 1,2 Dimensions (mm): 591 x 573 x 595
- Weight (Kg): 35

DOCUMENT FEEDER

▶ Original capacity (sheets): 40

PRINTER

- ▶ Resolution (dpi): 600 x 600
- ▶ Network Printer (Standard / Option): **OPT**
- ▶ Interface Std/Opt: STD USB 2.0 OPT 10Base-T/100Base-TX
- Supported OS Standard: Windows 2000/XP, Windows Server 2003/2008/2008R2, Windows Vista, Windows 7
- ► Supported OS Options: Mac OS X 10.2.8,10.3.9,10.4.11,10.5 10.5.8,10.6 - 10.6.5
- ▶ Network protocols: TCP/IP
- ▶ Printing protocols: LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, Novell Printserver application with NDS and Bindery, FTP for downloading print files, EtherTalk printing, IPP
- ▶ PDL Std/Opt: STD SPLC (GDI with JBIG compression) OPT PCL 6, PostScript 3
- Available fonts: 80 (PCL), 136 (PS3)

FINISHING

▶ Off-set shifting: STD

COPIER

- ▶ Original paper size (Max.): A3 First copy out time B/W (sec.): 7,2
- E-sort Std: •
- ▶ Continuous copy (Max. copies): 999 Resolution Scan B/W (dpi): 600 x 600
- ▶ Resolution Scan Colour (dpi): 600 x 600 Resolution Print (dpi): 600 x 600
- Gradation (equivalent levels) B/W: 2 Gradation (equivalent levels) - Colour: 256
- Zoom range (%): 25-400 Preset copy ratios: 10

SCANNER

- Network Scanner (Standard / Option): OPT
- Scan method Push scan and Pull scan:
- Resolution push scan (dpi): 75,100, 150,200, 300,400, 600
- Resolution pull scan (dpi): 75,100, 150,200, 300,400, 600,50-9600 custom File formats: TIFF, PDF, JPEG
- Scanner utilities: Button Manager, Sharpdesk
- Scan destinations Desktop:
- Scan destination FTP, Email: <
- ▶ Scan destination USB memory:

FAX

- ▶ Fax (Standard / Option): **OPT**
- ▶ Compression method: JBIG/MMR/MR/MH
- ▶ Communication protocol: Super G3/G3
- Transmission time (sec): 2
- ▶ Modem Speed (bps): 33,600 2,400
- ▶ Transmission resolution: STD: 203,2 x 97,8 dpi/Super Fine: 406,4 x 391 dpi
- Document Size (Min): A5
- ▶ Document Size (Max): A3
- Memory (MB): 16 (not upgradeable) Grey Scale levels: 256
- Dial Registration; rapid/speed dial: 350
- ▶ Broadcast Transmission (max. destinations): 200

