



10 mm Indoor FinePitch LED Module

NEC LED TiLE-T100Si (10 mm Indoor)



The NEC TiLE LED series – Tailor made displays for a brighter world

The all new NEC LED TiLE series products will inspire you with an eye-catching visual experience and shine a light on what matters to you. Whether in a board room, control room, a retail store, in a museum or at the airport, the versatility of the new LED TiLE products has virtually no limits.

With NEC'S TiLE LED Series you get the freedom you need to transform your walls into digital surfaces. TiLE - the intelligent Light Emitter - is the pixel card based solution with the capabilities to fit into almost any space using 240 mm to 320 mm square formats. Offering brightness levels of up to 6,000 cd even direct sunlight is not stopping your contents from shining. Protect your investment with high quality components and an exceptional longevity. Enter the world of mediatecture today – with a video wall that is made especially for you!

Benefits

Excellent homogeneity – uniform colour and brightness across the entire wall.

Supreme flexibility – tailor made pixelcards allow utmost flexibility within the available space.

Total cost of ownership reduction – with long-life LED lamp made by Nation Star, which creates the longest LED life available for a video wall.

Outstanding picture quality – through the use of Nation Star LEDs.

Specifications

Product Information

Product Name

NEC LED TILE-T100Si (10 mm Indoor)

Product Group

10 mm Indoor FinePitch LED Module

Order Code

60004157

Display

Pixel Configuration

3-in-1 SMD (Black)

LED type

SMD

Pixel Pitch [mm]

10

Contrast Ratio (typ.)

5000:1

Viewing Angle [°]

140 horizontal / 140 vertical

Brightness (max.) [cd/m²]

2000

Dimming Capability

256 levels

Lifetime

80000 hrs (50% brightness)

Colour Processing

16 bit

Colours [Trill.]

281 trillion

LED Driving Method

1/4 dynamic scan

Frame Rate [Hz]

60 fps

Refresh Rate [Hz]

≤ 4200

Colour Temperature [K]

3200 - 9300

Screen Resolution

Number of Pixel per m²

10000

Resolution of Pixel Card [px]

96 x 96

Connectivity

Input Digital (via controller)

DVI

Electrical

Power Consumption typ. [W]

180 per m² (normal use)

Power Consumption max. [W]

540 per m²

Environmental Conditions

Operating Temperature [°C]

0 to 40

Operating Humidity [%]

10 to 90

Mechanical

Dimensions (W x H x D) [mm] per module

960 x 960 x 166

Weight [kg]

39 per sqm

Regulatory

Safety and Ergonomics

CCC; CE; ETL; FCC Class A; RoHS

Additional Features

Manufacturer

S[quadrat]

Serviceability

Rear Service; Front Service optional

IP Level

IP30

Warranty

2 years



RoHS



CE



FCC Class A

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers.
All specifications are subject to change without notice. Errors and omissions are excepted. 24.09.2026