SHARP
Be Original.

- PRINT, COPY, SCAN, FAX, FILE
- PAGES PER MINUTE: 62 B/W 41 COLOUR
- PAPER CAPACITY: STD 3100 MAX 6600 SHEETS
- LARGE 10.4 INCH COLOUR TOUCH-SCREEN LCD AND CUSTOMISABLE USER SETTINGS
- HIGH-QUALITY IMAGING WITH NEW OIL-LESS TONER
- INDUSTRY-LEADING SECURITY SOLUTIONS FOR ULTIMATE DATA/DOCUMENT PROTECTION
- SHARP OPEN SYSTEMS ARCHITECTURE OSA ™ LETS THIRD PARTY DEVELOPERS TO CREATE CUSTOM APPLICATIONS THAT LINK THE MFP TO SOFTWARE PROGRAMMES ON A SERVER OR PC

Perfect for offices that mass-produce documents, the MX-6200N features a sturdy frame and streamlined paper feed system, boasts an extra-large paper capacity and offers a variety of productivity-enhancing finishing options. And with impressive output speeds of 41 ppm in colour and 62 ppm in black & white, documents are ready when you need them. What's more, if you are in need of an office-wide network printing solution, just add the optional Fiery Print Controller.

GENERAL

- Engine speed Colour ppm (A4): **41**
- Engine speed B/W ppm (A4): **62**
- Engine speed Colour ppm (A3): **19**
- Engine speed B/W ppm (A3): **34**
- Paper size: Min.-Max.: **A3W-A5R**
- Paper weight (g/m2): **55-256**
- Paper capacity:Std (sheets): **3100**
- Paper capacity: Max. (sheets): **6600**
- Warm Up Time (sec.): **295**
- Memory general min/max (MB): **1000**
- Memory printer min/max (MB): **896**
- Harddisk: **STD**
- Harddisk capacity (GB): **80**
- Duplex: **STD**
- Power requirements - rated local AC voltage (Hz): **200-240**
- Power consumption (kW): **1,84**
- Dimensions (mm): **795 x 715 x 1,225**
- Weight (Kg): **209**

DOCUMENT FEEDER

- Original capacity (sheets): **150**

DOCUMENT FILING

- Document filing (Standard / Option): **STD**
- Document filing capacity- main and custom folders (pages): **4200**
- Document filing capacity- quick file folder (pages): **1400**
- Stored jobs: **Copy, print, scan, fax transmission**
- Storage folders: **Quick file folder, main folder, custom folder (max. 500)**
- Confidential storage: ✔

FAX

- Fax (Standard / Option): **OPT**
- Compression method: **MH/MR/MMR/JBIG**
- Communication protocol: **Super G3**
- Transmission time (sec): **3**
- Modem Speed (bps): **33.600 - 2.400**
- Transmission resolution: **203,2 x 97,8/406,4 x 391**
- Document Size (Min): **A5**
- Document Size (Max): **A3**
- Memory (MB): **8**
- Grey Scale levels: **256**
- Dial Registration; rapid/speed dial: **999**
- Broadcast Transmission (max. destinations): **500**

COPIER

- Original paper size (Max.): **A3**
- First copy out time Colour (sec.): **8,4**
- First copy out time B/W (sec.): **4,5**
- E-sort Std: ✔
- Continuous copy (Max. copies): **999**
- Resolution Scan B/W (dpi): **600 x 300**
- Resolution Scan Colour (dpi): **600 x 600**
- Resolution Print (dpi): **600 x 600**
- Gradation (equivalent levels) - B/W: **2**
- Gradation (equivalent levels) - Colour: **256**
- Zoom range (%): **25-400**
- Preset copy ratios: **10**

SCANNER

- Network Scanner (Standard / Option): **STD**
- Scan method Push scan and Pull scan: ✔
- Resolution push scan (dpi): **100,200, 300,400, 600**
- Resolution pull scan (dpi): **75,100, 150,200, 300,400, 600,50 to 9600**
- File formats: **TIFF, PDF, encrypted PDF, JPEG (colour only)**
- Scanner utilities: **Network Scan Tool, Sharpdesk, Sharp Twain**
- Scan destinations Desktop: ✔
- Scan destination FTP, Email: ✔
- Scan destination Network folder: ✔
- Scan destination USB memory: ✔

PRINTER

- Resolution (dpi): **600 x 600**
- Enhanced resolution (dpi): **600 x 1200**
- Network Printer (Standard / Option): **STD**
- Interface Std/Opt: **STD USB 2.0,10Base-T/100Base-TX**
- Supported OS Standard:
  Windows NT4.0 SP5 or later, Windows 2000, Windows Server 2003, Windows XP, Windows 98/Me, Mac OS 9.0 to 9.2.2, Mac OS X10.1.5,10.2.8,10.3.3 to 10.3.9,10.4 -10.4.7
- Network protocols:
  TCP/IP, IPX/SPX (NetWare), NetBEUI, EtherTalk (AppleTalk)
- Printing protocols: **LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, Novell Printserver application with NDS and Bindery, FTP for downloading print files, EtherTalk printing, IPP**
- PDL Std/Opt: **STD PCL6/5c, OPT PS3 emulation**
- Available fonts: **80 (PCL), 136 (PS3)**

FINISHING

- Output Capacity Max.: **4000**
- Staple Capacity (sheets) Max.: **50**
- Saddle Stitch: **OPT**
- Off-set shifting: **OPT**
- Hole punch: **OPT**