Laser Projector - 4K+ 1 DLP - Professional

Sharp X141Q



Extreme efficiency in the sharpest detail

- Finest detail crisp 4K+ resolution achieves perfect image clarity for easy viewing of very detailed content
- Superb image quality producing vivid reds, the RB laser light source delivers excellent colour performance, projecting images that are remarkably lifelike
- IP6X rated optical engine protects against dust ingress for long lasting picture quality
- Designed for performance and efficiency these compact, flexible installation models achieve up to 20% lower energy consumption compared to our previous lamp-based models, such as the NEC PH1000U under comparable operating conditions.

Options

IoT and Asset Management

NaViSet Administrator 2 Sharp/NEC's software suite that provides monitoring, asset management and control functionality for display devices
Sharp/NEC's software suite that provides monitoring, asset management and control functionality for display devices.

Warranty Extensions

Warranty Extension for Laser Projectors Optional Warranty Extension (4th to 5th year) for dedicated Sharp Laser Projectors
Optional Warranty Extension (4th to 5th year) for dedicated Sharp Laser Projectors

Lenses

XP-57UL Ultra-short throw lens for dedicated X series projectors
Ultra-short throw lens for dedicated X series projectors.

XP-58ZL Short throw lens for dedicated X series projectors
Short throw lens for dedicated X series projectors.

XP-60ZL Standard zoom lens for dedicated X series projectors
Standard zoom lens for dedicated X series projectors.

XP-59ZL Short throw lens for dedicated X series projectors
Short throw lens for dedicated X series projectors.

XP-61ZL Standard zoom lens for dedicated X series projectors
Standard zoom lens for dedicated X series projectors.

XP-62ZL Long throw zoom lens for dedicated X series projectors
Long throw zoom lens for dedicated X series projectors.

Value Added Services

Laser Branding Optional Laser Branding Service for dedicated Sharp Display Products
Optional Laser Branding Service for dedicated Sharp Display Products

Support+ Optional additional services (1st to 3rd year) for dedicated Sharp Display Products
Optional additional services (1st to 3rd year) for dedicated Sharp Display Products

24/7 Usage for Projectors Optional 24/7 Usage (1st to 3rd year) for dedicated Sharp Projectors
Optional 24/7 Usage (1st to 3rd year) for dedicated Sharp Projectors

Mounting Options

Ceiling Mount PJ02CMPX Universal ceiling mount for dedicated Sharp/NEC projectors (PAxx4 and PXxx4 series)
Universal ceiling mount for dedicated Sharp/NEC projectors (PAxx4 and PXxx4 series).

Ceiling Mount PJ02UCMPF Universal ceiling mount for vertical and portrait projection for dedicated Sharp/NEC projectors
Universal ceiling mount for vertical and portrait projection for dedicated Sharp/NEC projectors.

Calilbration and Adjustment

ProAssist Generate perfectly homogeneous digital canvases from multiple projection installations
Generate perfectly homogeneous digital canvases from multiple projection installations.

Image Control and Connectivity

Hiperwall Innovative software- and IP-based solution to create reliable and flexible video wall solutions that can display data and video images from different sources at unequaled high resolutions
Innovative software- and IP-based solution to create reliable and flexible video wall solutions that can display data and video images from different sources at unequaled high resolutions.

Specifications

General

Series	[sharp-x-series]
Order Code	XP141Q (BK),XP141Q-W (WH)

Image

Aspect Ratio	16:10
Brightness Normal (lm)	13500
Compliant with ISO21118-2020	Yes
Contrast Ratio	[30000001]
Projection Technology	1-chip DLP™ Technology
Focus Adjustment	Motorized
Light Source Life Normal Mode (hrs)	20000
[AVProjectorSpecificationLensOptions]	6 motorized lens options
Lens Adjustment	Motorized
Lens Shift Up To H/V (3 values)	Up to H:±0.2, V:+0.6,-0.6
Panel Resolution	1920 x 1200 (WUXGA)
Projection Distance Minimum (m)	0.86
Projection Distance Maximum (m)	43.2
Projection Factor	depending on lens selection
Native Resolution	3840x2400 (4K+)
Screen Size Diagonal Maximum (cm)	1270.0
Screen Size Diagonal Maximum (inch)	500.0
Screen Size Diagonal Minimum (cm)	100.0
Screen Size Diagonal Minimum (inch)	40.0
Supported Resolution Interlaced	480i/50
Supported Resolution Progressive	480p/60
Supported Resolution (with format)	3840x2400 (4K+)
Zoom Type	Motorized
Keystone Correction V ± (°)	36
Keystone Correction H ± (°)	36

Connectivity

LAN	1 x RJ45
Digital Input	2 x HDMI™ supporting HDCP, 1 x HDBaseT, 2 x DisplayPort supporting HDCP, 1 x 12G-SDI
Digital Output	1 x 12G-SDI
Control	1 x Screen Trigger, 1 x D-Sub 9 pin (RS-232) (male)
USB	1 x USB A (2A power delivery)

Remote Control

Remote Control	Auto Adjust, Magnify-function, Eco Mode Control, Input Control, Direct Source Select, Picture Adjust, Full Lense control, AV Mute, Wired / Wireless Connection, Freeze-function, Test Picture, ID Select, Power (On-OFF), Shutter function, Select (up, down, left, right), Geometric Correction, On Screen On/Off Selection
3.5 mm Stereo Mini Jack Input	1

Electrical

Power Consumption Normal (W)	1080
Power Consumption Eco (W)	980
Power Consumption Stand-by (W)	0.5
Power Consumption Network Stand-by (W)	3
Power Supply (Hz)	50-60
Power Supply (V AC)	100-240

Mechanical

Colour Version	Black, White
Width Without Lens and Feet (mm)	500
Height Without Lens and Feet (mm)	216
Depth Without Lens and Feet (mm)	577
Fan Noise Eco (dB)	35
Fan Noise Normal (dB)	37
Weight (kg)	29.4

Environmental Conditions

Operating Humidity (%)	0 - 80
Storage Humidity (%)	0 - 90
Operating Temperature (°C)	5 to 45
Storage Temperature (°C)	-10 to 60

Ergonomics

Certifications	TUEV Type Approved, RoHS, ErP, CE

Green Features

Ecological Materials	100% recyclable packaging, Downloadable manuals
Ecological Standards	ErP compliant
Energy Efficiency	Laser light source

Guarantees

Warranty Light Source	3 years or 10000h (whatever comes first)
Warranty 3 Years Pan European Service	Yes

Shipping Content	Quick Setup Guide, Projector, Power Cord

Additional Features

Special Characteristics	Virtual Remote for direct PC control, AMX Beacon, Direct Power-Off Function, DICOM simulation, Constant Brightness Mode, NaViSet Administrator 2, Multi-Screen compensation mode, Cinema Quality Picture (CQP) Processing for best image quality, Light Source Adjustment, Lens Memory, Built-in Display/Multiscreen Splitter, LAN, 4K/60Hz interfaces, Digital 3D Reform™, Manual Wall Color Correction, Geometric Correction, Password Security System, Free Tilt, PJ LINK, PIP/Side by Side, HDMI - Input, Optional User Logo, Timer-Function, Stacking Function, RS-232 Control, OPS module support, Portrait Setting, IP5X/IP6X rated, Sealed engine, Edge Blending Function, Crestron Connected
OSD Languages	27

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. Sharp X141Q, 26/10/2026