

PN-R903A

- 90" (228,7 cm) display for professional 24/7 signage
- Slim bezel design with Built-in Stereo Speakers 10 + 10W
- LED, full array
- LANDSCAPE & PORTRAIT INSTALLATION SUPPORT
- 1920 x 1080 pixels with 700cd/m2
- Contrast 4000:1
- 24 / 7 Operation
- Sharp UV2A Display Technology

Specifications

DISPLAY MODULE DATA

Panel Technology	LCD UV2A RGB
Native Resolution (Pixels)	1920 x 1080
Diagonal Size (inches / cm)	90 / 228.7
Aspect Ratio	16 : 9
Backlight Technology	LED Full Array
Brightness (cd/m2)	700
Contrast Ratio	4000:1
Display Colours	1.06b
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	1.038 x 1.038 mm
Viewing Angle (H/V)0 CR >10	176 / 176

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 / 50-60
Power Consumption (W) (Operating MAX)	660
Operating Temperature (oC)	0 to 40
Humidity (%)	20 to 80
Heat Dissipation (BTU/h) MAX	2253.52

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4 / 600mm x 400mm or 4 / 600mm x 600mm

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

DVI-D	1
DisplayPort	1
Audio/Headphone 3.5mm Jack	1

ACCESSORIES

Remote Control Transmitter	STD
Power Cord	STD

KEY SPECIFICATIONS

24/7 Operation Certified	•
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 x 10
Computer Input - Plug and Play	•
Power Management	•
Cabinet Colour	BLACK
Fanless	•
Temperature Sensor	•
Multi-Screen Function - Videowall Mode (Enlarge Feature)	•
Multi Language OSD	•
Daisychain (Mirror mode)	•
Hardware Diagnosis	•
Monitor Control Software Support	•
Temperature Control	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	35
Bezel Size (U/L) mm	27
Product Dimensions (W/H/D) mm	2,055 x 1,197 x 122
Shipping Carton Dimensions (W/H/D) mm	2230 x 1525 x 570
Product Weight Without Stand (Kg)	75 kg
Shipping Weight (Kg)	105 kg

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DVI-I	1
DisplayPort	1
VGA	1
Component	1
Composite	1
Audio 3.5mm Jack	2

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
RS232C OUT	1
LAN Port	1