

NEC VT700



- **DVI-I Interface with HDCP**

see more.

NEC Display Solutions

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs

Display	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA
Lamp	210 W (172 W Eco Mode)
Lamp Life [hrs]	2500 (3500 Eco Mode)
Brightness ¹	3000 ANSI Lumens (2400 ANSI Lumens Eco Mode)
Contrast Ratio ¹	500:1
Lens	F= 1.7–2.07, f= 18.9–22.7 mm
Diagonal: min. / max. [cm]	53 / 762
Projection Distance [m]	0.7 – 11.1
Projection Factor	1.5 – 1.8 : 1
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz
Native Resolution	1024 x 768 (XGA)
Supported Resolutions	1920 x 1080 (HDTV 1080i/60. HDTV 1080i/50); 1600 x 1200 (UXGA); 1280 x 1024 (SXGA); 1280 x 1024 (Mac 23"); 1280 x 720 (HDTV 720p); 1152 x 870 (Mac 21"); 832 x 624 (Mac 16"); 800 x 600 (SVGA); 720 x 576 (DVD progressive); 720 x 480 (DVD progressive); 720 x 480 (SDTV 480p); 640 x 480 (VGA/Mac 13"); 1024 x 768 (XGA) compressed
ComputerAnalog	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr); Output: 1 x Mini D-sub 15 pin
DVI	Input: 1 x DVI-I with HDCP, shared with DVI analog (DVI-VGA Adapter)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x RCA Stereo for Video and S-Video; Input: 1 x 3.5 mm Stereo Mini Jack for Computer analog; Output: 1 x 3.5 mm Stereo Mini Jack (variable)
PC Control	Input: 1 x Mini DIN 8 pin (female)
Video Signals	PAL / PAL60 / NTSC / SECAM / NTSC 4.43 / PAL-N / PAL-M
Audio Functions [W]	1 x 5 (mono)
Zoom / Focus Adjustment	Manual / Manual
Benefits	Automatic and manual vertical Keystone Correction (V= ±30°); Colour Management; Help Function; Manual Wall Color Correction; Off-Timer; Optional User Logo; OSD with 21 languages; Password Security System; Plug&Play; Quick-Start-/Quick-Power-Off Function; RS-232 Control; Short Throw Lens; Source Select with Beep Function; Supports Windows Vista Network Functions
Remote Control	Type RD-427E; Aspect Ratio; Audio Control; Auto Adjust; Freeze-function; Lamp Mode Control; Magnify-function; Optional Presentation and Mouse Control; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Select (up, down, left, right); Source Select
Dimensions (W x H x D) [mm]	309 x 112 x 258 (without lens and feet)
Weight [kg]	3.1
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	295 max.; 9 Stand-by Mode
Fan Noise [dB (A)]	29 Eco Mode
Safety and Ergonomics	CE; TÜV GS; RoHS
Warranty	Projector: 3 years pan-European Premium Service; Lamp: 6 Months, max. 1000 Hrs
Shipping Contents	Projector; IR Remote Control (RD-427E); Mini D-SUB Signal Cable; Power Cord (4.5 m); Soft Case; Handle; DVI-VGA Adapter; Users Manual on CD-ROM; Quick Setup Guide; Lens Cap
Optional Accessories	Ceiling Mount Kit (NP03CM); Lamp (NP05LP); Mouse Receiver (NP01MR)

CE



www.nec-display-solutions.co.uk

NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU
Phone: 0207 202 6300, e-mail: infomail@nec-displays.com
For further information on NEC products call: 08701 201160