

Visitor Management

OVM LITE



Powerful and compact Visitor Management kiosk.

- Compact, small-footprint sign-in/out kiosk designed as part of our Optimised Visitor Management solution, ideal for spaces where a minimal physical presence is essential.
- Fully configured kiosks are deployed and supported remotely, ensuring fast setup and reducing the need for on-site technical support.
- Perfect for smaller, lower-volume environments or secondary entrances, providing an efficient sign-in experience without requiring a large installation area.
- 11" touchscreen kiosk housed in a secure, powder-coated, lockable enclosure for durability, protection and consistent long-term operation.
- Integrated webcam for capturing visitor photo ID, improving security and verification during the sign-in process.
- Supports sign-in/out for Visitors, Employees and Contractors.
- Optional wireless Brother 810WUK badge printer support for on-demand creation of visitor or contractor passes when required.
- Dedicated iOS and Android mobile app enabling employees to automatically sign in and out when entering or leaving the premises.
- Contactless sign-in/out via QR code scanning, enhancing convenience while supporting modern hygiene and access practices.
- Flexible mounting options for desk or wall installation, compatible with the standard 75x75 VESA mount for versatile placement.
- Synchronises seamlessly with Microsoft Entra ID and Google GSuite Directory, ensuring visitor and user data remains aligned with your core systems.
- Backed by a 3-year RTB warranty, fully supported through Sharp AV CarePack for peace of mind and long-term reliability.

Specifications

Landscape	True
Cabinet Colour	White
Brightness Sensor	True
Operating Time	24/7
Frame Material	Steel
Via AC-Adapter	True
Operating Temperature (oC)	0 - 35
Storage Temperature [°C]	-20 - 60
WLAN	True
Diagonal Size (inches / cm)	11
Diagonal Size (inches / cm)	28
Power Supply	USB-C (15 W)
Energy Efficiency	Energy efficiency class: G
Ecological Standards	Minimal use of harmful material, Energy Star 8.0

Backlight Technology	LED
Brightness (cd/m2)	500
Contrast Ratio	1000:1
Display Colours	16.77
Palm Cancellation	True
Touch Method	Finger
Energy Star	True
Shipping Carton Dimensions (W/H/D) mm	140
Shipping Carton Dimensions (W/H/D) mm	192
Shipping Carton Dimensions (W/H/D) mm	58
Optimum Resolution	2560 x 1440 at 60 Hz
Supported Resolution	2560 x 1440
Audio	Integrated Speakers (1 W + 1 W)
Adjust Functions	LED Brightness, sRGB, Brightness
Safety & Ergonomics	EnergyStar 8.0