

- Wi-Fi IEEE 802.11 a/b/g and Ethernet compliant
- Compatible with all projectors with VGA connectivity
- Increased wireless security through standard WEP 64/128-bit data encryption
- High frame rate (up to 15 FPS) ensures smooth display of embedded video clips during presentations
- For Power-PC and Intel-based Macintosh computers incl. full Universal support

WMS 100 Image

TECHNICAL SPECIFICATIONS

RECEIVER SPECIFICATIONS	
Network Standards	IEEE 802.11 a/b/g; Ethernet
Bandwidth	802.11a: 5 GHz; 802.11b/g: 2.4 GHz
Channels	802.11b/g: USA & Canada: 11, Europe: 13, Japan: 14
Transmission Rate*	802.11a/g: Up to 54 Mbps; 802.11b: Up to 11 Mbps
Transmission Range	802.11a: 20-30 M – depends on environment 802.11b/g: 50 - 100 M – depends on environment
Antenna	2.4~2.4835, 5.15~5.25, 5.725~5.825 GHz
Operating Temperature	0~40°C
Operating Humidity	10~85%, Non-Condensing
AC Adapter Output	USA & Taiwan: 5V, 1A~1.7A; Europe: 5V, 1.7A
Connectors	D-Sub 15 pin; RJ-45
Status Indicators	Power On
Dimensions (W x H x D)	116 x 79.5 x 26.2 mm
Weight	190 g
Certification	CE, FCC
Management Protocol	Web-based utility
Graphics Resolution	800 x 600 (SVGA); 1024 x 768 (XGA)
Color Depth	16-bit/24-bit/32-bit
Security Mechanism	64/128 bit WEP
Shipping Contents	WMS 100 Receiver, AC power adapter, Presto! WMS 2.5 Installation software CD-ROM (incl. licenses for 3 users), Quick installation guide, Warranty card
SYSTEM REQUIREMENTS WINDOWS	
Operating System	Microsoft Windows® 2000/XP
CPU	Intel Pentium® III 800MHz or above
Memory	256 MB RAM or above
Hard Disk Space	10 MB of available hard disk space required for installation
W-LAN	802.11 a/b/g or b/g card with Infrastructure / Ad-hoc mode support (embedded or card bus)
SYSTEM REQUIREMENTS MACINTOSH	
Operating System	Mac OSX 10.2 or higher
CPU	Intel Pentium® 4 G4 or higher processor is recommended
Memory	256 MB RAM or above
Hard Disk Space	10 MB of available hard disk space required for installation
W-LAN	802.11 a/b/g or b/g card with Infrastructure / Ad-hoc mode support (embedded or card bus)

Maximum wireless signal rate based on IEEE Standard 802.11 specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead may lower actual throughput rate.

As all-in-one wireless hardware and software solution, WMS 100 Image comprises NewSoft's Presto! WMS sending software with a hardware receiver and is the ideal wireless presentation solution for business professionals! Integrated with NewSoft's most advanced wireless AV technology, WMS 100 Image implements the latest Wi-Fi 802.11 a/b/g standard to provide users with the freedom to broadcast PowerPoint slides or screen-captured images from any Wi-Fi enabled computer to a VGA, SVGA or XGA projector incorporating the WMS 100 hardware receivers and enabling all meeting participants to view the presentation content from different projection screens in real-time.

There is also an upgradeable software application available: Presto! WMS 100 Deluxe. Users are able to further upgrade their presentation system with „many-to-one“ broadcasting feature, and allowing a projector's screen to display multiple presentations from up to four users at the same time.

WMS 100 Image is easy to set up and use, giving users complete broadcast control of their presentations. Presenters will enjoy total unwired freedom during busy meetings!



All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. October 2008

www.nec-displays.co.uk

Display Solutions, NEC (UK) Ltd, 1 Victoria road, London W3 6BL

Phone: +44 (0) 807 120 1160, e-mail: info@nec-displays.com