

# NEC P554W Projector



- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- Minimized cost of ownership – due to long lamp life and filter exchange intervals.
- Cost effective replacement – of existing NEC P model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.
- High brightness – for best performance in bright ambient light.
- Peace of Mind – with future-proof connectivity.

# Specifications

## PANEL RESOLUTION

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel - / - / •  
Native Resolution 1280 x 800 (WXGA)

## DATA TERMINALS

HDMI •  
15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr) •

## CONTROL TERMINALS

RS232C (Sub-D) •  
LAN •  
USB-Host •

## COLOUR STANDARDS

PAL 60/N/M • / • / •  
SECAM •  
NTSC (MHz) 3.58/ 4.43 • / •

## ACCESSORIES

Remote Control / Owners Manual (CD-ROM) • / •  
Power Cable / PC Cable • / -

## PC-INPUT

H-Frequency (kHz) 15 - 100 KHz  
V-Frequency (Hz) 50 - 120 Hz

## VIDEO TERMINALS

S-Video (Y/C) •  
HDMI •

## AUDIO TERMINALS

Mini Jack (3.5 mm) In/Out •  
RCA-Stereo Terminal In/Out •  
Via HDMI-Terminal •

## PICTURE DATA

Luminance ECO-mode (ANSI Lumen) / 3300 / 5500  
Standard (ANSI Lumen)  
Contrast 20000:1  
Projection lamp (W) / Lamp lifetime ECO-Mode 330 / 8000 / 4000  
(h) / Lamplife Standard (h)  
Fan 34 dB ECO / 37 dB  
Lens built-In / Changeable Lens - / •  
Zoom-Lens (Manual/ Motorized) • / -  
Lens Shift (H/V) • / •  
Keystone (manual/auto) • / -

## OTHERS

Power supply (V) / power consumption, 100-240 / 422 / 267 / 0.2  
standard (W) / power consumption, ECO (W) /  
stand-by (W)  
Dimensions in mm (W x H x D) 420 x 133 x 322  
Weight (kg) 4.7

