

MultiSync® LCD1530V

Preliminary specifications

Display Type:	38 cm (15.1 inch)
Active Display Area:	307 x 230 mm
Pixel Pitch:	0.30 x 0.30 mm
Viewing Angle:	120° horizontal / 90° vertical (at CR= 10:1)*
Brightness:	200 cd/m ² typ.
Contrast Ratio:	200 :1 typ.
Number of Colours:	16.19 Mill. (with dithering)
Optimum Resolution:	1024 x 768 @ 75 Hz
Other Resolutions:	832 x 624, 800 x 600, 720 x 400, 720 x 350, 640 x 480, 640 x 400
On-Screen Manager (OSM):	Brightness; Contrast; Auto Adjust; Colour Temperature Control; Fine Adjust; Monitor Info; Language select; Intelligent Power Management (VESA/EPA/NUTEK compliant) disable; OSM lock out
User Controls:	On/Off, OSM Menu
Plug & Play, Asset Management:	VESA DDC1, DDC2B and EDID-Standard
Horizontal Frequency:	31 - 60 kHz
Vertical Frequency:	56.2 - 75 Hz
Dot clock rate:	21.1 – 78.8 MHz
Connectors:	Mini D-Sub, 15 pin
Audio Functions:	No
USB Functions:	No
VESA Mounting Interface:	Yes
Kensington-Lock:	Yes
Dimensions (W x H x D):	370 x 370 x 160 mm
Screen Tilt / Swivel / Rotate:	-5° to +30° / No / No
Weight:	4,7 kg
Power Supply:	100-120V/220-240V / 0.46A/0.27A, internal power supply
Power Requirements:	25 W max. On mode, < 3 W Power save mode
Ambient Temperature (Operating):	+5 °C to +35 °C
Ambient Humidity (Operating):	10-80% (non-condensing)
Safety/Ergonomics:	CE; TÜV GS; TÜV ERGONOMIE; UL; ISO9241-3/-7/-8; TCO99; FCC Class B; Energy Star
Warranty:	3 years warranty, including backlight, 3 years on-site warranty*
Shipping Contents:	Monitor; Power cable; Video signal cable D-Sub to D-Sub; CD-ROM; List of retailers; Users manual

- ✓ Allround LCD monitor with Digital TFT Display
- ✓ New compact design
- ✓ VESA mounting interface enables versatile installation
- ✓ Ergonomics and safety compliant to state-of-the-art standards
- ✓ Analogue Input

*** 3 years on-site warranty within EU countries, Switzerland, Norway, Liechtenstein
and Ice with optional exchange or repair and return service
All specifications are subject to change without notice, Status October 2000.**

