

NEC MultiSync® LCD2690WUXi



Innovative High-end LCD widescreen monitor with outstanding features and benefits for ergonomics and economics.

- High performance H-IPS A-TW TFT 16:10 display
- Monitor for every situation and every application due to its versatile features such as AmbiBright, AutoBright, TileMatrix or HDCP support
- ErgoDesign®: Height adjustable stand (150 mm) with 90° Pivot features
- Best economics and reduced Total Cost of Ownership with multiple features such as EcoModes, Scheduler, Power Off timer, OSD KeyGuide
- Extraordinary features such as CableComp, ColorComp or X-light® Pro

see more.

NEC Display Solutions

Panel Technology	H-IPS A-TW Pol. (Horizontal IPS with Advanced True Wide Polarizer)
Screen Size [inch/cm]	26 / 64.9
Colour Gamuts (Size comparison, typ.)	95% AdobeRGB, 91% NTSC
Pixel Pitch [mm]	0.287
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	800:1
Brightness (typ.) [cd/m²]	400
Response Time (typ.) [ms]	8 (grey-to-grey), 16 (8 white / black; 8 black / white)
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	31.5 - 93.8 and 119.2 (analog) / 31.5 - 91.1 and 119.2 (digital)
Vertical Frequency [Hz]	50.0 - 85.0
Optimum Resolution	1920 x 1200 at 60 Hz
Supported Resolutions	1920 x 1080p; 1600 x 1200; 1280 x 1024; 1280 x 960; 1280 x 720p; 1200 x 1920; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 576p; 720 x 480p; 720 x 400; 640 x 480; 640 x 480p
Connectors	Digital: 1 x DVI-D; Digital/ Analog: 1 x DVI-I; Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; EDID Standard; VESA DDC2B
Adjust Functions	Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Advanced User Menu; Auto Adjust; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Fine Adjust (analog); Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Display (OSD) lock-out; Sharpness
Safety and Ergonomics	CE; TCO 03; TÜV Ergonomics; TÜV GS; C-tick; GEEA/Energy Label; Energy Star; FCC Class B; PCT/ Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; PCBC/B-mark; PSB; RoHS
Power Consumption on Mode [W]	111 (max.)
Power Consumption Power-Saving Mode [W]	1
Power Supply	100-120 V/220-240 V; 1.5 A/0.75 A; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	200 x 100 (5 points); 100 x 100 (4 points)
ErgoDesign®: Height adjustable Stand [mm]	150 (Landscape mode)
Screen Tilt / Swivel [°]	-5 to +30 / -170 to +170
Dimensions (W x H x D) [mm]	589.8 x 444.2 - 594.2 x 306.0 (Landscape mode)
Bezel Width [mm]	18.8
Weight [kg]	12.6
Cable Management	yes
Kensington Lock	yes
Benefits	16:10 wide format; Adjustable power LED (colour and brightness); Advanced NTAA (Advanced Non-Touch- Auto-Adjustment); AmbiBright; ambix³™; Auto Black Level; Auto Brightness; Auto Contrast; AutoBright; CableComp with Sync Continuity Detection; ColorComp; DDC/CI compatible; Direct Brightness and Contrast; EcoModes; GammaComp (12 bit Look Up Table) and 12 bit Gamma Correction; NaViSet® and NaViSet®Administrator compatible; OmniColor™: sRGB and 6-Axis-Colour-Control; Overdrive; Quick release Stand and Handle; Rapid Response Technology; RapidMotion; Real Time Clock with Scheduler (Power-On and Power-Off Timer); Self Diagnostics; TileComp; TileMatrix; TORO™ Design; Windows XP; X-Light® Pro (AutoLuminance, AutoColour)
Audio Functions	Option: MultiSync® Soundbar 90
Colour Versions	Silver Front Bezel, Light Grey Back Cabinet Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable DVI-A - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight



NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU
Phone: 0207 202 6300, e-mail: infomail@nec-displays.com
For further information on NEC products call: 08701 201160