

Interactive Display

NEC MultiSync CB651Q-2



- Out-of-the-box collaboration – thanks to embedded computing with built-in annotation tools and wireless presentation capabilities.
- Multi-Touch – true multi-touch support with up to 20 simultaneous touch points.
- Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.
- Protective Glass – premium toughened glass protects the security of the panel yet delivers a perfect touch experience with anti-glare coating to minimise reflections and fingerprints.
- Simple operation – with easy front access to USB ports and controls for major functionalities.

Specifications

DISPLAY MODULE DATA

| | |
|-------------------------------------|---|
| Panel Technology | IPS with Direct LED backlights |
| Native Resolution (Pixels) | 3840 x 2160 |
| Diagonal Size (inches / cm) | 65 / 163.9 |
| Aspect Ratio | 16:9 |
| Backlight Technology | LED |
| Brightness (cd/m2) | 350 |
| Contrast Ratio | 1200:1 |
| Response Time (grey to grey avg) ms | 8 |
| Viewing Angle (H/V) 0 CR >10 | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn] | 1,073 (10bit) |

POWER SUPPLY AND OPERATING ENVIRONMENT

| | |
|---------------------------------------|---------|
| Power Consumption (W) (Operating MAX) | 400 |
| Operating Temperature (oC) | 0 to 40 |
| Humidity (%) | 10-90 |

INSTALLATION

| | |
|---|---------------------|
| Landscape | • |
| Mounting (VESA/Number of Points/Pitch mm) | 4; 600 x 400 (FDMI) |

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

| | |
|----------------------------|---|
| Audio/Headphone 3.5mm Jack | 1 |
|----------------------------|---|

ACCESSORIES

| | |
|-------------------|--|
| Shipping Contents | 3 x Stylus; HDMI Cable; Power Cable; Remote Control; USB cable; User Manual; VGA cable; Wall Mount |
|-------------------|--|

KEY SPECIFICATIONS

| | |
|-------------------------|---|
| Special Characteristics | AMX NetLinx Support; HDMI with UHD at 60 Hz; NaViSet Administrator 2; Scheduler |
| Operating Time | 12 / 7 |
| Built in Speakers (W) | 2 x 12 W |

WEIGHTS AND MEASURES

| | |
|-----------------------------------|------------------------|
| Bezel Size (L/R) mm | 17.7 |
| Bezel Size (U/L) mm | 17.7 / 45.7 |
| Product Dimensions (W/H/D) mm | 1,488.4 x 896.8 x 87.5 |
| Product Weight Without Stand (Kg) | 39.2 |

CONNECTIVITY (AUDIO/VIDEO) INPUT

| | |
|------------------|---|
| HDMI | 3 |
| DisplayPort | 1 |
| VGA | 1 |
| Audio 3.5mm Jack | 1 |

CONNECTIVITY (CONTROL/SERIAL DATA)

| | |
|-----------|---|
| RS232C IN | 1 |
| LAN Port | 1 |
| USB | 8 |

