



- ▶ HIGH VOLUME PRODUCTION
- ▶ PAGES PER MINUTE: 120 B/W
- ▶ PAPER CAPACITY: STD 3100 MAX 13500
- ▶ OUTSTANDING PRODUCTION MACHINE  
ENGINEERED TO DELIVER FIRST-CLASS  
RELIABILITY AND PERFORMANCE
- ▶ EXTENSIVE FINISHING OPTIONS INCLUDE  
100-SHEET STAPLING, SADDLE STITCH,  
MULTI-FOLDING, CURL CORRECTION,  
TRIMMING AND INSERTION CAPABILITIES
- ▶ 120 OPM 1-SIDED AND 200 OPM 2-SIDED  
SCAN SPEED IN COLOUR AND B/W WITH  
STANDARD 250-SHEET DSPF
- ▶ TILT TABLE 10.1" COLOUR LCD PANEL WITH  
FINGER SWIPE TOUCH CONTROL OFFERS  
SUPERIOR
- ▶ DESIGNED TO ENSURE EASY SERVICING AND  
MAXIMUM UPTIME WITH FULL FRONT ACCESS  
TO KEY COMPONENTS

Take one look at the features of the MX-M1204 and you'll see that it's ideal for long and continuous use in demanding production environments. It's super fast output speed of 120 pages per minute and ability to handle stock of up to 300 gsm is complemented by a generous, 13,500-sheet paper supply; a 2 sided scan speed of 200 originals per minute and a huge choice of finishing options. Precision engineering for proven durability and a surprisingly quiet operation makes it easy to own and work with, too.

## GENERAL

- Engine speed B/W ppm (A4): **120**
- Engine speed B/W ppm (A3): **54**
- Paper size: Max.-Min.: **SRA3 - A5R**
- Paper weight (g/m<sup>2</sup>): **52 - 300**
- Paper capacity:Std (sheets): **3100**
- Paper capacity: Max. (sheets): **13500**
- Warm Up Time (sec.): **210**
- Memory general min/max (MB): **5120**
- Memory printer min/max (MB): **5120**
- Harddisk: **STD**
- Harddisk capacity (GB): **1024**
- Duplex: **STD**
- Power requirements - rated local AC voltage (Hz): **220-240V, 13A, 50/60Hz**
- Power consumption (kW): **2,99**
- Dimensions Base unit (mm): **1084 x 790 x 1237**
- Dimensions full configuration (mm): **5982 x 790 x 1551**
- Weight (Kg): **295**

## DOCUMENT FEEDER

- Original capacity (sheets): **250**
- Original replacement speed - B/W: **120 (simplex)200 (duplex)**
- Original replacement speed - Colour: **120 (simplex)200 (duplex)**

## DOCUMENT FILING

- Document filing (Standard / Option): **STD**
- Document filing capacity- main and custom folders (pages): **35000**
- Document filing capacity- quick file folder (pages): **10000**
- Stored jobs: **Copy, print, scan, fax transmission**
- Storage folders: **Quick file folder, main folder, custom folder (max. 1000)**
- Confidential storage: **✓**

## FAX

- Fax (Standard / Option): **STD**
- Compression method: **MH/MMR/MMR/JBIG**
- Communication protocol: **Super G3**
- Transmission time (sec): **3**
- Modem Speed (bps): **33,600**
- Transmission resolution: **203.2 x 97.8/406.4 x 391**
- Document Size (Min): **A5**
- Document Size (Max): **A3**
- Memory (MB) Std/Max: **1**
- Grey Scale levels: **256**
- Dial Registration; rapid/speed dial: **999**
- Broadcast Transmission (max. destinations): **500**

## COPIER

- Original paper size (Max.): **A3**
- First copy out time B/W (sec.): **3,2**
- E-sort Std: **✓**
- Continuous copy (Max. copies): **9999**
- Resolution Scan B/W (dpi): **600 x 600**
- Resolution Scan Colour (dpi): **600 x 600**
- Resolution Print (dpi): **1200 x 1200**
- Gradiation (equivalent levels) - B/W: **256**
- Zoom range (%): **25 - 400**
- Preset copy ratios: **10 (5E/5R)**

## SCANNER

- Network Scanner (Standard / Option): **STD**
- Scan method Push scan and Pull scan: **✓**
- Resolution push scan (dpi): **100,150, 200,300, 400,600**
- Resolution pull scan (dpi): **75,100, 150,200, 300,400, 60050 - 9600**
- File formats:  
**XPS, PDF, Encrypted PDF, Compact PDF, PDF/A-1b, JPEG, TIFF**
- Scanner utilities: **Sharp OSA Network Scanner Tool, Sharpdesk**
- Scan destinations Desktop: **✓**
- Scan destination FTP, Email: **✓**
- Scan destination Network folder: **✓**
- Scan destination USB memory: **✓**

## PRINTER

- Network Printer (Standard / Option): **STD**
- Resolution (dpi): **1200 x 1200**
- Enhanced resolution (dpi): **1200 x 1200**
- Interface Std/Opt: **Std USB 2.0,10Base-T/100Base-TX/1000Base-T**
- Supported OS Std: **Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows Server 2008 R2, Windows 7 Mac OS X 10.4.11,10.5 - 10.5.8,10.6 - 10.6.8,10.7 - 10.7.4**
- Network protocols:  
**TCP/IP, IPX/SPX (NetWare), EtherTalk (AppleTalk), IPv6**
- Printing protocols: **LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, Novell Printserver application with NDS and Bindery, FPT for downloading print files, EtherTalk printing, IPP**
- PDL Std/Opt: **Std PCL6, True Adobe PostScript 3 Opt XPS**
- Available fonts: **80 (PCL), 136 (PS3)**

## FINISHING

- Output Capacity: **4000**
- Staple Capacity (sheets) Max.: **100**
- Saddle Stitch: **OPT**
- Off-set shifting: **STD**
- Hole punch: **OPT**
- GBC Punch: **OPT**
- Inserter: **OPT**
- Folding unit: **OPT**