MX-B468P

Highly productive entry-level black & white business printer.



- A4 black & white printer with speeds of up to 44ppm and true 1200 x 1200 dpi printing
- Wireless connectivity enables easy access from mobile devices and flexible printer placement (option)
- Multi-layered security features keep information safe in the document, on the device, and over the network. Plus a range of embedded features strenthen the device against attacks
- Trusted Platform Module (option) delivers authentication, system integrity checks, and encrypt
- Versatile paper handling; supports a wide variety of paper including cardstock, envelopes and small media

- Easily configure and monitor vital system information via the 2.4-inch colour LCD
- Printing from mobile devices made easy with AirPrint
- Compact footprint with an expandable configuration with paper capacity of up to 2,000 sheets
- Energy management features reduce power consumption in active use or sleep mode



Specifications

GENERAL

Technology Laser Engine speed: A4 B/W (ppm) 44 Paper size: Min.-Max. A6 - A4 Paper weight (g/m²) 60 - 216 Paper capacity: Std. (sheets) 350 Paper capacity: Max. (sheets) 2000 Memory: Std. (MB) 512 Harddisk OPT Harddisk capacity (GB) 128GB ISD Duplex STD Power requirements - rated local AC voltage 220-240v

(Hz)

Power consumption (kW) 0.509 Dimensions (mm) 399 x

 Dimensions (mm)
 399 x 390 x 264

 Weight (kg)
 13.5

WIRELESS LAN

Wireless LAN (Standard / Option) OPT

 Compliant regulation
 IEEE802.11a/ac/b/g/n

 Access mode
 Infrastructure Mode, Wi-Fi Direct

 Security
 WEP, WPA PSK, WPA EAP, WPA2

 PSK, WPA2 EAP. WPA3

NETWORK PRINTER

 Resolution (dpi)
 1200 x 1200

 Interface: Std.
 STD: USB2.0 10Base-T / 100Base-TX

/ 1000Base-T

Supported OS: Std. Windows 8.1, 10, 11, Windows

Server 2012R2, Server 2016, Server 2019, Server 2022, Mac OS 10.15,

11, 12

PDL emulation PCL5e / PCL6 emulation, PostScript

3 emulation

Available fonts 94 fonts for PCL, 163 fonts for

PostScript 3 emulation

TONER YIELD

Black (pages at 5% coverage) 31000



