

CE EMC TEST REPORT

REPORT NO.: CE110222D03

MODEL NO.: P462-G1(C), L460U6

RECEIVED: Feb. 22, 2011

TESTED: Feb. 25 ~ Mar. 9, 2011

ISSUED: Mar. 15, 2011

APPLICANT: TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

ADDRESS: 10F., No. 230, Liancheng Rd., Zhonghe City, Taipei
County 23553, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan

This test report consists of 89 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Table of Contents

RELEASE CONTROL RECORD.....	5
1 CERTIFICATION.....	6
2 SUMMARY OF TEST RESULTS.....	7
2.1 MEASUREMENT UNCERTAINTY	8
3 GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT.....	9
3.2 DESCRIPTION OF TEST MODES.....	10
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	12
3.4 DESCRIPTION OF SUPPORT UNITS.....	13
3.4.1 FOR EMISSION TEST	13
3.4.2 FOR HARMONICS / FLICKER / IMMUNITY TEST	16
4 EMISSION TEST.....	17
4.1 CONDUCTED EMISSION MEASUREMENT	17
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	17
4.1.2 TEST INSTRUMENTS	18
4.1.3 TEST PROCEDURE	18
4.1.4 DEVIATION FROM TEST STANDARD	19
4.1.5 TEST SETUP	19
4.1.6 EUT OPERATING CONDITIONS.....	19
4.1.7 TEST RESULTS (1)	20
4.1.8 TEST RESULTS (2)	22
4.2 RADIATED EMISSION MEASUREMENT	24
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	24
4.2.2 TEST INSTRUMENTS	25
4.2.3 TEST PROCEDURE	26
4.2.4 DEVIATION FROM TEST STANDARD	27
4.2.5 TEST SETUP	28
4.2.6 EUT OPERATING CONDITIONS.....	28
4.2.7 TEST RESULTS (1)	29
4.2.8 TEST RESULTS (2)	33
4.3 HARMONICS CURRENT MEASUREMENT	37
4.3.1 LIMITS OF HARMONICS CURRENT MEASUREMENT.....	37
4.3.2 TEST INSTRUMENTS	37
4.3.3 TEST PROCEDURE	38
4.3.4 DEVIATION FROM TEST STANDARD	38
4.3.5 TEST SETUP	39
4.3.6 EUT OPERATING CONDITIONS.....	39
4.3.7 TEST RESULTS.....	40
4.4 VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT	41
4.4.1 LIMITS OF VOLTAGE FLUCTUATION AND FLICKS.....	41
4.4.2 TEST INSTRUMENTS	41
4.4.3 TEST PROCEDURE	41
4.4.4 DEVIATION FROM TEST STANDARD	42



4.4.5	TEST SETUP	42
4.4.6	EUT OPERATING CONDITIONS.....	42
4.4.7	TEST RESULTS.....	43
5	IMMUNITY TEST	44
5.1	GENERAL DESCRIPTION.....	44
5.2	GENERAL PERFORMANCE CRITERIA DESCRIPTION	45
5.3	PARTICULAR PERFORMANCE CRITERIA DESCRIPTION FOR DATA DISPLAY FUNCTION OF EUT	46
5.4	EUT OPERATING CONDITION	46
5.5	ELECTROSTATIC DISCHARGE IMMUNITY TEST (ESD).....	47
5.5.1	TEST SPECIFICATION	47
5.5.2	TEST INSTRUMENTS	47
5.5.3	TEST PROCEDURE	47
5.5.4	DEVIATION FROM TEST STANDARD	48
5.5.5	TEST SETUP	49
5.5.6	TEST RESULTS.....	50
5.6	RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD IMMUNITY TEST (RS).....	51
5.6.1	TEST SPECIFICATION	51
5.6.2	TEST INSTRUMENTS	52
5.6.3	TEST PROCEDURE	53
5.6.4	DEVIATION FROM TEST STANDARD	53
5.6.5	TEST SETUP	53
5.6.6	TEST RESULTS.....	54
5.7	ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST (EFT)	55
5.7.1	TEST SPECIFICATION	55
5.7.2	TEST INSTRUMENTS	55
5.7.3	TEST PROCEDURE	55
5.7.4	DEVIATION FROM TEST STANDARD	55
5.7.5	TEST SETUP	56
5.7.6	TEST RESULTS.....	57
5.8	SURGE IMMUNITY TEST.....	58
5.8.1	TEST SPECIFICATION.....	58
5.8.2	TEST INSTRUMENTS	58
5.8.3	TEST PROCEDURE	59
5.8.4	DEVIATION FROM TEST STANDARD	59
5.8.5	TEST SETUP	59
5.8.6	TEST RESULTS.....	60
5.9	IMMUNITY TO CONDUCTED DISTURBANCES INDUCED BY RF FIELDS (CS).....	61
5.9.1	TEST SPECIFICATION	61
5.9.2	TEST INSTRUMENTS	62
5.9.3	TEST PROCEDURE	63
5.9.4	DEVIATION FROM TEST STANDARD	63
5.9.5	TEST SETUP	64
5.9.6	TEST RESULTS.....	65
5.10	POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST	66



A D T

5.10.1	TEST SPECIFICATION	66
5.10.2	TEST INSTRUMENTS	66
5.10.3	TEST PROCEDURE	66
5.10.4	DEVIATION FROM TEST STANDARD	66
5.10.5	TEST SETUP	67
5.10.6	TEST RESULTS.....	68
5.11	VOLTAGE DIP/SHORT INTERRUPTIONS/VOLTAGE VARIATIONS (DIP) IMMUNITY TEST	69
5.11.1	TEST SPECIFICATION	69
5.11.2	TEST INSTRUMENTS	69
5.11.3	TEST PROCEDURE	69
5.11.4	DEVIATION FROM TEST STANDARD	69
5.11.5	TEST SETUP	70
5.11.6	TEST RESULTS.....	71
6	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	72
7	APPENDIX - INFORMATION ON THE TESTING LABORATORIES.....	89



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	N/A	Mar. 15, 2011

1 CERTIFICATION

PRODUCT: LCD Monitor

BRAND NAME: NEC

MODEL NO.: P462-G1(C), L460U6

APPLICANT: TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

TEST ITEM: ENGINEERING SAMPLE

TESTED: Feb. 25 ~ Mar. 9, 2011

STANDARDS: EN 55022: 2006+A1: 2007, Class B

CISPR 22: 2005+A1: 2005, Class B

AS/NZS CISPR 22: 2006, Class B

EN 61000-3-2: 2006+A1: 2009+A2: 2009, Class D

EN 61000-3-3: 2008

EN 55024: 1998+A1: 2001+A2: 2003

IEC 61000-4-2: 2008 ED.2.0

IEC 61000-4-3: 2006+A1: 2007 ED.3.0

IEC 61000-4-4: 2004+A1: 2010 ED.2.0

IEC 61000-4-5: 2005 ED.2.0

IEC 61000-4-6: 2008 ED.3.0

IEC 61000-4-8: 2009 ED.2.0

IEC 61000-4-11: 2004 ED.2.0

The above equipment (model: P462-G1(C)) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Albee Chu, **DATE:** Mar. 15, 2011
(Albee Chu / Specialist)

APPROVED BY : Kenny Meng, **DATE:** Mar. 15, 2011
(Kenny Meng / Assistant Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

EMISSION			
Standard	Test Type	Result	Remarks
EN 55022: 2006 +A1: 2007, Class B	Conducted Test	PASS	Meets Class B Limit Minimum passing margin is -16.66 dB at 0.150 MHz
CISPR 22: 2005 +A1: 2005, Class B AS/NZS CISPR 22: 2006, Class B	Radiated Test (30MHz ~ 6GHz)	PASS	Meets Class B Limit Minimum passing margin is -4.12 dB at 185.63 MHz
EN 61000-3-2: 2006 +A1: 2009+A2: 2009, Class D	Harmonic current emissions	PASS	Meets Class D Limited
EN 61000-3-3: 2008	Voltage fluctuations & flicker	PASS	Meets the requirements.

IMMUNITY (EN 55024: 1998+A1: 2001+A2: 2003)			
Standard	Test Type	Result	Remarks
IEC 61000-4-2 : 2008 ED.2.0	Electrostatic discharge immunity test	PASS	Meets the requirements of Performance Criterion B
IEC 61000-4-3: 2006 +A1: 2007 ED.3.0	Radiated, radio-frequency, electromagnetic field immunity test	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-4: 2004 +A1: 2010 ED.2.0	Electrical fast transient / burst immunity test.	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-5: 2005 ED.2.0	Surge immunity test	PASS	Meets the requirements of Performance Criterion B
IEC 61000-4-6: 2008 ED.3.0	Immunity to conducted disturbances, induced by radio-frequency fields	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-8: 2009 ED. 2.0	Power frequency magnetic field immunity test.	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-11:2004 ED.2.0	Voltage dips, short interruptions and voltage variations immunity tests	PASS	Meets the requirements of Voltage Dips: i) >95% reduction – Performance Criterion A ii) 30% reduction – Performance Criterion A Voltage Interruptions: i) >95% reduction – Performance Criterion C

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

"This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2."

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	3.43 dB
Radiated emissions	30MHz ~ 1GHz	3.78 dB
	Above 1GHz	2.76 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	LCD Monitor
MODEL NO.	P462-G1(C), L460U6
POWER SUPPLY	Internal Switching Power Supply AC I/P: 100-240V, 50/60Hz Power Cord Non-shielded AC 3-pin (3 m).
DATA CABLE SUPPLIED	Shielded DVI cable (1.8 m) with two ferrite cores Shielded D-Sub cable (4 m) with two ferrite cores Shielded HDMI cable (1.8 m) Shielded BNC to D-Sub cable (1.8 m) with two ferrite cores

NOTE:

- The EUT is a LCD Monitor with resolution up to 1920 x 1080. And it has two models , which are identical with each other, except for marketing difference only, as the following:

Model no.	Difference
P462-G1(C)	Marketing difference
L460U6	

During the test, the **model no.: P462-G1(C)** was selected as the representative one and therefore only its test data was recorded in this report.

- The EUT is equipped the following interfaces:

Input		Output	
♦ DVI	♦ LAN (RJ-45)	♦ RS-232	♦ Video (BNC)
♦ D-Sub	♦ RGB/HV (BNC)	♦ DVI	♦ External Audio x 2
♦ Display	♦ Video (BNC)	♦ Display	♦ Remote (IR control)
♦ RS-232	♦ Audio x 3	♦ Audio	
♦ HDMI	♦ Remote (IR control)		
♦ S-Video			
Accessory			
Remote controller (NEC/ RU-M117)			
Speaker 1 (NEC/ SP-P4046)			
Speaker 2 (NEC/ SP-RM1)			

- For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

3.2 DESCRIPTION OF TEST MODES

1. The EUT is designed with AC power supply of 100-240Vac, 50/60Hz.
For radiated emission evaluation, 230Vac/ 50Hz (for EN 55022), 240Vac/50Hz (for AS/NZS CISPR 22), 120Vac/ 60Hz (for FCC Part 15), 110Vac/ 60Hz (for BSMI CNS 13438), 100V/ 50Hz (for VCCI) had been covered during the pre-test. The worst radiated emission data was founded at **110Vac/ 60Hz** and recorded in the applied test report.
2. The EUT was pre-testing under the following resolution & refresh rate modes

Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
DVI	1920 x 1080 (60Hz)	♦ Speaker 1 ♦ Speaker 2	♦ Horizontal ♦ Vertical	♦ w./ plastics frame ♦ w./o plastics frame

3. The worst emission level was found under following mode:

Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
DVI	1920 x 1080 (60Hz)	Speaker 2	Horizontal	w./ plastics frame

4. Therefore the EUT was pre-testing other interfaces as the following:

Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
♦ D-Sub ♦ Display ♦ HDMI to DVI ♦ D-Sub to RGBHV	1920 x 1080 (60Hz)	Speaker 2	Horizontal	w./ plastics frame

5. Per evaluation **D-Sub to RGBHV** produced worst emission level and therefore the EUT was pre-testing under the following resolution & refresh rate modes:

Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
D-Sub to RGBHV	1920 x 1080 (60Hz)	Speaker 2	Horizontal	w./ plastics frame
	1600 x 1200 (60Hz)			
	1360 x 768 (60Hz)			
	1280 x 1024 (60Hz)			
	1280 x 720 (60Hz)			
	1024 x 768 (60Hz)			
	800 x 600 (60Hz)			
	640 x 480 (60Hz)			
HDMI	1080p			
AV	-			
S-Video	-			

The worst emission level was found under following mode:

Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
D-Sub to RGBHV	1920 x 1080 (60Hz)	Speaker 2	Horizontal	w./ plastics frame

6. Therefore EUT was tested under following mode:

For Conducted & Radiated tests:

Test Mode	Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
Mode 1	D-Sub to RGBHV	1920 x 1080 (60Hz)	Speaker 2	Horizontal	w./ plastics frame
Mode 2	HDMI	1080p			

For Harmonic, Flicker & Immunity tests:

Test Mode	Interface	Resolution	Speaker	Panel's Angle	Outer Appearance
Mode 1	D-Sub to RGBHV	1920 x 1080 (60Hz)	Speaker 2	Horizontal	w./ plastics frame

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of ITE equipment and, according to the specifications of the manufacturers, must comply with the requirements of the following standards:

EN 55022: 2006+A1: 2007, Class B

CISPR 22: 2005+A1:2005, Class B

AS/NZS CISPR 22: 2006, Class B

EN 61000-3-2: 2006+A1: 2009+A2: 2009, Class D

EN 61000-3-3: 2008

EN 55024: 1998+A1: 2001+A2: 2003

IEC 61000-4-2: 2008 ED.2.0

IEC 61000-4-3: 2006+A1: 2007 ED.3.0

IEC 61000-4-4: 2004+A1: 2010 ED.2.0

IEC 61000-4-5: 2005 ED.2.0

IEC 61000-4-6: 2008 ED.3.0

IEC 61000-4-8: 2009 ED.2.0

IEC 61000-4-11: 2004 ED.2.0

Notes: The above IEC basic standards are applied with latest version if customer has no special requirement

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


3.4.1 FOR EMISSION TEST

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PERSONAL COMPUTER	DELL	INSPIRON 518	9TPPY1S	FCC DoC Approved
2	VGA CARD	DELL	B382	911D128824	FCC DoC Approved
3	PERSONAL COMPUTER	HP	dx7300MT	SGH72102ND	FCC DoC Approved
4	VGA CARD	DELL	X300SE	260631006297	FCC DoC Approved
5	LCD MONITOR	DELL	U2410	CN082WXD728 720CC10NL	FCC DoC Approved
6	DVD player	Pioneer	DV-600AV-S	HCKD012042LS	Verification
7	EXTERNAL USB 1.1 FLOPPY	SONY	MPF82E	50010131	FCC DoC Approved
8	PRINTER	EPSON	LQ-300+	DCGY017066	FCC DoC Approved
9	EARPHONE	PHILIPS	SBC HL145	N/A	N/A
10	USB Keyboard	DELL	SK8115	MT-0J4635-716 19-4AQ-0478	FCC DoC Approved
11	PS/2 KEYBOARD	HP	KB-0316	BC3520BGAUJ 028	FCC DoC Approved
12	USB MOUSE	MICROSOFT	X800898	9241595-30608	FCC DoC Approved
13	PS/2 MOUSE	BTC	M851	N/A	E5XMSM860
14	IR	NEC	KT-RC	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	4 m Shielded D-Sub cable with two ferrite cores (provided by client); 1.8 m Shielded Display cable
2	N/A
3	1.8 m Shielded DVI cable with two ferrite cores (provided by client); 1.8 m Shielded BNC to D-Sub cable with two ferrite cores (provided by client); 1.8 m Shielded RS-232 cable; 1.8 m Shielded Audio cable
4	N/A
5	1.8 m Shielded DVI cable with two ferrite cores; 1.8 m Shielded Display cable; 1.8 m Shielded AV cable
6	1.8 m Shielded Audio cable; 1.8 m Shielded S-Video cable; 1.8 m Shielded AV cable; 1.8 m Shielded HDMI cable (provided by client)
7	1.5 m shielded cable, terminated with USB connector, with 1 core.
8	1.8m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
9	1.2 m wrapped shielded wire, terminated with 3.5mm phone plug via drain wire, w/o core.
10	1.8 m foil shielded wire, terminated with USB connector via drain wire, w/o core.
11	1.8 m foil shielded wire, terminated with PS/2 connector via metallic frame, w/o core.
12	1.8 m foil shielded wire, terminated with USB connector via drain wire, with 1 core.
13	1.5 m Non shielded wire, terminated with PS/2 connector via drain wire, w/o core.
14	1.8 m Shielded data cable.

- NOTE:** (1) All power cords of the above support units are non-shielded (1.8 m).
(2) The support unit 2 was installed in support unit 1 and the support unit 4 was installed in support unit 3.
(3) The support unit 14 was provided by client.
(4) One RS-232 cable (1.8m) was connected to EUT to form an open loop cable.
(5) One Audio cable (1.8m) was connected to EUT to form an open loop cable.
(6) One LAN cable (1.8m) was connected to the tuner port of EUT to form an open loop cable, which was terminated with a 100 ohm resistor load.

TEST CONFIGURATION




3.4.2 FOR HARMONICS / FLICKER / IMMUNITY TEST

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PERSONAL COMPUTER	HP	dx7300MT	SGH7500R58	FCC DoC Approved
2	DVD player	Pioneer	DV-600AV-S	GJKD006924LS	Verification
3	USB Keyboard	DELL	SK8115	CN-0J4635-716 16-596-0QAU	FCC DoC Approved
4	USB MOUSE	HP	M-UAE96	F93A90AN3V42 GPQ	FCC DoC Approved
5	IR	NEC	KT-RC	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.8 m Shielded Audio cable 1.8 m Shielded D-Sub to BNC cable with two ferrite cores (provided by client);
2	1.8 m Shielded S-Video cable
3	1.8 m shielded wire, terminated with USB connector via drain wire, w/o core.
4	1.8 m shielded wire, terminated with USB connector via drain wire, w/o core.
5	1.8 m Shielded data cable.

NOTE: (1) All power cords of the above support units are non-shielded (1.8 m).
(2) The support unit 5 was provided by client.

Test Configuration



4 EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: EN 55022

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- NOTE:**
- (1) The lower limit shall apply at the transition frequencies.
 - (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 - (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

**A D T**

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	100290	Dec. 21, 2010	Dec. 20, 2011
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	839135/006	Sep. 09, 2010	Sep. 08, 2011
LISN With Adapter (for EUT)	AD10	C00Ada-001	Sep. 09, 2010	Sep. 08, 2011
EMCO-L.I.S.N. (for peripheral)	3825/2	9204-1964	May 28, 2010	May 27, 2011
Software	ADT_Cond_V7.3.7	NA	NA	NA
Software	ADT_ISN_V7.3.7	NA	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C02.01	Jan. 08, 2011	Jan. 07, 2012
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-298	Jan. 24, 2011	Jan. 23, 2012
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-299	Jan. 24, 2011	Jan. 23, 2012

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in Shielded Room No. 2.
 3. The VCCI Site Registration No. C-240.


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


- Turned on the power of all equipment.
- PC ran a test program to enable all functions.
- PC read and wrote messages from HDD and USB Floppy.
- PC sent “H” messages to EUT, and then EUT displayed them on its screen.
- PC sent “H” messages to ext. monitor via EUT, and then monitor displayed them on its screen.
- DVD player sent messages to EUT
- DVD player sent messages to ext. monitor via EUT.
- PC sent messages to printer and printer printed them out.
- PC sent audio signal to earphone via EUT and ext. speaker of EUT.
- Steps c-j were repeated.

4.1.7 TEST RESULTS (1)

TEST MODE	Mode 1	6DB BANDWIDTH	9 kHz
INPUT POWER	230Vac, 50 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	13deg. C, 76% RH, 1015hPa	TESTED BY: Fox Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.41	48.93	-	49.34	-	66.00	56.00	-16.66	-
2	0.216	0.42	42.69	-	43.11	-	62.96	52.96	-19.84	-
3	0.322	0.44	36.44	-	36.88	-	59.66	49.66	-22.77	-
4	1.387	0.67	27.85	-	28.52	-	56.00	46.00	-27.48	-
5	8.156	1.29	30.30	-	31.59	-	60.00	50.00	-28.41	-
6	14.270	1.65	37.34	-	38.99	-	60.00	50.00	-21.01	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



TEST MODE	Mode 1	6dB BANDWIDTH	9 kHz
INPUT POWER	230Vac, 50 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	13deg. C, 76% RH, 1015hPa	TESTED BY: Fox Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.36	48.77	-	49.13	-	66.00	56.00	-16.87	-
2	0.214	0.37	42.63	-	43.00	-	63.06	53.06	-20.06	-
3	0.317	0.39	34.62	-	35.01	-	59.80	49.80	-24.79	-
4	0.431	0.41	32.16	-	32.57	-	57.23	47.23	-24.66	-
5	1.922	0.78	26.69	-	27.47	-	56.00	46.00	-28.53	-
6	14.270	1.40	36.49	-	37.89	-	60.00	50.00	-22.11	-
7	20.430	1.56	32.57	-	34.13	-	60.00	50.00	-25.87	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS (2)

TEST MODE	Mode 2	6DB BANDWIDTH	9 kHz
INPUT POWER	230Vac, 50 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	13deg. C, 76% RH, 1015hPa	TESTED BY: Fox Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.41	47.26	-	47.67	-	65.79	55.79	-18.12	-
2	0.185	0.42	43.22	-	43.64	-	64.25	54.25	-20.62	-
3	0.315	0.44	36.12	-	36.56	-	59.83	49.83	-23.27	-
4	1.387	0.67	29.26	-	29.93	-	56.00	46.00	-26.07	-
5	8.156	1.29	30.55	-	31.84	-	60.00	50.00	-28.16	-
6	14.270	1.65	37.85	-	39.50	-	60.00	50.00	-20.50	-
7	20.434	1.99	32.63	-	34.62	-	60.00	50.00	-25.38	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



TEST MODE	Mode 2	6dB BANDWIDTH	9 kHz
INPUT POWER	230Vac, 50 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	13deg. C, 76% RH, 1015hPa	TESTED BY: Fox Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.36	48.67	-	49.03	-	66.00	56.00	-16.97	-
2	0.213	0.37	42.65	-	43.02	-	63.11	53.11	-20.09	-
3	0.318	0.39	36.70	-	37.09	-	59.76	49.76	-22.67	-
4	1.809	0.75	26.68	-	27.43	-	56.00	46.00	-28.57	-
5	14.270	1.40	36.80	-	38.20	-	60.00	50.00	-21.80	-
6	20.430	1.56	32.39	-	33.95	-	60.00	50.00	-26.05	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: EN 55022

FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 – 230	40	30
230 – 1000	47	37

FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (GHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
1 to 3	76	56	70	50
3 to 6	80	60	74	54

NOTE: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement Range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	Up to 5 times of the highest frequency or 6 GHz, whichever is less

4.2.2 TEST INSTRUMENTS

Frequency Range 30MHz~1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ TEST RECEIVER	ESCS30	847793/022	Apr. 27, 2010	Apr. 26, 2011
CHASE BILOG Antenna	CBL6111C	2765	Apr. 28, 2010	Apr. 27, 2011
CT Turn Table	TT100	CT-0055	NA	NA
CT Tower	AT100	CT-0055	NA	NA
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
ADT RF Switches BOX	EMH-011	08005	Jun. 22, 2010	Jun. 21, 2011
WOKEN RF cable	8D	CABLE-ST6-01	Jun. 22, 2010	Jun. 21, 2011

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in Open Site No. 6.
 3. The VCCI Site Registration No. R-728.
 4. The FCC Site Registration No. 90427.

Frequency Range above 1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum	E4446A	MY46180666	Jul. 22, 2010	Jul. 21, 2011
Agilent Preamplifier	8449B	3008A01924	Jul. 14, 2010	Jul. 13, 2011
Agilent Preamplifier	8449B	3008A02367	Jul. 14, 2010	Jul. 13, 2011
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Jul. 14, 2010	Jul. 13, 2011
Schwarzbeck Horn Antenna	BBHA-9170	BBHA9170190	Sep. 24, 2010	Sep. 23, 2011
Schwarzbeck Horn Antenna	BBHA-9120	D130	May 25, 2010	May 24, 2011
Max Full. Turn Table & Tower	MF7802	MF780208103	NA	NA
Software	ADT_Radiated_V8.7.03.5	NA	NA	NA
SUHNER RF cable	SF106-18	Cable-CH7	Aug. 20, 2010	Aug. 19, 2011

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in Chamber No. 7.
 3. The Industry Canada Reference No. IC 7450E-7.
 4. The FCC Site Registration No. 127748.
 5. The VCCI Site Registration No. G-39

4.2.3 TEST PROCEDURE

<Frequency Range 30MHz ~ 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter-to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:


1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
2. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

4.2.5 TEST SETUP

<Frequency Range 30MHz ~ 1GHz >



<Frequency Range above 1GHz>



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as item 4.1.6


4.2.7 TEST RESULTS (1)

TEST MODE	Mode 1		
FREQUENCY RANGE	30-1000 MHz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120 kHz
ENVIRONMENTAL CONDITIONS	18deg. C, 82% RH, 1018hPa	TESTED BY: Gary CC Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.62	25.37 QP	30.00	-4.63	4.00 H	182	10.70	14.67
2	48.27	24.43 QP	30.00	-5.57	4.00 H	235	14.48	9.95
3	73.52	22.65 QP	30.00	-7.35	4.00 H	283	15.36	7.29
4	111.33	23.81 QP	30.00	-6.19	4.00 H	12	11.95	11.86
5	149.82	23.44 QP	30.00	-6.56	4.00 H	165	11.59	11.85
6	166.40	23.20 QP	30.00	-6.80	4.00 H	265	11.59	11.61
7	185.47	23.56 QP	30.00	-6.44	4.00 H	347	13.41	10.15
8	217.82	21.87 QP	30.00	-8.13	4.00 H	261	9.63	12.24
9	334.16	25.55 QP	37.00	-11.45	2.54 H	25	8.32	17.23
10	427.51	27.27 QP	37.00	-9.73	1.00 H	299	7.18	20.09
11	630.09	29.38 QP	37.00	-7.62	1.00 H	97	3.05	26.33
12	652.45	30.32 QP	37.00	-6.68	1.00 H	35	3.83	26.49
13	748.00	28.62 QP	37.00	-8.38	1.00 H	312	1.52	27.10
14	780.34	31.21 QP	37.00	-5.79	1.00 H	344	4.02	27.19


- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



TEST MODE	Mode 1		
FREQUENCY RANGE	30-1000 MHz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120 kHz
ENVIRONMENTAL CONDITIONS	18deg. C, 82% RH, 1018hPa	TESTED BY: Gary CC Lee	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.59	25.69 QP	30.00	-4.31	1.12 V	138	11.00	14.69
2	55.81	22.57 QP	30.00	-7.43	1.00 V	250	14.85	7.72
3	74.82	25.53 QP	30.00	-4.47	1.54 V	0	17.98	7.55
4	110.59	25.62 QP	30.00	-4.38	1.00 V	295	13.84	11.78
5	145.02	23.46 QP	30.00	-6.54	1.00 V	11	10.64	12.82
6	165.86	25.58 QP	30.00	-4.42	1.00 V	0	13.86	11.72
7	178.13	22.41 QP	30.00	-7.59	1.00 V	19	12.51	9.90
8	185.63	25.88 QP	30.00	-4.12	1.00 V	15	15.72	10.16
9	229.08	20.80 QP	30.00	-9.20	1.00 V	343	7.67	13.13
10	287.34	25.49 QP	37.00	-11.51	1.00 V	1	9.58	15.91
11	630.35	31.59 QP	37.00	-5.41	3.68 V	21	5.26	26.33
12	752.52	28.32 QP	37.00	-8.68	2.21 V	350	1.20	27.12

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.




TEST MODE	Mode 1		
FREQUENCY RANGE	1-6 GHz	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1MHz
ENVIRONMENTAL CONDITIONS	12deg. C, 72% RH, 1021hPa	TESTED BY: Kevin Liao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2249.40	49.40 PK	70.00	-20.60	1.89 H	214	18.19	31.21
2	2249.40	33.98 AV	50.00	-16.02	1.89 H	214	2.77	31.21
3	2987.31	48.64 PK	70.00	-21.36	1.23 H	253	14.52	34.12
4	2987.31	34.36 AV	50.00	-15.64	1.23 H	253	0.24	34.12
5	3736.03	55.97 PK	74.00	-18.03	1.65 H	227	19.18	36.79
6	3736.03	37.58 AV	54.00	-16.42	1.65 H	227	0.79	36.79

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 1		
FREQUENCY RANGE	1-6 GHz	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1MHz
ENVIRONMENTAL CONDITIONS	12deg. C, 72% RH, 1021hPa	TESTED BY: Kevin Liao	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1499.80	48.98 PK	70.00	-21.02	1.09 V	360	20.90	28.08
2	1499.80	43.27 AV	50.00	-6.73	1.09 V	360	15.19	28.08
3	1798.34	53.14 PK	70.00	-16.86	1.74 V	88	23.57	29.57
4	1798.34	30.26 AV	50.00	-19.74	1.74 V	88	0.69	29.57
5	2249.74	53.31 PK	70.00	-16.69	1.10 V	289	22.10	31.21
6	2249.74	36.93 AV	50.00	-13.07	1.10 V	289	5.72	31.21
7	2986.39	51.33 PK	70.00	-18.67	1.78 V	286	17.22	34.11
8	2986.39	34.95 AV	50.00	-15.05	1.78 V	286	0.84	34.11

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.




4.2.8 TEST RESULTS (2)

TEST MODE	Mode 2		
FREQUENCY RANGE	30-1000 MHz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120 kHz
ENVIRONMENTAL CONDITIONS	18deg. C, 82% RH, 1018hPa	TESTED BY: Gary CC Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	48.71	22.76 QP	30.00	-7.24	4.00 H	208	12.94	9.82
2	73.52	22.30 QP	30.00	-7.70	4.00 H	288	15.01	7.29
3	118.86	21.89 QP	30.00	-8.11	4.00 H	38	9.21	12.68
4	143.87	22.91 QP	30.00	-7.09	4.00 H	127	9.86	13.05
5	179.23	23.25 QP	30.00	-6.75	4.00 H	333	13.35	9.90
6	220.45	20.52 QP	30.00	-9.48	4.00 H	329	8.07	12.45
7	258.41	24.49 QP	37.00	-12.51	2.74 H	16	9.28	15.21
8	429.09	27.37 QP	37.00	-9.63	1.00 H	264	7.23	20.14
9	535.78	27.07 QP	37.00	-9.93	1.00 H	288	3.44	23.63
10	678.34	29.72 QP	37.00	-7.28	1.00 H	336	3.08	26.64
11	741.71	31.83 QP	37.00	-5.17	1.00 H	289	4.78	27.05
12	890.56	29.72 QP	37.00	-7.28	1.00 H	347	0.53	29.19

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 2		
FREQUENCY RANGE	30-1000 MHz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120 kHz
ENVIRONMENTAL CONDITIONS	18deg. C, 82% RH, 1018hPa	TESTED BY: Gary CC Lee	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	58.42	25.40 QP	30.00	-4.60	1.00 V	53	18.46	6.94
2	72.83	25.77 QP	30.00	-4.23	1.68 V	39	18.62	7.15
3	110.70	24.28 QP	30.00	-5.72	1.00 V	180	12.49	11.79
4	120.54	24.00 QP	30.00	-6.00	1.00 V	254	11.17	12.83
5	146.49	21.81 QP	30.00	-8.19	1.00 V	78	9.29	12.52
6	178.52	21.57 QP	30.00	-8.43	1.00 V	30	11.67	9.90
7	216.63	22.22 QP	30.00	-7.78	1.00 V	357	10.07	12.15
8	289.17	26.62 QP	37.00	-10.38	1.00 V	58	10.68	15.94
9	531.25	28.09 QP	37.00	-8.91	3.79 V	17	4.63	23.46
10	742.81	30.72 QP	37.00	-6.28	1.39 V	358	3.66	27.06
11	890.13	32.10 QP	37.00	-4.90	2.18 V	348	2.92	29.18


- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



TEST MODE	Mode 2		
FREQUENCY RANGE	1-6 GHz	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1MHz
ENVIRONMENTAL CONDITIONS	12deg. C, 72% RH, 1021hPa	TESTED BY: Kevin Liao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2077.04	55.32 PK	70.00	-14.68	1.44 H	183	24.53	30.79
2	2077.04	40.83 AV	50.00	-9.17	1.44 H	183	10.04	30.79
3	2225.30	56.28 PK	70.00	-13.72	1.65 H	183	25.13	31.15
4	2225.30	41.68 AV	50.00	-8.32	1.65 H	163	10.53	31.15
5	2967.02	54.81 PK	70.00	-15.19	2.21 H	182	20.78	34.03
6	2967.02	45.40 AV	50.00	-4.60	2.21 H	182	11.37	34.03
7	3732.62	57.63 PK	74.00	-16.37	1.82 H	313	20.85	36.78
8	3732.62	38.02 AV	54.00	-15.98	1.82 H	313	1.24	36.78

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 2		
FREQUENCY RANGE	1-6 GHz	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1MHz
ENVIRONMENTAL CONDITIONS	12deg. C, 72% RH, 1021hPa	TESTED BY: Kevin Liao	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2076.96	54.40 PK	70.00	-15.60	1.55 V	222	23.61	30.79
2	2076.96	40.61 AV	50.00	-9.39	1.55 V	222	9.82	30.79
3	2225.27	54.02 PK	70.00	-15.98	1.06 V	142	22.87	31.15
4	2225.27	37.64 AV	50.00	-12.36	1.06 V	142	6.49	31.15
5	2967.04	56.82 PK	70.00	-13.18	1.53 V	201	22.79	34.03
6	2967.04	45.51 AV	50.00	-4.49	1.53 V	201	11.48	34.03
7	3732.74	55.16 PK	74.00	-18.84	1.89 V	226	18.38	36.78
8	3732.74	37.74 AV	54.00	-16.26	1.89 V	226	0.96	36.78

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



4.3 HARMONICS CURRENT MEASUREMENT

4.3.1 LIMITS OF HARMONICS CURRENT MEASUREMENT

TEST STANDARD: EN 61000-3-2

Limits for Class A equipment	
Harmonics Order n	Max. permissible harmonics current A
Odd harmonics	
3	2.30
5	1.14
7	0.77
9	0.40
11	0.33
13	0.21
15<=n<=39	0.15x15/n
Even harmonics	
2	1.08
4	0.43
6	0.30
8<=n<=40	0.23x8/n

Limits for Class D equipment		
Harmonics Order n	Max. permissible harmonics current per watt mAW	Max. permissible harmonics current A
Odd Harmonics only		
3	3.4	2.30
5	1.9	1.14
7	1.0	0.77
9	0.5	0.40
11	0.35	0.33
13	0.30	0.21
15<=n<=39	3.85/n	0.15x15/n

- NOTE:** 1. Class A and Class D are classified according to section 5 of EN 61000-3-2: 2006.
2. According to section 7 of EN 61000-3-2: 2006, the above limits for all equipment except for lighting equipment are for all applications having an active input power > 75 W and no limits apply for equipment with an active input power up to and including 75 W.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
EMC PARTNER EMC Emission Tester	HAR1000-1P	084	Apr. 16, 2010	Apr. 15, 2011
Software	HARCS	NA	NA	NA

- NOTE:** 1. The test was performed in EMS Room No. 1.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. According to IEC 61000-4-7: 2002, the time window shall be synchronized with each group of 10 or 12 cycles (200 ms) for power frequency of 50 or 60Hz.

4.3.3 TEST PROCEDURE

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- b. The classification of EUT is according to section 5 of EN 61000-3-2: 2006.

The EUT is classified as follows:

Class A: Balanced three-phase equipment, Household appliances excluding equipment as Class D, Tools excluding portable tools, Dimmers for incandescent lamps, audio equipment, equipment not specified in one of the three other classes.

Class B: Portable tools. ; Arc welding equipment which is not professional equipment

Class C: Lighting equipment.


Class D: Equipment having a specified power less than or equal to 600 W of the following types: Personal computers and personal computer monitors.

- c. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS

- a. Turned on the power of all equipment.
- b. PC ran a test program to enable all functions.
- c. PC read and wrote messages from HDD.
- d. PC sent “full white screen pattern” messages to EUT, and then EUT displayed them on its screen.
- e. DVD player sent messages to EUT
- f. PC sent audio signal to ext. speaker of EUT.
- g. Steps c-g were repeated.

4.3.7 TEST RESULTS

TEST MODE	Mode 1		
FUNDAMENTAL VOLTAGE/AMPERE	230.3Vrms/ 0.941Arms	POWER FREQUENCY	49.987Hz
POWER CONSUMPTION	204.33W	POWER FACTOR	0.939
ENVIRONMENTAL CONDITIONS	17deg. C, 69%RH, 1021 hPa	TESTED BY: Yuenyang Lin	

Harm. Order	Iavg (A)	Iavg Limit (A)	I _{max} (A)	I _{max} Limit (A)	Harm. Order	Iavg (mA/W)	Iavg Limit (mA/W)	I _{max} (mA/W)	I _{max} Limit (mA/W)
1	0.9100	-	0.9119	-	1	4.4536	-	4.4629	-
3	0.2439	2.3000	0.2449	3.4500	3	1.1937	3.4000	1.1986	5.1000
5	0.0319	1.1400	0.0323	1.7100	5	0.1561	1.9000	0.1581	2.8500
7	0.0406	0.7700	0.0408	1.1550	7	0.1987	1.0000	0.1997	1.5000
9	0.0000	0.4000	0.0046	0.6000	9	0.0000	0.5000	0.0225	0.7500
11	0.0070	0.3300	0.0072	0.4950	11	0.0343	0.3500	0.0352	0.5250
13	0.0119	0.2100	0.0121	0.3150	13	0.0582	0.2962	0.0592	0.4442
15	0.0100	0.1500	0.0100	0.2250	15	0.0489	0.2567	0.0489	0.3850
17	0.0000	0.1324	0.0055	0.1985	17	0.0000	0.2265	0.0269	0.3397
19	0.0000	0.1184	0.0045	0.1776	19	0.0000	0.2026	0.0220	0.3039
21	0.0057	0.1071	0.0059	0.1607	21	0.0279	0.1833	0.0289	0.2750
23	0.0000	0.0978	0.0054	0.1467	23	0.0000	0.1674	0.0264	0.2511
25	0.0000	0.0900	0.0038	0.1350	25	0.0000	0.1540	0.0186	0.2310
27	0.0000	0.0833	0.0024	0.1250	27	0.0000	0.1426	0.0117	0.2139
29	0.0000	0.0776	0.0028	0.1164	29	0.0000	0.1328	0.0137	0.1991
31	0.0000	0.0726	0.0033	0.1089	31	0.0000	0.1242	0.0162	0.1863
33	0.0000	0.0682	0.0031	0.1023	33	0.0000	0.1167	0.0152	0.1750
35	0.0000	0.0643	0.0022	0.0964	35	0.0000	0.1100	0.0108	0.1650
37	0.0000	0.0608	0.0023	0.0912	37	0.0000	0.1041	0.0113	0.1561
39	0.0000	0.0577	0.0029	0.0865	39	0.0000	0.0987	0.0142	0.1481

NOTE: Steady state values on AC mains are recorded in the table.

4.4 VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT

4.4.1 LIMITS OF VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT

TEST STANDARD: EN 61000-3-3

TEST ITEM	LIMIT	NOTE
P_{st}	1.0	P_{st} means short-term flicker indicator.
P_{lt}	0.65	P_{lt} means long-term flicker indicator.
$T_d(t)$ (ms)	500	$T_d(t)$ means maximum time that $d(t)$ exceeds 3.3%
d_{max} (%)	4	d_{max} means maximum relative voltage change.
dc (%)	3.3	dc means relative steady-state voltage change

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
EMC PARTNER EMC Emission Tester	HAR1000-1P	084	Apr. 16, 2010	Apr. 15, 2011
Software	HARCS	NA	NA	NA

NOTE: 1. The test was performed in EMS Room No. 1.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. According to IEC 61000-4-7: 2002, the time window shall be synchronized with each group of 10 or 12 cycles (200 ms) for power frequency of 50 or 60Hz.


4.4.3 TEST PROCEDURE

- The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.4.6 EUT OPERATING CONDITIONS

Same as item 4.3.6

4.4.7 TEST RESULTS

TEST MODE	Mode 1		
FUNDAMENTAL VOLTAGE/AMPERE	230.3Vrms/ 0.936 Arms	POWER FREQUENCY	49.987Hz
OBSERVATION PERIOD (Tp)	10 minutes	POWER FACTOR	0.939
ENVIRONMENTAL CONDITIONS	17deg. C, 69%RH, 1021hPa	TESTED BY: Yuenyiang Lin	

TEST PARAMETER	MEASUREMENT VALUE	LIMIT	REMARKS
P _{st}	0.072	1.0	Pass
P _{lt}	0.072	0.65	Pass
T _{d(t)} (ms)	0	500	Pass
d _{max} (%)	0	4	Pass
dc (%)	0	3.3	Pass

NOTE:

- (1) P_{st} means short-term flicker indicator.
- (2) P_{lt} means long-term flicker indicator.
- (3) T_{d(t)} means maximum time that d(t) exceeds 3.3%.
- (4) d_{max} means maximum relative voltage change.
- (5) dc means relative steady-state voltage change.

5 IMMUNITY TEST

5.1 GENERAL DESCRIPTION

Product Standard:	EN 55024: 1998+A1: 2001+A2: 2003	
Basic Standard, specification requirement, and Performance Criteria:	IEC 61000-4-2	Electrostatic Discharge – ESD: 8kV air discharge, 4kV Contact discharge, Performance Criterion B
	IEC 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80-1000 MHz, 3V/m, 80% AM (1kHz), Performance Criterion A
	IEC 61000-4-4	Electrical Fast Transient/Burst - EFT AC Power line: 1kV, DC Power line: 0.5kV Signal line: 0.5kV Performance Criterion B
	IEC 61000-4-5	Surge Immunity Test: 1.2/50 us Open Circuit Voltage, 8 /20 us Short Circuit Current, AC Power Line: line to line 1 kV, line to earth 2kV DC Power Line: line to earth 0.5kV Signal line: 1kV Performance Criterion B
	IEC 61000-4-6	Conducted Radio Frequency Disturbances Test – CS: 0.15-80 MHz, 3Vrms, 80% AM, 1kHz, Performance Criterion A
	IEC 61000-4-8	Power Frequency Magnetic Field Test, 50 Hz, 1A/m, Performance Criterion A
	IEC 61000-4-11	Voltage Dips: i) >95% reduction -0.5 period, Performance Criterion B ii) 30% reduction – 25 period, Performance Criterion C Voltage Interruptions: i) >95% reduction – 250 period, Performance Criterion C

5.2 GENERAL PERFORMANCE CRITERIA DESCRIPTION

According to Clause 7.1 of EN 55024: 1998+A1: 2001+A2: 2003 standard, the following describes the general performance criteria.

CRITERION A	The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
CRITERION B	After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomenon below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state if stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
CRITERION C	Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

5.3 PARTICULAR PERFORMANCE CRITERIA DESCRIPTION FOR DATA DISPLAY FUNCTION OF EUT

CRITERION A	When seen from normal viewing distance, the EUT shall operate with no change beyond the manufacturer's specification, in flicker, color, focus and jitter (except for the power magnetic field test).
CRITERION B	Screen disturbances during the application of the test are permissible.
CRITERION C	Failures which are not self-recovered after removal of the external disturbance, but which can be recovered to normal operation by reset or reboot are permissible.

5.4 EUT OPERATING CONDITION

- Turned on the power of all equipment.
- PC ran a test program to enable all functions.
- PC read and wrote messages from HDD.
- PC sent "H" messages to EUT, and then EUT displayed them on its screen.
- DVD player sent messages to EUT
- PC sent audio signal to ext. speaker of EUT.
- Steps c-g were repeated.

5.5 ELECTROSTATIC DISCHARGE IMMUNITY TEST (ESD)

5.5.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-2
Discharge Impedance:	330 ohm / 150 pF
Discharge Voltage:	Air Discharge : 2kV/ 4kV/ 8kV (Direct) Contact Discharge : 2kV/ 4kV (Direct/Indirect)
Polarity:	Positive & Negative
Number of Discharge:	Air Discharge: Min. 20 times at each test point Contact Discharge: Min. 200 times in total
Discharge Mode:	Single Discharge
Discharge Period:	1 second minimum

5.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
EM Test ESD Simulator	Dito	V0707102251	Mar. 29, 2010	Mar. 28, 2011

NOTE: 1. The test was performed in ESD Room No. 3.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.5.3 TEST PROCEDURE

The discharges shall be applied in two ways:

a. Contact discharges to the conductive surfaces and coupling planes:

The EUT shall be exposed to at least 200 discharges, 100 each at negative and positive polarity, at a minimum of four test points. One of the test points shall be subjected to at least 50 indirect discharges to the center of the front edge of the horizontal coupling plane. The remaining three test points shall each receive at least 50 direct contact discharges. If no direct contact test points are available, then at least 200 indirect discharges shall be applied in the indirect mode. Test shall be performed at a maximum repetition rate of one discharge per second.

b. Air discharges at slots and apertures and insulating surfaces:

On those parts of the EUT where it is not possible to perform contact discharge testing, the equipment should be investigated to identify user accessible points where breakdown may occur. Such points are tested using the air discharge method. This investigation should be restricted to those area normally handled by the user. A minimum of 10 single air discharges shall be applied to the selected test point for each such area.

The basic test procedure was in accordance with IEC 61000-4-2:

- a. Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- b. The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- c. The time interval between two successive single discharges was at least 1 second.
- d. The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the EUT.
- e. Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- f. Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- g. At least ten single discharges (in the most sensitive polarity) were applied to the **Horizontal Coupling Plane** at points on each side of the EUT. The ESD generator was positioned horizontally at a distance of 0.1 meters from the EUT with the discharge electrode touching the **HCP**.
- h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the **Vertical Coupling Plane** in sufficiently different positions that the four faces of the EUT were completely illuminated. The **VCP** (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the EUT.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation



5.5.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	20deg. C, 45%RH, 1023hPa	TESTED BY: Yuenyang Lin	

TEST RESULTS OF DIRECT APPLICATION					
Discharge Level (kV)	Polarity	Test Point	Contact Discharge	Air Discharge	Performance Criterion
2, 4	+/-	1, 2, 3	Note(1)	N/A	A
2, 4, 8	+/-	4 ~ 11	N/A	Note(1)	A
2, 4	+/-	12, 13	N/A	Note(1)	A
8	+/-	12	N/A	Note(2)	B
8	+/-	13	N/A	Note(3)	B
2, 4, 8	+/-	14, 15	N/A	Note(1)	A

Description of test point: Please refer to ESD test photo for representative mark only.

TEST RESULTS OF INDIRECT APPLICATION					
Discharge Level (kV)	Polarity	Test Point	Horizontal Coupling Plane	Vertical Coupling Plane	Performance Criterion
2, 4	+/-	1 ~ 4	Note(1)	Note(1)	A

Description of test point:

1. Left side
2. Right side
3. Front side
4. Rear side

NOTE: (1) There was no change compared with initial operation during the test.

(2) There was flickered disturbance on the screen during the test, but self-recoverable after the test.

(3) There was noise disturbance from ext. speaker of EUT during the test, but self-recoverable after the test.

5.6 RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD IMMUNITY TEST (RS)

5.6.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-3
Frequency Range:	80 MHz - 1000 MHz
Field Strength:	3 V/m
Modulation:	1 kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of fundamental
Polarity of Antenna:	Horizontal and Vertical
Antenna Height:	1.5 m
Dwell Time:	3 seconds



A D T

5.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Signal Generator	E8257D	MY48050465	Jun. 09, 2010	Jun. 08, 2011
PRANA RF Amplifier	AP32DP280	0811-894	NA	NA
AR RF Amplifier	150W1000M3	306601	NA	NA
AR RF Amplifier	35S4G8AM4	0326094	NA	NA
AR RF Amplifier	100S1G4M3	0329249	NA	NA
AR Controller	SC1000M3	305910	NA	NA
Radisense Electric Field Sensor	CTR1001A RadiSense 6	06D00232SN O-02 06D00232SN O39	Jan. 11, 2011	Jan. 10, 2012
Radisense Electric Field Sensor	CTR1002A	08D00016SN O-09	Jul. 09, 2010	Jul. 08, 2011
BOONTON RF Voltage Meter	4232A	10180	Jun. 08, 2010	Jun. 07, 2011
BOONTON Power Sensor	51011-EMC	34152	Jun. 08, 2010	Jun. 07, 2011
BOONTON Power Sensor	51011-EMC	34153	Jun. 08, 2010	Jun. 07, 2011
AR Log-Periodic Antenna	AT6080	0329465	NA	NA
EMCO BiconiLog Antenna	3141	1001	NA	NA
AR High Gain Antenna	AT4002A	306533	NA	NA
AR High Gain Horn Antenna	AT4010	0329800	NA	NA
CHANCE MOST Full Anechoic Chamber (9x5x3m)	Chance Most	RS-002	Feb. 18, 2011	Feb. 17, 2012
Software	ADT_RS_V7.6	NA	NA	NA

NOTE: 1. The test was performed in RS Room No.2.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

3. The transmit antenna was located at a distance of 3.5 meters from the EUT.

5.6.3 TEST PROCEDURE


The test procedure was in accordance with IEC 61000-4-3

- The testing was performed in a fully-anechoic chamber.
- The frequency range is swept from 80 MHz to 1000 MHz with the signal 80% amplitude modulated with a 1kHz sine wave.
- The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to respond, but shall in no case be less than 0,5s.
- The field strength level was 3V/m.
- The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

5.6.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	18deg. C, 64%RH, 1021hPa	TESTED BY: Yuenyang Lin	

Frequency (MHz)	Polarity	Azimuth	Field Strength (V/m)	Observation	Performance Criterion
80 - 1000	V & H	0	3	Note	A
	V & H	90	3		
	V & H	180	3		
	V & H	270	3		

NOTE: There was no change compared with the initial operation during the test.

5.7 ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST (EFT)

5.7.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-4
Test Voltage:	Power Line : 1 kV Signal/Control Line : N/A
Polarity:	Positive & Negative
Impulse Frequency:	5 kHz
Impulse Waveshape :	5/50 ns
Burst Duration:	15 ms
Burst Period:	300 ms
Test Duration:	1 min.

5.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Haefely, EFT Generator	PEFT 4010	154954	Apr. 30, 2010	Apr. 29, 2011
Haefely, Capacitive Clamp	IP4A	155173	NA	NA

NOTE: 1. The test was performed in EFT Room
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.7.3 TEST PROCEDURE

- Both positive and negative polarity discharges were applied.
- The length of the “hot wire” from the coaxial output of the EFT generator to the terminals on the EUT should not exceed 0.5 meter $\pm$ 0.05 meter.
- The duration time of each test sequential was 1 minute.
- The transient/burst waveform was in accordance with IEC 61000-4-4, 5/50ns.

5.7.4 DEVIATION FROM TEST STANDARD

No deviation

5.7.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	18deg. C, 63%RH, 1021hPa	TESTED BY: Yenyiang Lin	

Test Point	Polarity	Test Level (kV)	Observation	Performance Criterion
L1	+/-	1	Note	A
L2	+/-	1	Note	A
PE	+/-	1	Note	A
L1-L2-PE	+/-	1	Note	A

NOTE: There was no change compared with the initial operation during the test.

5.8 SURGE IMMUNITY TEST

5.8.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-5
Wave-Shape:	Combination Wave
	1.2/50 us Open Circuit Voltage
	8 /20 us Short Circuit Current
Test Voltage:	Power Line : 0.5kV/ 1 kV/ 2 kV
Surge Input/Output:	L1-L2, L1-PE, L2-PE
Generator Source	2 ohm between networks
Impedance:	12 ohm between network and ground
Polarity:	Positive/Negative
Phase Angle:	0° /90°/180°/270°
Pulse Repetition Rate:	1 time / 20 sec.
Number of Tests:	5 positive and 5 negative at selected points

5.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
KeyTek, Surge Coupler/Decoupler	E-Class Series 100	9508347	Jun. 29, 2010	Jun. 28, 2011
Coupling Decoupling Network	CDN-UTP8	028	Jul. 05, 2010	Jul. 04, 2011
KeyTek I/O Signal Line Coupler/Decoupler	CM-I/OCD	9907177	NA	NA
Surge Cable	WE-4	SU1Cab-001	NA	NA
Surge Adapter WONPRO	WA-9	SU1ADA-002	NA	NA
Software	E500	NA	NA	NA

- NOTE:** 1. The test was performed in Surge Room.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.8.3 TEST PROCEDURE

a. For EUT power supply:

The surge is to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).

b. For test applied to unshielded unsymmetrically operated interconnection lines of EUT:

The surge is applied to the lines via the capacitive coupling. The coupling / decoupling networks shall not influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).


c. For test applied to unshielded symmetrically operated interconnection / telecommunication lines of EUT:

The surge is applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor cannot be specified. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).

5.8.4 DEVIATION FROM TEST STANDARD

No deviation

5.8.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.8.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	17deg. C, 68%RH, 1021hPa	TESTED BY: Yuenyang Lin	

Voltage (kV)	Test Point	Polarity	Phase Angle				Performance Criterion
			0°	90°	180°	270°	
0.5, 1	L1-L2	+/-	Note(2)	Note(2)	Note(2)	Note(2)	B
0.5, 1, 2	L1-PE	+/-	Note(1)	Note(1)	Note(1)	Note(1)	B
	L2-PE	+/-	Note(1)	Note(1)	Note(1)	Note(1)	B

NOTE: (1) There was noise disturbance from ext. speaker of EUT and flickered disturbance on the screen during the test, but self-recoverable after the test.

(2) There was noise disturbance from ext. speaker of EUT during the test, but self-recoverable after the test.

5.9 IMMUNITY TO CONDUCTED DISTURBANCES INDUCED BY RF FIELDS (CS)

5.9.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-6
Frequency Range:	0.15 MHz - 80 MHz
Field Strength:	3 V _{r.m.s.}
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of fundamental
Coupled Cable:	Power Mains
Coupling Device:	CDN-M3 (3 wires)

5.9.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Signal Generator	SMY01	841104/033	Nov. 23, 2010	Nov. 22, 2011
Digital Sweep Function Generator	8120	984801	NA	NA
AR Power Amplifier	75A250AM 1	312196	NA	NA
FCC Coupling Decoupling Network	FCC-801-M 3-25A	48	Jul. 15, 2010	Jul. 14, 2011
FCC Coupling Decoupling Network	FCC-801-M 3-25A	01022	Feb. 25, 2011	Feb. 24, 2012
FCC Coupling Decoupling Network	FCC-801-M 2-16A	01047	Jul. 15, 2010	Jul. 14, 2011
FISCHER CUSTOM COMMUNICATIONS EM Injection Clamp	FCC-203I	50	NA	NA
FISCHER CUSTOM COMMUNICATIONS Current Injection Clamp	F-120-9A	361	NA	NA
EM TEST Coupling Decoupling Network	CDN M1/32A	306508	Feb. 25, 2011	Feb. 24, 2012
FCC Coupling Decoupling Network	FCC-801-T 8	02038	Feb. 25, 2011	Feb. 24, 2012
FCC Coupling Decoupling Network	FCC-801-T 4	02031	Feb. 25, 2011	Feb. 24, 2012
FCC Coupling Decoupling Network	FCC-801-T 2	02021	Feb. 25, 2011	Feb. 24, 2012
R&S Power Sensor	NRV-Z5	837878/038	Nov. 01, 2010	Oct. 31, 2011
R&S Power Sensor	NRV-Z5	837878/039	Nov. 01, 2010	Oct. 31, 2011
R&S Power Meter	NRVD	837794/040	Nov. 01, 2010	Oct. 31, 2011
Software	ADT_CS_V 7.4.2	NA	NA	NA

NOTE: 1. The test was performed in CS Room No. 1.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.9.3 TEST PROCEDURE

- a. The EUT shall be tested within its intended operating and climatic conditions.
- b. An artificial hand was placed on the hand-held accessory and connected to the ground reference plane.
- c. The test shall be performed with the test generator connected to each of the coupling and decoupling devices in turn, while the other non-excited RF input ports of the coupling devices are terminated by a 50-ohm load resistor.
- d. The frequency range is swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80 % amplitude. The signal is modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or the switch coupling devices as necessary. Where the frequency is swept incrementally, the step size shall not exceed 1 % of the preceding frequency value.
- e. The dwell time of the amplitude modulated carrier at each frequency shall not be less than the time necessary for the EUT to be exercised and to respond, but shall in no case be less than 0,5 s. The sensitive frequencies (e.g. clock frequencies) shall be analyzed separately.
- f. Attempts should be made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.

5.9.4 DEVIATION FROM TEST STANDARD

No deviation

5.9.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	17deg. C, 63%RH, 1021hPa	TESTED BY: Yuenyang Lin	

Frequency (MHz)	Field Strength (V _{r.m.s.})	Cable	Injection Method	Observation	Performance Criterion
0.15 – 80	3	AC power line	CDN-M3	Note	A

NOTE: There was no change compared with the initial operation during the test.

5.10 POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST

5.10.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-8
Frequency Range:	50Hz
Field Strength:	1 A/m
Observation Time:	1 minute
Inductance Coil:	Rectangular type, 1 m x 1 m

5.10.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HAEFELY Magnetic Field Tester	MAG 100.1	083794-06	NA	NA
COMBINOVA Magnetic Field Meter	MFM10	224	Mar. 02, 2011	Mar. 01, 2012

NOTE: 1. The test was performed in EMS Room No. 1.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.10.3 TEST PROCEDURE

- The equipment is configured and connected to satisfy its functional requirements.
- The power supply, input and output circuits shall be connected to the sources of power supply, control and signal.
- The cables supplied or recommended by the equipment manufacturer shall be used. 1 meter of all cables used shall be exposed to the magnetic field.

5.10.4 DEVIATION FROM TEST STANDARD

No deviation

5.10.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The equipment shall be subjected to the test magnetic field by using the induction coil of standard dimension (1 m x 1 m). The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

FLOOR-STANDING EQUIPMENT

The equipment shall be subjected to the test magnetic field by using induction coils of suitable dimensions. The test shall be repeated by moving and shifting the induction coils, in order to test the whole volume of the EUT for each orthogonal direction. The test shall be repeated with the coil shifted to different positions along the side of the EUT, in steps corresponding to 50 % of the shortest side of the coil. The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

5.10.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	19deg. C, 67%RH, 1021hPa	TESTED BY: Yuenyang Lin	

Direction	Field Strength (A/m)	Observation	Performance Criterion
X - Axis	1	Note	A
Y - Axis	1	Note	A
Z - Axis	1	Note	A

NOTE: There was no change compared with the initial operation during the test.

5.11 VOLTAGE DIP/SHORT INTERRUPTIONS/VOLTAGE VARIATIONS (DIP) IMMUNITY TEST

5.11.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-11
Test Duration Time:	Minimum three test events in sequence
Interval between Event:	Minimum ten seconds
Phase Angle:	0°/180°
Test Cycle:	3 times

5.11.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HAEFELY Mains Interference Simulator	PLINE1610	083690-17	Jun 01, 2010	May 31, 2011

- NOTE:** 1. The test was performed in EMS Room No. 1.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.11.3 TEST PROCEDURE

The EUT shall be tested for each selected combination of test levels and duration with a sequence of three dips/interruptions with intervals of 10 s minimum (between each test event). Each representative mode of operation shall be tested. Abrupt changes in supply voltage shall occur at zero crossings of the voltage waveform.

5.11.4 DEVIATION FROM TEST STANDARD

No deviation

5.11.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.11.6 TEST RESULTS

TEST MODE	Mode 1	INPUT POWER	230Vac, 50 Hz & 100Vac, 50 Hz
ENVIRONMENTAL CONDITIONS	19deg. C, 67%RH, 1021hPa	TESTED BY: Yuenyang Lin	


Input Power for testing: 230Vac, 50 Hz			
VOLTAGE % REDUCTION	PERIODS	OBSERVATION	PERFORMANCE CRITERION
>95	0.5	Note (1)	A
30	25	Note (1)	A
>95	250	Note (2)	C

Input Power for testing: 100Vac, 50 Hz			
VOLTAGE % REDUCTION	PERIODS	OBSERVATION	PERFORMANCE CRITERION
>95	0.5	Note (1)	A
30	25	Note (1)	A
>95	250	Note (2)	C


NOTES: (1) There was no change compared with the initial operation during the test.
(2) The EUT reset and the PIP function couldn't auto recover.

6 PHOTOGRAPHS OF THE TEST CONFIGURATION


CONDUCTED EMISSION TEST – For Mode 1




CONDUCTED EMISSION TEST – For Mode 2




RADIATED EMISSION TEST – For Mode 1 (Frequency Range 30MHz ~ 1GHz)




RADIATED EMISSION TEST – For Mode 2 (Frequency Range 30MHz ~ 1GHz)




RADIATED EMISSION TEST – For Mode 1 (Frequency Range above 1GHz)




RADIATED EMISSION TEST – For Mode 2 (Frequency Range above 1GHz)





HARMONICS EMISSION TEST & VOLTAGE FLUCTUATIONS AND FLICKER TEST




ESD TEST



ESD TEST POINT





ESD TEST POINT




ESD TEST POINT



ESD TEST POINT




ESD TEST POINT




ESD TEST POINT




RS TEST




EFT TEST




SURGE TEST



CONDUCTED SUSCEPTIBILITY TEST



POWER-FREQUENCY MAGNETIC FIELDS TEST



VOLTAGE DIPS AND INTERRUPTIONS TEST



7 APPENDIX - INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5.phtml.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Email: service@adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

---END---