

PRELIMINARY DATASHEET



MultiSync® LCD1700M

Display Type:	43,3 cm (17,0 Zoll)
Active Display Area:	33,8 cm x 27,0 cm
Pixel Pitch:	0,264 mm
Viewing Angle:	160° horizontal/160° vertical (contrast ratio 10:1)
Brightness:	200 cd/m²
Contrast Ratio:	200 : 1
Number of Colours:	16,7 million
Optimum Resolutions:	1280 x 1024
Other Resolutions:	1280 x 960; 1152 x 900; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 640 x 480; 720 x 400
Features/Adjust Functions:	Contrast; Brightness; Fine adjust; Colour control; Monitor Info; Language select; Intelligent Power Management (VESA/EPA/NUTEK compliant) disable;
User Controls:	OSM menu
Plug & Play; Asset Management:	VESA DDC1, DDC2B
Horizontal Frequency:	30 – 81 kHz
Vertical Frequency:	56 – 75 Hz
Connectors:	D-Sub 15 pin
USB Functions:	No
VESA Mounting Interface:	Yes; 100 x 100 mm
Kensington Lock:	Yes
Dimensions (WxHxD):	422 x 451 x 208 mm
Audio Functions:	Yes, Speaker
Screen Tilt/Swivel/Rotate:	0° to 25° / 300° / No
Weight:	7,3 kg
Power Supply:	100-240V; 1,2 A
Power Requirements:	54 W max. on mode; < 3,0 W power saving mode
Ambient Temperature (Operat.):	0 to +40 ° C
Ambient Humidity (Operat.):	20-80% (non-condensing)
Safety/Ergonomics:	CE; TÜV GS; TÜV ERGONOMIE; UL/C-UL; ISO 9241-3/-8; TC099; ENERGY STAR; FCC Class B
Warranty LCD:	3 years warranty incl. backlight* 3 years on-site warranty*
Shipping Contents:	User's manual, Power Cord, Audio Cable

- Professional LCD monitor with Wide Viewing Angle TFT display
- Built-in 2x1 W speakers
- VESA mounting interface enables versatile installation
- Ergonomics and safety compliant to state-of-the-art standards

*3years on-site warranty within EU countries, Switzerland, Norway, Liechtenstein and Iceland; with optional exchange or repair and return service
All specifications are subject to change without notice, Status October 2000.