

This is Why



- ► 60" (152,5 CM) DISPLAY FOR PROFESSIONAL 24/7 SIGNAGE
- ▶ 1920 X 1080 PIXELS WITH 700CD/M2
- ► BUILT-IN STEREO SPEAKERS 10 + 10W AND UV2A LCD TECHNOLOGY
- ► CONTRAST 4.000:1
- ▶ LED, EDGE LIT
- ▶ 24 / 7 OPERATION
- ► LANDSCAPE & PORTRAIT INSTALLATION SUPPORT

Amply sized and attractively designed, Sharp's PN-R603 professional LCD monitors have the thin profile, high brightness, and low power consumption to accommodate a wide range of indoor digital signage applications. Exceptionally thin and lightweight, this streamlined monitor makes for easy, eye-pleasing installations and can be counted on for realiable, energy-efficient operation. Thanks to the Edge-lit LED backlighting on the PN-R603; this monitor consumes roughly only 32.5/50% which is less energy than the conventional CCFL-backlight displays.



DISPLAY MODULE DATA

 ▶ Panel Technology: LCD UV2A RGB
▶ Native Resolution (Pixels): 1920 X 1080 ▶ Diagonal Size (inches / cm): 60/152.5

Aspect Ratio: 16:9

▶ Backlight Technology: **EDGE LIT LED**

▶ Brightness (cd/m2): 700 Contrast Ratio: 4000:1 ▶ Display Colours: 1.06b

▶ Response Time (grey to grey avg) ms: 6

▶ Viewing Angle (H/V)0 CR >10: **176/176**

POWER SUPPLY AND OPERATING ENVIRONMENT

▶ Operating Voltage(ACV) / Frequency(Hz): 100 - 240/50-60

▶ Power Consumption (W) (Operating MAX): 200

▶ Power Consumption (W) (Standby): 0.5

▶ Operating Temperature (oC): 0 - 40

▶ Humidity (%): 20 - 80

WEIGHTS AND MEASURES

▶ Bezel Size (L/R) mm: 19 ▶ Bezel Size (U/L) mm: 19

Product Dimensions (W/H/D) mm: 1378 x 794 x 39.4

▶ Product Weight Without Stand (Kg): 32

CONNECTIVITY (AUDIO/VIDEO) INPUT

▶ HDMI: 2 ▶ DVI-I: 1 DisplayPort: 1 ▶ VGA: 1 ▶ Component: 1 Composite: 1 Audio 3.5mm Jack: 2

CONNECTIVITY (CONTROL/SERIAL DATA)

▶ RS232C IN: 1 ▶ RS232C OUT: 1 LAN Port: 1

KEY SPECIFICATIONS

▶ 24/7 Operation Certified: ✓ ▶ Built in Speakers (W): 10 x 10

▶ Computer Input - Plug and Play: ✓

Power Management:

Cabinet Colour: BLACK

▶ Fanless: ✓

▶ Multi-Screen Function - Videowall Mode (Enlarge Feature): ✓

▶ Daisychain (Mirror mode):

▶ Hardware Diagnosis: ▼

▶ Monitor Control Software Support: ✓

SAFETY AND ENVIRONMENT (EUROPE)

▶ CE, CB Report: ✓

▶ Mercury Content (mg): 0

INSTALLATION

Landscape:

Portrait: •

▶ Mounting (VESA/Number of Points/Pitch mm): 6/200mm x 200mm or 4/ 200mm x 200mm

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

▶ DVI-D: 1

DisplayPort: 1

▶ Audio/Headphone 3.5mm Jack: 1

www.sharp.co.uk



SHARP ELECTRONICS (UK) LIMITED 4 FURZEGROUND WAY STOCKLEY PARK

UXBRIDGE, MIDDLESEX UB11 1EZ. TEL. 0208 734 2000