

NEC V191W



16:9 LCD monitor with TN TFT display for office use

- Slim bezel design
- Versatile installation (VESA standard)
- Low power consumption for reduced Total Cost of Ownership (TCO)
- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- Rapid Response Technology (5 ms)

see more.

NEC Display Solutions

Panel Technology	TN TFT
Screen Size [inch/cm]	18.5 / 47.01
Pixel Pitch [mm]	0.300
Viewing Angle [°]	170 horizontal / 160 vertical (typ. at contrast ratio 10:1) 176 horizontal / 170 vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	800:1
Brightness (typ.) [cd/m²]	280
Response Time (typ.) [ms]	5
Colours [Mio.]	16.7
Horizontal Frequency [kHz]	31.5 - 81.0
Vertical Frequency [Hz]	55.0 - 76.0
Optimum Resolution	1366 x 768 at 60 Hz
Supported Resolutions	1360 x 768; 1280 x 1024; 1152 x 864; 1024 x 768; 800 x 600; 720 x 400; 640 x 480
Connectors	Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Brightness; Contrast; EcoMode; Expansion Mode; Language Select; Monitor Information; On-Screen-Display (OSD) lock-out
Safety and Ergonomics	EPEAT Silver™; CE; ERP; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star 5.0; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III
Power Consumption on Mode [W]	21 (typ.)
Stand-by Mode [W]	< 0.5
Power Supply	100-120 V/220-240 V; 0.75 A/0.4 A; integrated power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
Screen Tilt / Swivel / Rotate [°]	-4 to 18
Dimensions (W x H x D) [mm]	445.4 x 335.0 x 193.8
Bezel Width [mm]	17.0
Weight [kg]	3.2
Kensington security slot	yes
Benefits	Rapid Response Technology
Colour Versions	Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA - VGA; User Manual
Warranty	3 years warranty incl. backlight



NEC (UK) Ltd. - Display Solutions Division, NEC House, 1 Victoria Road, London W3 6BL
Phone: +44 (0) 870 0120 1160, Fax : +44 (0) 208 8752 3670