4K digital signage display

PN-HW501

Slim and lightweight digital signage displays

- Make an impact with the 50" display in your retail or corporate environments

- Enhanced and true representation of colour shown from wide colour gamut

- Show and hear content easily with integrated 4K USB media player and speakers

- Slim, sleek and elegant design to suit any setting

- Showcase images and video in detail with 4K Ultra HD resolution (3840 x 2160 pixels)

- Continuous display of content during business operating hours 16/7

- Latest HDMI Connectivity for 4K at 60Hz

- Flexible installation in portrait and landscape

SHARP

Specifications

DISPLAY MODULE DATA

Panel Technology	TFT LCD
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	50 / 125
Aspect Ratio	16:9
Backlight Technology	W-LED / Full Array
Brightness (cd/m2)	350
Contrast Ratio	4000 : 1
Display Colours	1,06 billion
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V)0 CR >10	178 / 178

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 / 50-60
Power Consumption (W) (Operating MAX)	130
Power Consumption (W) (Standby)	0,50
Operating Temperature (oC)	0 - 40
Humidity (%)	20 - 80RH

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	VESA / 4 / 400 x 200

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio RCA R-L	1

KEY SPECIFICATIONS

Built in Speakers (W)	10W + 10W
Computer Input - Plug and Play	•
Power Management	•
Cabinet Colour	Black

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	12 / 12
Bezel Size (U/L) mm	12 / 14
Product Dimensions (W/H/D) mm	1124 x 646 x 69
Product Weight Without Stand (Kg)	13

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
VGA	1
Audio 3.5mm Jack	1
Other	HDMI2.0 / HDCP 2.2 / CEC

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

4K 3840 × 2160 Pixels   HDMI   Cd   A↑G G