

NEC MultiSync C860Q



- Future Ready with Open Modular Intelligence Expansion – upgrade your display by integrating one of Sharp/NEC's options for OPS Slot-in PCs or signal interfaces for content feed and computing.
- Ease of use and operation – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.
- Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.
- Mission-critical 24/7 ready operation – the selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.
- Future-proof signal connectivity and processing – numerous native UHD resolution inputs with 60Hz refresh rate, plus automatic upscaling to UHD for other signals, provide "pixel-free viewing".

Specifications

DISPLAY MODULE DATA

Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	86 / 217
Aspect Ratio	16:9
Brightness (cd/m2)	350, 250 (shipment setting)
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0.364
Viewing Angle (H/V) @ CR >10	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	28

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	230 shipping
Operating Temperature (oC)	0 to 40
Humidity (%)	20 to 80

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 400 (FDMI); 600 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

KEY SPECIFICATIONS

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
24/7 Operation Certified	•
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10W + 10W
Power Management	•
Cabinet Colour	Black
Colour Versions	Optional coloured overframes
Temperature Sensor	•
Brightness Sensor	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	15.3
Bezel Size (U/L) mm	15.3
Product Dimensions (W/H/D) mm	1,928 x 1,099 x 74
Shipping Carton Dimensions (W/H/D) mm	2,157 x 1,290 x 320
Product Weight With Stand (Kg)	57.8
Shipping Weight (Kg)	73.4

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DisplayPort	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

