

NEC MultiSync® EA192M

Order Code: 60003065 (WH), 60003064 (BK)

NEC LCD 19" Commercial Display

The EA192M is an energy saving 19" 5:4 format monitor. It offers LED backlight, DisplayPort connectivity and full adjustability. Low power consumption and low operating costs make the display perfect for use in the professional office environment. Outstanding ergonomic qualities and intelligent features such as the Ambient Light Sensor make it very user-friendly and help to increase productivity.

Ideal for large corporates and medium sized businesses for the standard office use with environmental attention.

DELIVERING GENUINE BENEFITS

Ambient Light Sensor - with Auto Brightness function always sets optimised brightness level according to ambient light and content conditions.

Ergonomic Office - full height adjustability (110 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Green Product Concept - Eco Mode and Carbon Footprint Meter / Carbon Savings Meter, Ambient Light Sensor.

Image display - 19inch 5:4 TN with LED backlight.

Input - Display can be used with two digital (DVI-D, DisplayPort) and one analogue input.

Sustainable Office - low power consumption with LED backlight and ambient light sensor.

Vesa Mount (100 mm) - allows to install the monitor via various mounting solutions, stand has a quick release for faster installations.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



OUTSTANDING PERFORMANCE

- EA192M sets new standard in environmental compatibility. The Ambient Light Sensor serves to increase energy saving even further. It measures the ambient light and adjusts the screen to the optimum brightness automatically without any manual settings being required. The use of recycling plastic for the monitor housing and of mercury-free materials fulfil the demands of the NEC "Green Vision" campaign.
- The connection options ensure leading-edge compatibility. With a DisplayPort, a DVI-D as well as an analogue interface, the NEC MultiSync® EA192M provides outstanding connectivity and the optimum basis for all business applications. The display also features speakers and a headphone socket for comfortable office communication.
- Height adjustment through up to 110 mm and the pivot function allow the screen to be positioned to meet individual needs and ensure a high degree of user-friendliness. Thanks to its ergonomic and ecological characteristics, the monitor has gained TCO 5.0 certification and been awarded the EPEAT Silver Seal.
- The eco-friendly display further extends our comprehensive range for the corporate sector. It helps to reduce running costs throughout the display's entire lifetime and its features make daily operations simpler and more productive. Excellent value for money.



SPECIAL CHARACTERISTICS

19" (5:4) Highly efficient panel with only 2 backlights saves more than 30 % energy, Ambient light sensor for optimized brightness levels, Carbon Footprint Meter, Carbon Savings Meter, ErgoDesign®: Height adjustable stand (110 mm) with 90° Pivot features, NaViSet Administrator 2, NaViSet® and NaViSet® Administrator compatible, sRGB Support, TORO™ Design, Windows 7 compatible, Windows Vista Certified Logo



Energy Efficiency LED backlight technology

Ecological Standards Energy Star 5.0; EPEAT™ Gold (black version); EPEAT Silver; ErP compliant; RoHS compliant

Technical Specification NEC MultiSync® EA192M

DISPLAY	
Panel Technology	W-LED TN TFT
Screen Size [inch/cm]	19 / 48.2
Screen Aspect Ratio	5:4
Pixel Pitch [mm]	0.294
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	170 horizontal / 160 vertical (typ. at contrast ratio 10:1); 176 horizontal / 170 vertical (typ. at contrast ratio 5:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	16.77
SYNCHRONISATION RATE	
Horizontal Frequency [kHz]	30 - 82
Vertical Frequency [Hz]	56 - 75
RESOLUTION	
Optimum Resolution	1280 x 1024 at 60 Hz
Supported	1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
CONNECTIVITY	
Digital	1 x DVI-D (with HDCP); 1 x DisplayPort
Analog	1 x mini D-sub 15 pin
ELECTRICAL	
Power Consumption on Mode [W]	23 (typ.); 16 (Eco Mode 2)
Power Savings Mode [W]	< 0.5
Power Supply	100-120 V/220-240 V; 1 A/0.5 A; integrated power supply
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
ERGONOMICS	
Height adjustable Stand [mm]	110
Screen Tilt [°]	-5 to 20
Screen Tilt / Swivel [°]	-45 to 45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)
MECHANICAL	
Bezel Width [mm]	15
Dimensions (W x H x D) [mm]	408 x 386.4 x 213.9; Without stand: 408 x 338 x 65
Weight [kg]	5.5; Without stand: 3.5
VESA Mounting [mm]	100 x 100
ADDITIONAL FEATURES	
Colour Versions	Silver Front Bezel; White Back Cabinet; Black Front Bezel; Black Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Audio	1W + 1W (De-activateable)
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; DV Mode; EcoMode; Fine Adjust (analog); Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Power-Off Timer; sRGB
Shipping Content	Monitor; Power Cable; CD-ROM; Sales Office List; User Manual Signal Cable: VGA - VGA; DVI-D - DVI-D
Safety and Ergonomics	EPEAT Silver™; EPEAT™ Gold (black version); CE; ErP; TCO 5.0; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star 5.0; FCC Class B; PCT/Gost; UL/C-UL or CSA; ISO 9241-307 (pixel failure class I); MPR II/ MPR III; RoHS
Warranty	3 years warranty incl. backlight