

A3 colour MFP with advanced features for connected teams

MX-3061

Office MFP with enhanced security features and superior functionality for flexible working



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 650 Max 6,300 sheets
- Print Release function gives users the ability to send and store documents on a main MFP for authentication and print out from any networked MFP
- Short warm up time and motion sensor ensure that the device is always ready for immediate operation
- Pages per minute: 30 B/W 30 Colour
- Customisable, tiltable 10.1 inch colour LCD touchscreen with easy UI mode enables intuitive navigation of MFP functions
- Single sign-on brings easy access to public cloud storage services
- OCR allows users to convert scanned documents into editable MS Office files (pptx, xlsx, docx) and searchable PDFs

Specifications

GENERAL

Engine speed: A4 Colour (ppm)	30
Engine speed: A4 B/W (ppm)	30
Engine speed: A3 Colour (ppm)	16
Engine speed: A3 B/W (ppm)	16
Paper size: Min.-Max.	A5 - SRA3
Paper weight (g/m ²)	60 - 300
Paper capacity: Std. (sheets)	650
Paper capacity: Max. (sheets)	6300
Warm Up Time (sec.)	20
Memory general: Min./Max. (MB)	5120
Harddisk	STD
Harddisk capacity (GB)	500
Duplex	STD
Power requirements - rated local AC voltage (Hz)	200 - 240V, 50 / 60Hz
Power consumption (kW)	1.84
Dimensions (mm)	608 x 650 x 834
Weight (kg)	79

DOCUMENT FEEDER

Original capacity (sheets)	100
----------------------------	-----

DOCUMENT FILING

Document filing (Standard / Option)	STD
Document filing capacity: main & custom folders (pages)	20000
Document filing capacity: quick file folder (pages)	10000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick file folder, main folder, custom folder (max. 1000)
Confidential storage	•

FAX

Fax (Standard / Option)	OPT
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3 / G3
Transmission time (sec.)	2
Modem speed (bps)	33600 - 2400
Transmission resolution (dpi)	STD 203.2 x 97.8 dpi / Ultra Fine 406.4 x 391 dpi
Document size: Min.	A5
Document size: Max.	A3
Memory (MB)	1024
Grey scale (levels)	256
Dial registration: rapid/speed dial	2000
Broadcast transmission (Max. destinations)	500

WIRELESS LAN

Wireless LAN (Standard / Option)	STD
----------------------------------	-----

COPIER

Original paper size: Max.	A3
First copy out time: Colour (sec.)	6.7
First copy out time: B/W (sec.)	4.7
E-sort Std.	•
Continuous copy (Max. copies)	9,999
Scan resolution: B/W (dpi)	600 x 600, 600 x 400
Scan resolution: Colour (dpi)	600 x 600
Print resolution (dpi)	1200 x 1200, 600 x 600, 9600 x 600
Gradation: Colour (equivalent levels)	256
Zoom range (%)	25 - 400
Preset copy ratios	10

SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	•
Push scan resolution (dpi)	100, 150, 200, 300, 400, 600
Pull scan resolution (dpi)	75, 100, 150, 200, 300, 400, 600, 50 to 9600
File formats	TIFF, PDF, PDF / A-1a, PDF / A-1b, encrypted PDF, compact PDF, JPEG, XPS, searchable PDF, Microsoft Office (pptx, xlsx, docx), text (TXT), rich text (RTF)
Scan destination: Desktop	•
Scan destination: FTP, Email	•
Scan destination: Network folder	•
Scan destination: USB memory	•

PRINTER

Resolution (dpi)	1200 x 1200, 600 x 600, 9600 x 600
Network Printer (Standard / Option)	STD
Interface: Std./Opt.	USB 2.0, 10Base-T / 100Base-TX / 1000Base-T, Optional secondary LAN support
Supported OS: Std.	Windows Server 2008 / 2008R2 / 2012 / 2012R2 / 2016, Windows 7, 8.1, 10, Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Network protocols	TCP / IP (IPv4 and IPv6)
Printing protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP, SMB, WSD
PDL: Std./Opt.	STD PCL 6 emulation, Adobe® PostScript® 3™
Available fonts	80 (PCL), 139 (Adobe PostScript 3)

FINISHING

Output capacity: Max. (sheets)	500 - 3000
Staple capacity: Max. (sheets)	65
Saddle stitch	OPT
Off-set shifting	STD
Hole punch	OPT

TONER YIELD

Black (pages at 5% coverage)	40000
Cyan (pages at 5% coverage)	24000
Magenta (pages at 5% coverage)	24000
Yellow (pages at 5% coverage)	24000

