

ALLROUND MOBILE PROJECTOR

NEC NP63



Extremely compact, lightweight, stylish and fully automatic projector for ultra mobile presentation.

- Native Resolution: 1024 x 768 (XGA)
- Brightness: 3.000 ANSI Lumens; Weight: 1.7 kg
- Auto Focus, Auto Keystone Correction, Auto Power On and automatic signal detection
- Up to 3.500 hrs lamp life
- Low operating cost and carbon savings meter

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs

Display	1 x 1.4 cm (0.55") DDD DMD Chip (Aspect Ratio 4:3)
Lamp	220 W (170 W Eco Mode)
Lamp Life [hrs]	2500 (3500 Eco Mode)
Brightness ¹	3000 ANSI Lumens (approx. 75% in Eco Mode)
Contrast Ratio ¹	1600:1
Lens	F= 2.2–2.34, f= 20.4–24.5 mm
Diagonal: min. / max. [cm]	84 (33") / 762 (300")
Projection Distance [m]	1.44 – 13.45
Projection Factor	1.8 – 2.16 : 1
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– kHz); Vertical: 50 – 120 Hz
Native Resolution	1024 x 768 (XGA)
Supported Resolutions	1920 x 1080 (HDTV 1080i at 50/60 Hz); 1600 x 1200 (UXGA); 1400 x 1050 (SXGA+); 1280 x 1024 (SXGA); 1024 x 768 (XGA); 832 x 624 (MAC); 800 x 600 (SVGA); 640 x 480 (VGA/MAC); 1280 x 720 (HDTV 720p) compressed; SDTV 480p/576p
ComputerAnalog	Input: 1 x Mini D-sub 15 pin
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x 3.5 mm Stereo Mini Jack; Output: 0.3 W mono speaker
PC Control	Input: 1 x Mini DIN 8 pin (female)
USB	no
Video Signals	PAL / PAL60 / NTSC / SECAM / NTSC 4.43 / PAL-N / PAL-M
Zoom / Focus Adjustment	Manual / Automatic/manual
Optical Zoom	1:1.2 manual
Benefits	6-segment Colour Wheel; Auto Power Start; Automatic and manual vertical Keystone Correction (V= ±40°); Automatic Focus; Automatic Signal Detection; BrilliantColor™ and VIDi technology; Carbon Savings Meter; digital zoom; Direct Power-Off Function; Electric Whiteboard Function; High Altitude Mode; Kensington security slot; Keypad Lock; Off-Timer; OSD with 21 languages; Password Security System; Quick-Start-/ Quick-Power-Off Function; Wall Colour Correction
Remote Control	Aspect Ratio; Automatic Picture Adjustment; Direct Source Select; Freeze-function; Help-function; Lamp Mode Control; Magnify-function; Mute-function; Page Control
Dimensions (W x H x D) [mm]	246 x 72 x 177 (without lens and feet)
Weight [kg]	1.7
Power Supply	200-240 V AC; 50 - 60 Hz
Power Consumption [W]	272 Normal Mode; 212 Eco Mode; 3.7 Network Stand-by Mode
Fan Noise [dB (A)]	32 / 37 (Eco / Normal)
Safety and Ergonomics	CE; TÜV GS; RoHS; Gost-R
Warranty	Projector: 3 years pan-European Premium Service; Lamp: 6 Months, max. 1000 Hrs
Shipping Contents	Projector; IR Remote Control (RD-437E); Mini D-SUB Signal Cable; Power Cord; Soft Case; Users Manual on CD-ROM (8 Languages); Quick Setup Guide (7 Languages); Lens Cap
Optional Accessories	Ceiling Mount Kit (NP02CM); Lamp (NP09LP); Universal Ceiling Mounts (NP01/02/03/04/05UCM)

CE



www.nec-display-solutions.co.uk

NEC (UK) Ltd. - Display Solutions Division, NEC House, 1 Victoria Road, London W3 6BL
Phone: +44 (0) 807 120 1160, Fax : +44 (0) 208 8752 3670