

Direct View LED - FullHD Bundle

Sharp LD-E151-135



High Impact

- Trouble-free installation for wall mounted or freestanding deployments, the mechanical cabinet design makes installation quick and easy.
- Large scale for perfectly detailed imagery completely bezel-less design with high contrast rates deliver an unhindered viewing experience.
- Low-profile integration the super slim and light weight modules align with perfection to create a large digital canvas which integrates unobtrusively into any environment.
- Front serviceable modules with front access to the LED modules, maintenance is easy.
- Slim design with a flush rear profile, LED modules can be integrated very close to the wall with minimal gap necessary due to very low heat emission.

Options

Warranty Extensions

Warranty Extension for Direct View LED (3rd, 3rd to 5th year) Optional Warranty Extension (3rd year and 3rd to 5th year) for dedicated Sharp Direct View LED Screen Solutions

Optional Warranty Extension (3rd year and 3rd to 5th year) for dedicated Sharp Direct View LED Screen Solutions

Warranty Extension for Direct View LED (4th to 5th year) Optional Warranty Extension (4th to 5th year) for dedicated Sharp Direct View LED Screen Solutions

Optional Warranty Extension (4th to 5th year) for dedicated Sharp Direct View LED Screen Solutions

Remote Power Switches

LED-RPS-CL-R Remote Power Switch

Remote Power Switch

LED-RPS-CL-B1 Remote Power Switch (standalone boxed version)

Remote Power Switch (standalone boxed version)

LED-RPS-CL-BL1 Remote Power Switch (standalone boxed version - LAN)

Remote Power Switch (standalone boxed version - LAN)

Value Added Services

Installation Service for Direct View LED Optional Installation Service for dedicated Sharp Direct View LED Screen Solutions

Optional Installation Service for dedicated Sharp Direct View LED Screen Solutions

Installation Supervision for Direct View LED Optional Installation Supervision Service for dedicated Sharp Direct View LED Screen Solutions

Optional Installation Supervision Service for dedicated Sharp Direct View LED Screen Solutions

Site Survey for Direct View LED Optional Site Survey for dedicated Sharp Direct View LED Screen Solutions

Optional Site Survey for dedicated Sharp Direct View LED Screen Solutions

On-site Service for Direct View LED Optional On-site Service for dedicated Sharp Direct View LED Screen Solutions

Optional On-site Service for dedicated Sharp Direct View LED Screen Solutions

Brightness Calibration Service for Direct View LED Optional Brightness Calibration Service for dedicated Sharp Direct View LED Screen Solutions

Optional Brightness Calibration Service for dedicated Sharp Direct View LED Screen Solutions

Preventive Maintenance for Direct View LED Optional Preventive Maintenance Service for dedicated Sharp Direct View LED Screen Solutions

Optional Preventive Maintenance Service for dedicated Sharp Direct View LED Screen Solutions

Pixel Card Service Pack for Direct View LED Optional free of charge Pixel Card Service Pack for dedicated Sharp Direct View LED Screen Solutions

Optional free of charge Pixel Card Service Pack for dedicated Sharp Direct View LED Screen Solutions

Specifications

General

Series	[sharp-ld-e-series-indoor]
Order Code	LDE151-135,LDE151-135-NP (no powerbar)

Display

Aspect Ratio	16:9
Brightness Max. (cd/m ²)	600
Colour Processing	16 bit
Colours (Trill.)	281 trillion
Colour Temperature (K)	3000 - 9500
Contrast Ratio	4000:1
Dimming Capability	256 levels
Frame Rate (Hz)	50/60
LED Driving Method	1/54 dynamic scan
LED Type	SMD (1212)
Lifetime (hrs)	100000 hrs (50% brightness)
[AVLEDSpecificationPixelConfiguration]	3-in-1 SMD (Black)
Pixel Pitch (mm)	1.5
Refresh Rate ≤ (Hz)	3840
Screen Size (inch)	135
Screen Size (cm)	342.9
Viewing Angle (°)	140 horizontal / 140 vertical

Resolution

Number of Pixel Per Card (dot)	96 x 216
Resolution Per m ²	409600
Number of Pixel Per Module (dot)	384 x 216
Resolution	1920 x 1080

Connectivity

Input Control	1 x LAN, 1 x GenLock
Input Video Digital (via controller)	1 x DVI-D, 1 x HDMI, 1 x 3G SDI

Electrical

Power Consumption Max (BTU/h per m ²)	2099
Power Consumption Typ. Normal Use (BTU/h per m ²)	672
Power Consumption Max (W/m ²)	617
Power Consumption Typ. Normal Use (W/m ²)	198
[AVLEDSpecificationTotalPowerConsumptionTypW]	1000
[AVLEDSpecificationTotalPowerConsumptionMaxW]	3125

Mechanical

Module Width (mm)	600
Module Height (mm)	337.5
Module Depth (mm)	29
Bundle Width (mm)	3012
Bundle Height (mm)	1743.5
Bundle Depth (mm)	50
Bundle Height excl. Powerbar (mm)	1699.5
Weight (kg)	150.2
Weight excl. Powerbar (kg)	154.1

Environmental Conditions

Operating Humidity (%)	10 to 80
Operating Temperature (°C)	-20 to 40

Additional Features

Special Characteristics	Single Data Receiving Cards, Single Power Supplies, Flush Surface SMD Design
Certifications	FCC Class A, RoHS, CE, ETL
Warranty	2 years
Material	Aluminum Cabinet
Serviceability	Front Service
Shipping Content	Pixel Card Removal Tool, Powerbar (depending on version), Overframe Kit (5x5), LED Modules (25 Cabinets, 100 Pixel Cards), 5 x 5, Spare Parts Kit, Wall mount (5x5), 1x LED Controller

