


NU-JC Series

NU-JC365B

365 W

The Design Solution



Powerful product features



Guaranteed positive power tolerance (0/+5 %)

9BB 9 busbar technology
Improved reliability
Higher efficiency
Reduced series resistance



Tested and certified
VDE, IEC/EN61215, IEC/EN61730
CE Safety class II, CE
Fire rating class C



High module efficiency 19.73 %
PERC monocrystalline silicon photovoltaic modules



Half-cut cell
Improved shading performance
Lower internal losses
Reduced hot spot risk



Robust product design
PID resistance test passed
Salt mist test passed (IEC61701)
Ammonia test passed (IEC62716)
Dust and sand test passed (IEC60068)

Your solar partner for life



60 years of solar expertise



Linear power output guarantee



Product guarantee



Local support team in Europe



50 million PV modules installed



Tier 1 - BloombergNEF



Energy Solutions

SHARP
Be Original.

* Applicable for modules installed in countries as shown in the guarantee conditions.

Electrical data (STC)

NU-JC365B

Maximum power	P_{max}	365	W_p
Open-circuit voltage	V_{oc}	40.56	V
Short-circuit current	I_{sc}	11.46	A
Voltage at point of maximum power	V_{mpp}	34.18	V
Current at point of maximum power	I_{mpp}	10.68	A
Module efficiency	η_m	19.73	%

STC = Standard Test Conditions: irradiance 1,000 W/m², AM 1.5, cell temperature 25 °C.

Rated electrical characteristics are within ±10 % of the indicated values of I_{sc} , V_{oc} and 0 to +5 % of P_{max} .

Reduction of efficiency from an irradiance change of 1,000 W/m² to 200 W/m² ($T_{module} = 25$ °C) is less than 3 %.

Electrical data (NMOT)

NU-JC365B

Maximum power	P_{max}	273.67	W_p
Open-circuit voltage	V_{oc}	38.44	V
Short-circuit current	I_{sc}	9.29	A
Voltage at point of maximum power	V_{mpp}	31.86	V
Current at point of maximum power	I_{mpp}	8.59	A

NMOT = Nominal Module Operating Temperature: 42.5 °C, irradiance 800 W/m², air temperature of 20 °C, wind speed of 1 m/s.

Mechanical data

Length	1,765 mm
Width	1,048 mm
Depth	35 mm
Weight	21.0 kg

Temperature coefficient

P_{max}	-0.347 %/°C
V_{oc}	-0.263 %/°C
I_{sc}	0.057 %/°C


Limit values

Maximum system voltage	1,000 V DC
Over-current protection	20 A
Temperature range	-40 to 85 °C
Max. mechanical load (snow/wind)	2,400 Pa
Tested snow load (IEC61215 test pass*)	5,400 Pa

Packaging data

Modules per pallet	31 pcs
Pallet size (L × W × H)	1.80 m x 1.13 m x 1.24 m
Pallet weight	Approx. 685 kg

Dimensions (mm)



*Please refer to SHARP's installation manual for details.

General data

Cells	Half-cut cell mono, 166 mm x 83 mm, 9BB, 2 strings of 60 cells in series
Front glass	Anti-reflective high transmissive low iron tempered glass, 3.2 mm
Frame	Anodized aluminium alloy, black
Backsheet	Black
Cable	Ø 4.0 mm ² , length 1,250 mm
Connection box	IP68 rating, 3 bypass diodes
Connector	MC4 (Multi Contact, Stäubli), IP68

Note: Technical data is subject to change without prior notice. Before using SHARP products, please request the latest data sheets from SHARP. SHARP accepts no responsibility for damage to devices which have been equipped with SHARP products on the basis of unverified information. The specifications may deviate slightly and are not guaranteed. Installation and operating instructions are to be found in the corresponding handbooks, or can be downloaded from www.sharp.eu. This module should not be directly connected to a load.