

Digital Signage Display

# NEC MultiSync E558



- Reduced Installation and Operating Costs – highly energy efficient LED backlit display ensures low power consumption, longer backlight lifetime and lighter design.
- Slim Design and Integrated Speakers – the aesthetic design is pleasing to the eye and enables easy, low cost installation.
- Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.
- Standalone operation – the display is designed for straightforward standalone operation due to integrated USB media player, speakers and scheduling functionality.
- Effortless content playback – the integrated USB media player supports various image video file formats for effortless and standalone content playback.

# Specifications

## DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	54.6 / 139
Aspect Ratio	16:9
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0.315
Viewing Angle (H/V)0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	1

## POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 V AC; 50 / 60 Hz
Power Consumption (W) (Operating MAX)	185
Operating Temperature (oC)	0 to 40
Storage Temperature [°C]	-10 to +60
Humidity (%)	10 to 80
Storage Humidity [%]	5 to 85

## INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 200 (FDMI)

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

## ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

## KEY SPECIFICATIONS

### Special Characteristics

Ambient Light Sensor; Audio settings with equalizer; CEC Support; Colour temperature mode; Display Browser Control; Energy saving picture mode; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); Mac and Windows compatible; NaViSet Administrator 2; Powered USB-Port; Retail picture mode; Scheduler; SNMP Support; USB Media Player

### HDR High Dynamic Range

### Limited Manufacturer's Warranty (yrs.)

### Built in Speakers (W)

### Cabinet Colour

### Colour Versions

### Temperature Sensor

### Brightness Sensor

3

10W + 10W

Black

Black Front Bezel, Black Back Cabinet

•

•

## WEIGHTS AND MEASURES

Bezel Size (L/R) mm	12.5
Bezel Size (U/L) mm	13.9
Product Dimensions (W/H/D) mm	1,238.6 x 717.7 x 72

## CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
VGA	1
Component	1
Composite	1
Audio 3.5mm Jack	1

## CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

**4K UHD**

