

NEC MultiSync® PA301W

Order Code: 60002926

NEC LCD 30" Professional Desktop Display

Professional Reference 10-bit P-IPS Performance Desktop Display delivers uncompromising image quality as well as minimising life-cycle environmental impact. Uniting outstanding colour reproduction, class-leading ergonomics, an built-in carbon savings meter, ambient light sensor and true 10-bit P-IPS performance makes it ideal for creative, medical, scientific and engineering professionals.

The ideal display for all creative professionals, designers, photographers, CAD-CAM, video-editing, finance, precision engineering and industrial applications (e.g. NDT) and anyone who cares about their visual work. This innovative display design has won the prestigious iF Design Award 2010.



DELIVERING GENUINE BENEFITS

Future-proof Connectivity - as well as easier support of high resolution, 10-bit P-IPS colour signals is assured with the DisplayPort connector.

Improved Productivity and Reduced Desk Clutter - through easy multi-platform support and input following USB hub. Picture-by-picture allows two different platforms to be simultaneously viewed. A single mouse and keyboard can be switched to the active operating system.

Instant Real-time Visualisation - with the 3D LUT colour emulation and the picture-in-picture function you can simulate accurately different lighting conditions with varying paper colours.

Save Time and Increase Personal Productivity - see reality on your screen and see your creative masterpieces or engineering data precisely as you demand them, with huge 2560x1600 resolution. Precisely as you envisioned them.

Ergonomic Office - full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



OUTSTANDING PERFORMANCE

- **Ergonomic.** Suitable for long and intensive working with 150 mm height adjust and 10-bit P-IPS viewing angle stability for best ergonomics.
- **Colour Space Emulation.** Each input can be assigned independently to the 3D LUT (9x9x9) to define a unique colour space e.g. sRGB, AdobeRGB.
- **Integrated USB Hub** (2 up; 3 down) can be used to attach USB peripherals such as mouse and keyboard. At the same time the 2 up connectors can be assigned to different video inputs (input following), which may be feeding the Picture-in-Picture function. Since the USB standard is supported by various platforms easy support is assured when using simultaneous heterogeneous environment.
- **Cabinet and Stand Design** allow a very reduced packaging footprint compared to similar displays.
- **DisplayPort**, compact and features an built-in locking mechanism, which can be disengaged with a simple button press. Longer cable lengths and 10-bit P-IPS colour support ensure that application flexibility is enhanced.



SPECIAL CHARACTERISTICS

Adjustable power LED (colour and brightness), AmbiBright, Auto Black Level, Auto Brightness, Auto Contrast, AutoBright, CableComp with Sync Continuity Detection, DDC/CI compatible, Digital Uniformity Control (ColorComp), Direct Brightness and Contrast, EcoModes, Integrated USB Hub (2 up; 3 down), NaViSet Administrator 2, NaViSet® and NaViSet® Administrator compatible, OmniColor™: sRGB and 6-Axis-Colour-Control, Outstanding productivity with Picture in Picture, USB hub, DisplayPort connectivity and real-time Colour emulation via 3D LUT, Overdrive, Picture-in-Picture Mode, PiP/PbP, Programmable 3D LUT, Quick release Stand and Handle, Rapid Response Technology, RapidMotion, Self Diagnostics, Smooth gamma with 14-bit Look Up Table and 16-bit processing, TileComp, TileMatrix, TORO™ Design, Viewing Angle Stability, Wide Colour Gamut P-IPS TFT 16:9 display with 10-bit Colour (1 billion colours), Windows 7 compatible



Energy Efficiency Carbon Footprint Meter / Carbon Savings Meter; ECOMode

Ecological Materials Arsenic-free panel module; Efficient mechanical design for minimised packaging; Minimal use of harmful material; Use of post-consumer plastics cabinet design

Ecological Standards ErP compliant; TCO 03

Technical Specification NEC MultiSync® PA301W	
DISPLAY	
Panel Technology	P-IPS
Screen Size [inch/cm]	29.8 / 75.6
Pixel Pitch [mm]	0.251
Brightness (typ.) [cd/m ²]	350
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6 (grey-to-grey); 12 (6 white / black; 6 black / white)
Colours [Billion]	1.074 (10-bit per colour)
Colour Gamut Size / Coverage	98% / 107% Adobe RGB
SYNCHRONISATION RATE	
Horizontal Frequency [kHz]	31.5 - 91.1 and 118.4 (digital)
Vertical Frequency [Hz]	50 - 85
RESOLUTION	
Optimum Resolution	2560 x 1600 at 60 Hz
Supported	2560 x 1440; 1920 x 1080p; 1600 x 1200; 1280 x 1024; 1280 x 960; 1280 x 720p; 1200 x 1920; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 576p; 720 x 480p; 720 x 400; 640 x 480; 640 x 480p
CONNECTIVITY	
Digital	2 x DVI-D; 2 x DisplayPort
ELECTRICAL	
Power Consumption on Mode [W]	90 (typ.); 155 (max.)
Power Supply	100-240 V; integrated power supply
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	30 to 80
ERGONOMICS	
Height adjustable Stand [mm]	150 (Landscape mode)
Screen Tilt / Swivel [°]	-5 to +30; -45 to +45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)
MECHANICAL	
Bezel Width [mm]	22.3 (left and right); 22 (top and bottom)
Dimensions (W x H x D) [mm]	688 x 465 x 302
Weight [kg]	18.8
ADDITIONAL FEATURES	
Colour Versions	Black Front Bezel, Black Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC/CI; EDID Standard; VESA DDC2B
Adjust Functions	Advanced User Menu; Auto Adjust; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Display (OSD) lock-out; PiP; Sharpness; USB
Shipping Content	Monitor; Power Cable; Signal Cable DisplayPort; CD-ROM; Sales Office List; User Manual Signal Cable: DVI-D - DVI-D
Safety and Ergonomics	CE; ErP; TCO 03; TÜV Ergonomics; TÜV GS; C-tick; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 9241-307 (pixel failure class 2); MPR III; PCBC/B-mark; PSB; RoHS
Warranty	3 years warranty incl. backlight