

Projector

Sharp/ NEC PA1505UL



- No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.
- Compact design – a large venue projector with a comparatively small footprint and light weight design.
- Incredible visualisation capabilities – with free tilt and portrait installation capability, unique geometric adjustment, picture in picture, tiling, 3D support and camera based blending/stacking.
- No filter service required – the enhanced sealed optical laser LCD engine allows a filter-free design, IP5X rated against dust ingress, reducing costs whilst maintaining brilliant brightness.
- Impress with vivid colour & contrast – brilliant white and wide colour space with high dynamic contrast supporting HDR10 standard via HDMI interface.

Specifications

PANEL RESOLUTION

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel - / - / •
Native Resolution 1920 x 1200 (WUXGA)

DATA TERMINALS

HDMI •

CONTROL TERMINALS

RS232C (Sub-D) •
LAN •
USB-Host •

COLOUR STANDARDS

720p/1.035i • / -
1.080i/1.080p • / •
1.080/24p •

ACCESSORIES

Remote Control / Owners Manual (CD-ROM) • / •
Power Cable / PC Cable • / -

PC-INPUT

H-Frequency (kHz) analog: 0-0, digital: 15 / 24-153
V-Frequency (Hz) 24 - 120

VIDEO TERMINALS

HDMI •
HDCP Compatible •

AUDIO TERMINALS

Mini Jack (3.5 mm) In/Out •
Via HDMI-Terminal •

PICTURE DATA

Luminance ECO-mode (ANSI Lumen) / 14000 Lm / 15000 Lm Centre
Standard (ANSI Lumen)
Contrast 3000000:1
Projection lamp (W) / Lamp lifetime ECO-Mode 925 / 20000
(h) / Lamplife Standard (h)
Lens built-in / Changeable Lens - / •
Zoom-Lens (Manual/ Motorized) - / •
Lens Shift (H/V) • / •
Keystone (manual/auto) • / -

OTHERS

Dimensions in mm (W x H x D) 599 x 238 x 490 (without lens and feet)
Weight (kg) 28.7

