


Interactive Display

# Sharp LM431



- Best readability – high brightness panel ensures content is readable even in well-lit environments and anti-glare coating avoids distracting reflections.
- Out-of-the-box collaboration – the integrated Android PC features a powerful home screen launcher offering fast and flexible access to a range of pre-installed applications.
- Safe & Secure – latest Android 14 SoC provides a secure operating system which, together with extra security features, meets the highest IT security standards.
- Pen-On-Paper user experience – Zero bonded glass and latest infrared touch technology enable highly accurate and responsive writing and drawing with up to 20 touch points.
- Highly customizable – a variety of settings allow the display to be optimised to meet the needs of different applications, from small meeting and huddle rooms to touch signage and wayfinding.

# Specifications

## DISPLAY MODULE DATA

|                                     |                               |
|-------------------------------------|-------------------------------|
| Panel Technology                    | VA with Direct LED backlights |
| Native Resolution (Pixels)          | 3840 x 2160                   |
| Diagonal Size (inches / cm)         | 43 / 108                      |
| Aspect Ratio                        | 16:9                          |
| Backlight Technology                | LED                           |
| Brightness (cd/m2)                  | 500                           |
| Contrast Ratio                      | 4000:1                        |
| Response Time (grey to grey avg) ms | 8                             |
| Viewing Angle (H/V) 0 CR >10        | 178 / 178                     |
| Colour Depth [bn]                   | 1.07 (8bit + FRC)             |

## POWER SUPPLY AND OPERATING ENVIRONMENT

|  |  |
|--|--|
| Operating Voltage(ACV) / Frequency(Hz) | 100-240 V AC; 50 / 60 Hz                     |
| Power Consumption (W) (Operating MAX)  | 110 shipping                                 |
| Operating Temperature (oC)             | +5 to +35                                    |
| Humidity (%)                           | 20 to 80                                     |
| Power Savings Mode [W]                 | < 0.5 (ECO Standby); < 2 (Networked Standby) |

## INSTALLATION

|   |  |
|---|--|
| Landscape                                 | •  |
| Portrait                                  | •  |
| Mounting (VESA/Number of Points/Pitch mm) | 400 x 400                                      |
| Other                                     | Aluminum alloy (front side); metal (back side) |

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

|                            |   |
|----------------------------|---|
| HDMI                       | 1 |
| USB-C                      | 1 |
| Audio/Headphone 3.5mm Jack | 1 |

## ACCESSORIES

|                   |  |
|-------------------|--|
| Shipping Contents | 2 x Passive Stylus; 2x AAA batteries; Blank Sticker; Bracket for Camera; Cable Clamps; Display; Power Cable; Remote Control; Setup Manual; USB cable; Wireless Adapter |
|-------------------|--|

## KEY SPECIFICATIONS

|                                |  |
|--------------------------------|--|
| Special Characteristics        | CEC Support; HDMI ARC; NaViSet Administrator 2 - free download; OSD rotation for portrait mode; Powered USB Port (65 W); Scheduler |
| Operating Time                 | 18 / 7   |
| Built in Speakers (W)          | 10 W + 10 W  |
| Computer Input - Plug and Play | •  |
| Power Management               | •  |

## WEIGHTS AND MEASURES

|                               |                               |
|-------------------------------|-------------------------------|
| Bezel Size (L/R) mm           | 15                            |
| Bezel Size (U/L) mm           | 15                            |
| Product Dimensions (W/H/D) mm | Without stand: 994 x 582 x 73 |

## CONNECTIVITY (AUDIO/VIDEO) INPUT

|             |   |
|-------------|---|
| HDMI        | 3 |
| USB-C       | 1 |
| DisplayPort | 1 |

## CONNECTIVITY (CONTROL/SERIAL DATA)

|           |   |
|-----------|---|
| RS232C IN | 1 |
| LAN Port  | 1 |
| USB       | 4 |

