Direct View LED - UHD Bundle

Sharp LD-EC121-217



Built to last, designed to inspire

- Reduced operating costs Up to 60% lower power consumption than standard SMD technology at equivalent brightness, with reduced cooling demands.
- Consistent high-contrast image quality A 10000:1 contrast ratio delivers deep blacks and clear detail, ensuring excellent visibility even in bright environments.
- Durability and longevity A sealed, easy-clean surface protects against dust, moisture and projectiles, making it robust for use in high traffic areas.
- Fast and easy installation Established mechanical housing design and front-access modules enable quick, precise installation and simplified servicing.

Options

Warranty Extensions

Warranty Extension for Direct View LED (3rd, 3rd to 5th year) Optional Warranty Extension (3rd year and 3rd to 5th year) for dedicated Sharp Direct View LED Screen Solutions
Optional Warranty Extension (3rd year and 3rd to 5th year) for dedicated Sharp Direct View LED Screen Solutions

Warranty Extension for Direct View LED (4th to 5th year) Optional Warranty Extension (4th to 5th year) for dedicated Sharp Direct View LED Screen Solutions
Optional Warranty Extension (4th to 5th year) for dedicated Sharp Direct View LED Screen Solutions

Remote Power Switches

LED-RPS-CL-R Remote Power Switch
Remote Power Switch

LED-RPS-CL-B1 Remote Power Switch (standalone boxed version)
Remote Power Switch (standalone boxed version)

LED-RPS-CL-BL1 Remote Power Switch (standalone boxed version - LAN)
Remote Power Switch (standalone boxed version - LAN)

Value Added Services

Installation Service for Direct View LED Optional Installation Service for dedicated Sharp Direct View LED Screen Solutions
Optional Installation Service for dedicated Sharp Direct View LED Screen Solutions

Installation Supervision for Direct View LED Optional Installation Supervision Service for dedicated Sharp Direct View LED Screen Solutions
Optional Installation Supervision Service for dedicated Sharp Direct View LED Screen Solutions

Site Survey for Direct View LED Optional Site Survey for dedicated Sharp Direct View LED Screen Solutions
Optional Site Survey for dedicated Sharp Direct View LED Screen Solutions

On-site Service for Direct View LED Optional On-site Service for dedicated Sharp Direct View LED Screen Solutions
Optional On-site Service for dedicated Sharp Direct View LED Screen Solutions

Brightness Calibration Service for Direct View LED Optional Brightness Calibration Service for dedicated Sharp Direct View LED Screen Soluitons
Optional Brightness Calibration Service for dedicated Sharp Direct View LED Screen Soluitons

Preventive Maintenance for Direct VIew LED Optional Preventive Maintenance Service for dedicated Sharp Direct View LED Screen Solutions
Optional Preventive Maintenance Service for dedicated Sharp Direct View LED Screen Solutions

Pixel Card Service Pack for Direct View LED Optional free of charge Pixel Card Service Pack for dedicated Sharp Direct View LED Screen Solutions
Optional free of charge Pixel Card Service Pack for dedicated Sharp Direct View LED Screen Solutions

Specifications

General

Series	[sharp-ld-ec-series-indoor]
Order Code	LDEC121-217,LDEC121-217-NP (no powerbar)

Display

Aspect Ratio	16:9
Brightness Max. (cd/m²)	600
Colour Processing	14 bit
Colour Temperature (K)	3000 - 9500
Contrast Ratio	10000:1
Dimming Capability	256 levels
Frame Rate (Hz)	50/60
LED Driving Method	1/60 dynamic scan
LED Type	FlipChip COB (0407)
Lifetime (hrs)	100000 hrs (50% brightness)
Pixel Pitch (mm)	1.2
Refresh Rate ≤ (Hz)	3840
Screen Size (inch)	217
Screen Size (cm)	551.18
Viewing Angle (°)	160 horizontal / 140 vertical

Resolution

Number of Pixel Per Card (dot)	120 x 135
Resolution Per m²	640000
Number of Pixel Per Module (dot)	480 x 270
Resolution	3840 x 2160

Connectivity

Input Control	1 x LAN
Input Video Digital (via controller)	1 x HDMI

Electrical

Power Consumption Max (BTU/h per m²)	488
Power Consumption Typ. Normal Use (BTU/h per m²)	859
Power Consumption Max (W/m²)	252
Power Consumption Typ. Normal Use (W/m²)	143
[AVLEDSpecificationTotalPowerConsumptionTypW]	1920
[AVLEDSpecificationTotalPowerConsumptionMaxW]	3264

Mechanical

Module Width (mm)	600
Module Height (mm)	337.5
Module Depth (mm)	27.4
Bundle Width (mm)	4812
Bundle Height (mm)	2756
Bundle Depth (mm)	50
Bundle Height excl. Powerbar (mm)	2712
Weight (kg)	360.1
Weight excl. Powerbar (kg)	330.6

Environmental Conditions

Operating Humidity (%)	10 to 80
Operating Temperature (°C)	-10 to 40

Additional Features

Special Characteristics	Single Power Supplies, Single Data Receiving Cards
Certifications	RoHS, FCC Class A, ETL, UKCA, CE
Warranty	2 years
Manufacturer	[sharp]
Material	Aluminum Cabinet
Serviceability	Front Service
Shipping Content	Powerbar (depending on version), 8 x 8, 1x LED Controller, Overframe Kit (8x8), Pixel Card Removal Tool, Spare Parts Kit, Wall mount (8x8), LED Modules (64 Cabinets, 512 Pixel Cards)

4K UHD

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. Sharp LD-EC121-217, 15/10/2026