



MultiSync® LCD1525M/LCD1525M Black

Display Type:	TFT Active Matrix TFT, 15 inch
Active Display Area:	304 x 228 mm
Pixel Pitch:	0.297 x 0.297 mm
Viewing Angle:	120° horizontal/100° vertical (at contrast ratio 10:1)
Brightness:	200 cd/m² typ.
Contrast Ratio:	350:1 typ.
Number of Colours:	16.77 million
Optimum Resolution:	1024 x 768 at 60 Hz
Other Resolutions:	832 x 624, 800 x 600, 720 x 400, 720 x 350, 640 x 480, 640 x 400, 640 x 350
Features/Adjust Functions:	On-Screen Manager (OSM) lock out, contrast, brightness, auto adjust, fine adjust, colour control, monitor info, language select, Intelligent Power Management (VESA/EPA/NUTEK compliant) disable
User Controls:	On/Off, OSM menu, mute
Plug & Play, Asset Management:	VESA DDC1, DDC2B and EDID standard
Horizontal Frequency:	24–60 kHz
Vertical Frequency:	56–75 Hz
Input Connectors:	Mini D-sub 15 pin, analog VGA input
Audio Functions:	Yes, 1 + 1 W max., Headphone jack
USB Functions:	Yes, active USB hub, 2 x upstream, 4 x downstream
VESA Mounting Interface:	Yes, 75 x 75 mm
Kensington Lock:	Yes
Dimensions (W x H x D):	370 x 360 x 158 mm
Screen Tilt/Swivel/Rotate:	–5° to +30°/ –45° to +45°
Weight:	4.5 kg
External Adapter:	100–240 V/0.7/0.4 A, integrated power supply, detachable
Power Requirements:	45 W max. on mode, < 5 W power saving mode (display)
Ambient Temperature (Operat.):	+5 °C to +35 °C
Ambient Humidity (Operating):	30–80% (non-condensing)
Safety/Ergonomics:	CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO 99 (LCD 1525M), TCO 95 (LCD 1525M Black)
Warranty:	3 years warranty, warranty extension programs depending on specific country
Shipping Contents:	Monitor, power cord, VGA signal cable 1.8 m, user manual

- Allround LCD monitor with analog input
- VESA mounting interface enables versatile installation
- Built-in 2 x 1 W speakers
- Active USB hub
- Ergonomics and safety compliant to state-of-the-art standards
- Also available in dark grey housing version (LCD 1525M Black)

All specifications are subject to change without notice. Status June 2000

