

Fieri® ready black & white production print system

# MX-M1205

Effortless efficiency & Fieri® ready for superior control



- High volume production
- Paper capacity: Std 3100 Max 13500
- Large, fully adjustable 15.4" touchscreen featuring Sharp's award-winning integral print server & intuitive touch control of all settings
- One-touch, dedicated Fieri® gateway key for direct touchscreen access to the Fieri® Command WorkStation
- Pages per minute: 120 B/W
- Powerful & durable, Fieri® ready production print system that delivers end-to-end efficiency for maximum productivity & lower operating costs
- Full compatibility with EFI Fieri® workflow & the very latest Fieri® print server as an option
- Extensive finishing options & SRA3 compatibility for professional in-house document production

# Specifications

## GENERAL

Engine speed: A4 B/W (ppm)	120
Engine speed: A3 B/W (ppm)	54
Paper size: Max.-Min.	SRA3 - A5R
Paper weight (g/m <sup>2</sup> )	52 - 300
Paper capacity: Std. (sheets)	3100
Paper capacity: Max. (sheets)	13500
Warm Up Time (sec.)	210
Memory general min/max (GB)	5
Harddisk	STD
Harddisk capacity (GB)	1000
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220-240V, 13A, 50 / 60Hz
Power consumption (kW)	2,99
Dimensions base unit (mm)	1084 x 790 x 1237
Dimensions full configuration (mm)	5982 x 790 x 1551
Weight (kg)	295

## DOCUMENT FEEDER

Original capacity (sheets)	250
Original replacement speed: B/W	120 (simplex)200 (duplex)
Original replacement speed: Colour	120 (simplex)200 (duplex)

## DOCUMENT FILING

Document filing (Standard / Option)	STD
Document filing capacity: main & custom folders (pages)	35000
Document filing capacity: quick file folder (pages)	10000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick file folder, main folder, custom folder (max. 1000)
Confidential storage	.

## FAX

Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3

## TONER YIELD

Black (pages at 6% coverage)	120000
------------------------------	--------

## COPIER

Original paper size: Max.	A3
First copy out time: B/W (sec.)	3,2
E-sort Std.	.
Continuous copy (Max. copies)	9999
Scan resolution: B/W (dpi)	600 x 600
Scan resolution: Colour (dpi)	600 x 600
Print resolution (dpi)	1200 x 1200
Gradation: B/W (equivalent levels)	256
Zoom range (%)	25 - 400
Preset copy ratios	10 (5E / 5R)

## SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	.
Push scan resolution (dpi)	100, 150, 200, 300, 400, 600
Pull scan resolution (dpi)	75, 100, 150, 200, 300, 400, 60050 - 9600
File formats	XPS, PDF, Encrypted PDF, Compact PDF, PDF / A-1b, JPEG, TIFF
Scanner utilities	Sharp OSA Network Scanner Tool
Scan destination: Desktop	.
Scan destination: FTP, Email	.
Scan destination: Network folder	.
Scan destination: USB memory	.

## PRINTER

Network Printer (Standard / Option)	STD
Resolution (dpi)	1200 x 1200
Enhanced resolution (dpi)	1200 x 1200
Interface: Std./Opt.	Std USB 2.0, 10Base-T / 100Base-TX / 1000Base-T
Supported OS: Std.	Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows Server 2008 R2, Windows 7Mac OS X 10.4.11, 10.5 - 10.5.8, 10.6 - 10.6.8, 10.7 - 10.7.4
Network protocols	TCP / IP, IPX / SPX (NetWare), EtherTalk (AppleTalk), IPv6
Printing protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, Novell Printserver application with NDS and Bindery, FPT for downloading print files, EtherTalk printing, IPP
PDL: Std./Opt.	Std PCL6, Genuine Adobe PS3, Opt XPS
Available fonts	80 (PCL), 136 (PS3)

## FINISHING

Output capacity: Max. (sheets)	4000
Staple capacity: Max. (sheets)	100
Saddle stitch	OPT
Off-set shifting	STD
Hole punch	OPT
GBC punch	OPT
Insertter	OPT
Folding unit	OPT

