

NEC MultiSync® LCD1570NX



Fully featured office monitors with outstanding display quality and ergonomic performance.

- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- ErgoDesign®: Height adjustable stand (75 mm)
- Safety of investment with analog/digital interface
- Versatile and easy installation (VESA standard) with NaViSet and NaViKey
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment)

see more.

NEC Display Solutions

[illegible]

Panel Technology	TN+ film TFT
Screen Size [inch/cm]	15 / 38.0
Pixel Pitch [mm]	0.297
Viewing Angle [°]	130 horizontal / 100 vertical (typ. at contrast ratio 10:1) 160 horizontal / 140 vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	450:1
Brightness (typ.) [cd/m²]	250
Response Time (typ.) [ms]	16 (11 white / black; 5 black / white)
Colours [Mio.]	16.2
Horizontal Frequency [kHz]	31.5 - 60.1
Vertical Frequency [Hz]	56 - 75
Optimum Resolution	1024 x 768 at 60 Hz
Supported Resolutions	1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analog); Intelligent Power Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; sRGB
Safety and Ergonomics	CE; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
Power Consumption on Mode [W]	20 (typ.)
Power Consumption Power-Saving Mode [W]	< 2
Power Supply	100-120 V/220-240 V; 0.2 A/0.2 A; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	10 to 80
VESA Mounting [mm]	75 x 75
ErgoDesign®: Height adjustable Stand [mm]	75
Screen Tilt / Swivel [°]	-5 to +30 / -170 to +170
Dimensions (W x H x D) [mm]	336 x 305 x 183
Bezel Width [mm]	15.3
Weight [kg]	3.8
Cable Management	yes
Kensington Lock	yes
Benefits	NaViSet® and NaViSet® Administrator compatible; Rapid Response Technology; sRGB Support
Audio Functions	None
Colour Versions	Silver Front Bezel, Black Back Cabinet Silver Front Bezel, Light Grey Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight



NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU
Phone: 0207 202 6300, e-mail: infomail@nec-displays.com
For further information on NEC products call: 08701 201160