



- ► 60" (152,5 CM) DISPLAY FOR DIGITAL 24/7 SIGNAGE
- ▶ 1920 X 1080 PIXELS WITH 700CD/M2
- FLEXIBLE INSTALLATION WITH MINI-OPS EXTENSION SLOT
- ► CONTRAST 4000:1
- ▶ LED, EDGE LIT
- SLIM BEZEL DESIGN WITH SPEAKERS 10W + 10W
- ▶ PORTRAIT, LANDSCAPE, FACE-UP INSTALLATION SUPPORT
- SHARP UV2A DISPLAY TECHNOLOGY

The Sharp PN-R monitor series have set a new benchmark for mission-critical reliability and flexible extension. These displays have been specially designed for a range of demanding and high brightness 700cd/m2 applications including command and control rooms, 24/7 retail signage, transport signage, way-finding, hospitality, reception areas, lobbies and other corporate and public spaces. With an elegant, slim and discreet cabinet design the latest generation of PN-R Series offers powerful imaging, ease of use, peace-of-mind and convenient stand-alone operation when using the Intel® Mini-OPS capability.

The brand new PN-R 60" (152.5 cm) is designed for demanding high brightness 24/7 display applications and is supported by the flexible Intel® Mini-OPS expansion slot – no need for unsightly cabling when using one of the module options. As an easy-to-use and highly reliable solution with outstanding high-brightness image and sound quality, the PN-R606 sets the ultimate standard for reliable, robust, plug-and-go display signage used anytime and anywhere.

With state-of-the-art high-brightness LED backlight technology, which allows for a new level of slim bezels and shallow cabinet depth, Sharp's 60" PN-R606 display is an attractive and elegant addition to any demanding signage application. With unparalleled reliability, superb durability and straight-forward operation, the monitor can be installed in either portrait or landscape mode, and even suspended from a ceiling for face-up at any tilted angle.

The in-built Daisy Chain capability via the DisplayPort video connection allows up to 5 units to be connected together for the same mirrored display content. Just another reason why Sharp's LCD monitors can be employed to broaden your business potential.

The new Intel® Mini-OPS expansion slot builds on the well-known OPS industry standard by reducing the mechanical format factor and making the most of the energy saving opportunities of Intel's latest generation of lower power chipsets. A range of upgrade modules, include wireless (PN-ZB03W), HDBaseT (PN-ZB03H) and embedded PC controller (PN-ZB03PC) ensures that the PN-R has maximum flexibility and enhanced application range.

DISPLAY MODULE DATA

▶ Panel Technology: LCD UV2A

Native Resolution (Pixels): 1920 x 1080
Diagonal Size (inches / cm): 60/152.5

Aspect Ratio: 16:9

▶ Backlight Technology: Edge LED
 ▶ Brightness (cd/m2): 700

▶ Brightness (cd/m2): 700
▶ Contrast Ratio: 4000:1
▶ Display Colours: 1.07b

► Response Time (grey to grey avg) ms: 8
► Pixel Pitch (mm H/V): 0.692 x 0.692 mm
► Viewing Angle (H/V)0 CR >10: 178/178

POWER SUPPLY AND OPERATING ENVIRONMENT

▶ Operating Voltage(ACV) / Frequency(Hz): 100-240/50-60

▶ Power Consumption (W) (Operating MAX): 190

▶ Operating Temperature (oC): 0 to 40

▶ Humidity (%): 20 to 80

▶ Heat Dissipation (BTU/h) MAX: 648

INSTALLATION

▶ Landscape: ✓

Portrait: 🗸

▶ Horizontal: ✓

▶ Mounting (VESA/Number of Points/Pitch mm): 4/400mm x 400mm

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

DisplayPort: 1

▶ Audio/Headphone 3.5mm Jack: 1

ACCESSORIES

▶ Remote Control Transmitter: STD

▶ Power Cord: STD▶ Mounting Bracket: OPT

KEY SPECIFICATIONS

▶ 24/7 Operation Certified: ✓

Limited Manufacturer's Warranty (yrs.): 3

▶ Built in Speakers (W): 10 x 10

▶ Computer Input - Plug and Play: ✓

▶ Power Management: ✓

▶ Cabinet Colour: BLACK

Fanless:

▶ Temperature Sensor: ✓

▶ Multi-Screen Function - Videowall Mode (Enlarge Feature): ✓

▶ Multi Language OSD: ✓

▶ Daisychain (Mirror mode):

▶ Hardware Diagnosis: ◀

▶ Monitor Control Software Support: ✓

▶ Temperature Control: ∨

WEIGHTS AND MEASURES

▶ Bezel Size (L/R) mm: **10/10**

▶ Bezel Size (U/L) mm: 9.5/14

Product Dimensions (W/H/D) mm: 1352 x 778 x 60

▶ Product Weight Without Stand (Kg): 35

▶ Shipping Weight (Kg): **TBD**

CONNECTIVITY (AUDIO/VIDEO) INPUT

▶ HDMI: 2

▶ DVI-D: 1

DisplayPort: 1

▶ VGA: 1

▶ Component: 1

▶ Audio 3.5mm Jack: 1

CONNECTIVITY (CONTROL/SERIAL DATA)

▶ RS232C IN: 1

▶ RS232C OUT: 1

▶ LAN Port: 1

www.sharp.co.uk



SHARP BUSINESS SYSTEMS UK PLC Northern House Moor Knoll Lane East Ardsley Wakefield, WF3 2EE Tel. 01924 823455