


NU-JC Series

NU-JC415

415 W

The High Performer



Powerful product features



Guaranteed positive power tolerance (0/+5 %)



MBB MBB busbar technology
Improved reliability
Higher efficiency
Reduced series resistance



Tested and certified
VDE, IEC/EN61215, IEC/EN61730
Safety class II, CE
Fire rating class C



High module efficiency 21.25 %
PERC monocrystalline silicon
photovoltaic modules



Half-cut cell
Improved shading performance
Lower internal losses



Robust product design
PID resistance test passed
Salt mist test passed (IEC61701)
Ammonia test passed (IEC62716)
Dust and sand test passed (IEC60068)
Hail resistance class 4 (40 mm hailstone)

Your solar partner for life



60 YEARS 60 years of solar expertise



25 YEARS Linear power output guarantee



12* YEARS Product guarantee



Local support team in Europe



50 MIL 50 million PV modules installed



1 TIER Tier 1 - BloombergNEF



Energy Solutions

SHARP
Be Original.

* Applicable for modules installed in countries as shown in the guarantee conditions.

Electrical data (STC)

NU-JC415			
Maximum power	P_{max}	415	W_p
Open-circuit voltage	V_{oc}	38.08	V
Short-circuit current	I_{sc}	13.87	A
Voltage at point of maximum power	V_{mpp}	31.49	V
Current at point of maximum power	I_{mpp}	13.18	A
Module efficiency	η_m	21.25	%

STC = Standard Test Conditions: irradiance 1,000 W/m², AM 1.5, cell temperature 25 °C.
 Rated electrical characteristics are within ±10 % of the indicated values of I_{sc} , V_{oc} and 0 to +5 % of P_{max} .
 Reduction of efficiency from an irradiance change of 1,000 W/m² to 200 W/m² ($T_{module} = 25$ °C) is less than 3 %.

Electrical data (NMOT)

NU-JC415			
Maximum power	P_{max}	311.11	W_p
Open-circuit voltage	V_{oc}	36.09	V
Short-circuit current	I_{sc}	11.25	A
Voltage at point of maximum power	V_{mpp}	29.35	V
Current at point of maximum power	I_{mpp}	10.6	A

NMOT = Nominal Module Operating Temperature: 42.5 °C, irradiance 800 W/m², air temperature of 20 °C, wind speed of 1 m/s.

Mechanical data

Length	1,722 mm
Width	1,134 mm
Depth	30 mm
Weight	20.7 kg

Temperature coefficient

P_{max}	-0.341 %/°C
V_{oc}	-0.262 %/°C
I_{sc}	0.054 %/°C



Limit values

Maximum system voltage	1,000 V DC
Over-current protection	25 A
Temperature range	-40 to 85 °C
Max. mechanical load (snow/wind)	2,400 Pa
Tested snow load (IEC61215 test pass*)	5,400 Pa


Packaging data

Modules per pallet	36 pcs
Pallet size (L × W × H)	1.75 m x 1.13 m x 1.25 m
Pallet weight	Approx. 780 kg

Dimensions (mm)



Frame long side cross section



Frame short side cross section

*Please refer to SHARP's installation manual for details.

General data

Cells	Half-cut cell mono, 182 mm x 91 mm, MBB, 2 strings of 54 cells in series
Front glass	Anti-reflective high transmissive low iron tempered glass, 3.2 mm
Frame	Anodized aluminium alloy, silver
Backsheet	White
Cable	Ø 4.0 mm ² , length 1,250 mm
Connection box	IP68 rating, 3 bypass diodes
Connector	MC4 (Multi Contact, Stäubli), IP68

Note: Technical data is subject to change without prior notice. Before using SHARP products, please request the latest data sheets from SHARP. SHARP accepts no responsibility for damage to devices which have been equipped with SHARP products on the basis of unverified information. The specifications may deviate slightly and are not guaranteed. Installation and operating instructions are to be found in the corresponding handbooks, or can be downloaded from www.sharp.eu. This module should not be directly connected to a load.