



MultiSync® LCD1510+

Display Type:	Wide Angle Active Matrix TFT, 15 inch
Active Display Area:	304 x 228 mm
Pixel Pitch:	0.297 x 0.297 mm
Viewing Angle:	160° horizontal/160° vertical (at contrast ratio 10:1)
Brightness:	200 cd/m² typ.
Contrast Ratio:	200:1 typ.
Number of Colours:	16.77 million
Optimum Resolution:	1024 x 768 at 75 Hz
Other Resolutions:	832 x 624, 800 x 600, 720 x 400, 720 x 350, 640 x 480, 640 x 400, 640 x 350
Features/Adjust Functions:	On-Screen Manager (OSM) lock out, contrast, brightness, auto adjust, fine adjust, colour control, monitor info, language select, Intelligent Power Management (VESA/EPA/NUTEK compliant) disable
User Controls:	On/Off, OSM menu
Plug & Play, Asset Management:	VESA DDC1, DDC2B and EDID standard
Horizontal Frequency:	24.8–60 kHz
Vertical Frequency:	56.2–75 Hz
Input Connectors:	Mini D-sub 15 pin, analog connector
Audio Functions:	No
USB Functions:	No
VESA Mounting Interface:	Yes, 100 x 100 mm
Kensington Lock:	Yes
Dimensions (W x H x D):	381 x 447 (max.) x 217 mm
Screen Tilt/Swivel/Rotate:	–5° to +45°/ –45° to +45°
Weight:	7.0 kg
External Adapter:	AC 100–240 V, 1.6 A/0.8 A, external AC adapter
Power Requirements:	34 W max. on mode, < 5 W power saving mode
Ambient Temperature (Operat.):	+5 °C to +35 °C
Ambient Humidity (Operating):	30–80% (non-condensing)
Safety/Ergonomics:	CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO 99
Warranty:	3 years warranty, warranty extension programs depending on specific country
Shipping Contents:	Monitor, power cord, VGA signal cable 1.8 m, user manual, Pivot® software

- Professional LCD monitor with wide angle TFT display
- VESA mounting interface enables versatile installation
- TORO design, screen rotation by 90 degrees
- Complies with TCO 99 for stringent standards of safety and ergonomics

All specifications are subject to change without notice. Status June 2000

Pivot® and the Pivot Enabled™ logo are registered trademarks of Portrait Displays, Inc. Copyright 1999 Portrait Displays, Inc. All rights reserved.

