



Product Service

C E R T I F I C A T E

No. Z1A 10 09 56546 061

Holder of Certificate: NEC Display Solutions, Ltd.4-13-23 Shibaura, Minato-ku,
Tokyo
108-0023 JAPAN**Certification Mark:****Product:****Monitor
(LCD Monitor)**

The product meets the safety and health requirements of the German Equipment and Product Safety Act section 7 subsection 1 sentence 2 GPSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

Test report no.: 6121010111501**Valid until:** 2015-09-28**Date,** 2010-09-29

(Bill Lin)

Page 1 of 3



Product Service

CERTIFICATE**No. Z1A 10 09 56546 061****Model(s):** L309TY, PA301W-BK-L1(W)

Parameters:

Rated input voltage:	100-240 Vac
Rated input current:	1.9-0.7 A
Rated frequency:	50/60 Hz
Protection class:	I
Max. ambient temperature:	40 °C
Degree of protection against ingress of liquids:	Ordinary

Remark: See attachment for LCD(s) covered by this certificate.

**Tested
according to:**

EN 60950-1/A11:2009
EK1-ITB 2000:2010
ZEK 01.2-08/12.08

Factory(ies): 45530, 66259



Taiwan

Attachment to the Certificate No. Z1A 10 09 56546 061

The following LCD's panel description of the models are as below:

1. LG Display Type: LM300WQ5

Suitable for environments: $L_{REF,EXT} = 200 \text{ cd/m}^2$ and $L_{REF,SML} = 2000 \text{ cd/m}^2$

Design screen illuminance, E_s : 293.4 lx

Pixel fault classification: I

Design viewing distance: 500 mm

Design viewing direction: (0° , 90°)

Viewing direction range: Φ range is 0° to 360°

θ range is 74.2° (for 30" LCD Panel)

Content and perception: Artificial information

Date: 2010-09-29



Testing Laboratory

Bill Lin

Bill Lin