

NEC LCD1511M



Display Type:	15.0 inch diagonal screen size
Active Display Area:	304.1 x 228.1 mm
Pixel Pitch:	0.297 x 0.297 mm
Viewing Angle:	130° horizontal / 100° vertical (at CR= 10:1)
Brightness:	250 cd/m ² (typ.)
Contrast Ratio:	400 :1 (typ.)
Response Time:	35 ms (typ.)
Number of Colours:	16.2 Mill.
Optimum Resolution:	1024 x 768 @ 60 Hz (0.8 mega pixel)
Other Resolutions:	800 x 600, 832 x 624, 720 x 400, 640 x 480, 640 x 400, 640 x 350
Features/Adjust Functions:	Auto Adjustment; Contrast; Horizontal Position; Vertical Position; Frequency; Tracking; Display Mode; OSD Off-Time; Language; Colour Adjustment; Volume; Mute
User Controls:	On/Off, OSM Menu
Plug & Play, Asset Management:	DDC 1/2B
Horizontal Frequency:	31.5 – 60 kHz
Vertical Frequency:	56 – 75 Hz
Dot clock rate:	78.75 MHz
Connectors:	Mini D-Sub, 15 pin
Audio Functions:	Yes, 2x1W Loudspeakers
USB Functions:	No
VESA Mounting Interface:	75 x 75 mm
Kensington-Lock:	Yes
Dimensions (W x H x D):	346x338.1x171 mm
Screen Tilt	0° to +20°
Weight:	3.25 kg
Power Supply:	100-240V; external power supply
Power Requirements:	35 W max. On mode, < 5 W off mode
Safety/Ergonomics:	CE; TÜV GS; UL; cUL; TCO99; FCC Class B
Warranty:	T.B.D.
Shipping Contents:	Monitor; AC/DC power adapter; power cord; video cable; driver CD; users manual; audio cable

- ✓ Allround LCD monitor with Digital TFT Display
- ✓ Elegant, flat design with silvery front
- ✓ Analogue Input
- ✓ Internal Loudspeakers
- ✓ VESA mounting interface enables versatile installation
- ✓ Ergonomics and safety complying to the highest industry standards



All specifications are subject to change without notice. Status September 2002.