

NEC MultiSync® EA192M

Objednáací kód: 60003065 (WH), 60003064 (BK)

NEC LCD 19" Commercial Display

The EA192M is an energy saving 19" 5:4 format monitor. It offers LED backlight, DisplayPort connectivity and full adjustability. Low power consumption and low operating costs make the display perfect for use in the professional office environment. Outstanding ergonomic qualities and intelligent features such as the Ambient Light Sensor make it very user-friendly and help to increase productivity.

Ideal for large corporates and medium sized businesses for the standard office use with environmental attention.

POSKYTOVÁNÍ SKUTEČNÝCH VÝHOD

Ambient Light Sensor - with Auto Brightness function always sets optimised brightness level according to ambient light and content conditions.

Ergonomická kancelář - plně nastavitelná výška (110 mm), natočení, naklonění a otočná funkce zajišťují perfektní individuální ergonomické nastavení.

Green Product Concept - Eco Mode and Carbon Footprint Meter / Carbon Savings Meter, Ambient Light Sensor.

Image display - 19inch 5:4 TN with LED backlight.

Input - Display can be used with two digital (DVI-D, DisplayPort) and one analogue input.

Udržitelná kancelář - nízká spotřeba energie s LED podsvícením a snímačem okolního světla.

Vesa Mount (100 mm) - allows to install the monitor via various mounting solutions, stand has a quick release for faster installations.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



VYNIKAJÍCÍ VÝKON

- EA192M sets new standard in environmental compatibility. The Ambient Light Sensor serves to increase energy saving even further. It measures the ambient light and adjusts the screen to the optimum brightness automatically without any manual settings being required. The use of recycling plastic for the monitor housing and of mercury-free materials fulfil the demands of the NEC "Green Vision" campaign.
- The connection options ensure leading-edge compatibility. With a DisplayPort, a DVI-D as well as an analogue interface, the NEC MultiSync® EA192M provides outstanding connectivity and the optimum basis for all business applications. The display also features speakers and a headphone socket for comfortable office communication.
- Height adjustment through up to 110 mm and the pivot function allow the screen to be positioned to meet individual needs and ensure a high degree of user-friendliness. Thanks to its ergonomic and ecological characteristics, the monitor has gained TCO 5.0 certification and been awarded the EPEAT Silver Seal.
- The eco-friendly display further extends our comprehensive range for the corporate sector. It helps to reduce running costs throughout the display's entire lifetime and its features make daily operations simpler and more productive. Excellent value for money.



SPECIÁLNÍ CHARAKTERISTIKA

19" (5:4) Vysoce účinný panel pouze s dvojitým podsvícením uspoří více než 30 % energie, Ambient light senzor pro optimalizaci jasu, Carbon Footprint Meter, Carbon Savings Meter, ErgoDesign®: Height adjustable stand (110 mm) with 90° Pivot features, Kompatibilní s NaViSet® a NaViSet®Administrator, kompatibilní s Windows 7, NaViSet Administrator 2, podpora sRGB, TORO™ Design, WindowsVistaCertifiedLogo



Energetická účinnost

LED backlight technology

Ekologické standardy

Energy Star 5.0; EPEAT™ Gold (black version); EPEAT Silver; ErP; RoHS compliant

TECHNICKÁ SPECIFIKACE NEC MultiSync® EA192M

DISPLAY	
Technologie panelu	W-LED TN TFT
Velikost obrazovky [palce/cm]	19 / 48.2
Poměr stran obrazovky	5:4
Rozteč bodů [mm]	0.294
Jas (typ.) [cd/m²]	250
Kontrastní poměr (typ.)	1000:1
Pozorovací úhly [°]	170 horizontální / 160 vertikální (typ. při kontrastním poměru 10:1); 176 horizontální / 170 vertikální (typ. při kontrastním poměru 5:1)
Doba odezvy (typ.) [ms]	5
Barvy [mil.]	16.77
SYNCHRONISATION RATE	
Horizontální frekvence [kHz]	30 - 82
Vertikální frekvence [Hz]	56 - 75
RESOLUTION	
Optimální rozlišení	1280 x 1024 at 60 Hz
Podporované rozlišení	1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
CONNECTIVITY	
Digitální	1 x DVI-D (with HDCP); 1 x DisplayPort
Analog	1 x mini D-sub 15 pin
ELECTRICAL	
Spotřeba energie v módu [W]	23 (typ.); 16 (Eco Mode 2)
Power Savings Mode [W]	< 0.5
Napájení	100-120 V/220-240 V; 1 A/0.5 A; integrované napájení
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
ERGONOMICS	
ErgoDesign®: Výšková nastavitelnost stojanu [mm]	110
Naklonění [°]	-5 to 20
Naklonění/ Otočení [°]	-45 to 45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)
MECHANICAL	
Tloušťka rámečku [mm]	15
Rozměry (W x H x D) [mm]	408 x 386.4 x 213.9; Without stand: 408 x 338 x 65
Hmotnost [kg]	5.5; bez podstavce: 3,5
VESA montáž [mm]	100 x 100
ADDITIONAL FEATURES	
Barevné provedení	Stříbrný přední rámeček; bílá zadní strana; Černý přední rámeček, černá zadní strana
Cable Management	ano
Bezpečnostní Kensington slot	yes
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Audio funkce	1W + 1W (De-activateable)
Nastavení funkcí	Automatické nastavení; DV Mode; Eco mód; Informace o monitoru; Intelligent Power Management; Jas; Jemné nastavení (analog); Kontrast; LED jas; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Ovládání teploty barev; sRGB; Výběr jazyka; Časovač vypnutí (Power-Off)
Obsah balení	Monitor; Napájecí kabel; CD-ROM; Sales Office List; Uživatelský manuál Signální kabel: VGA - VGA; DVI-D - DVI-D
Bezpečnost a ergonomie	EPEAT Silver™; EPEAT™ Gold (black version); CE; ErP; TCO 5.0; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star 5.0; FCC Class B; PCT/Gost; UL/C-UL or CSA; ISO 9241-307 (pixel failure class I); MPR II/ MPR III; RoHS
Záruka	3 roky záruka vč. podsvitu