# Sharp BP-51C26

The Sharp BP-51C26 is a smart A3 colour MFP with multi-layered security features and advanced environmental credentials, perfect for any modern office.



- 26ppm A3 colour MFP with seamless integration and connection to cloud based business process applications
- Multi-layeredsecurity features include automatic BIOS recovery, Trusted Platform Module and optional Bitdefender anti-malware protection software
- Collaborate with ease using the Microsoft® Teams connector to print from or scan to your Microsoft® Teams channels directly from the MFP control panel $^{[1]}$
- Keep your data, device and network secure with optional Bitdefender antimalware protection software  $^{\!\!(2)}$
- Bring more flexibility to your print output with an extensive range of finishing options including stapling, punching and folding
- A sustainable design uses up to 50% recycled plastics in manufacturing the base unit of the MFP and cardboard packaging helps reduces plastic waste

- 100-sheet Reversing Single Pass Feeder scans one or two-sided originals at speeds of up to 80ipm for completing large jobs with ease and efficiency
- Advanced eco-technologies deliver an impressively low TEC value and standby power consumption rate
- Now integrates with Microsoft Entra ID to support organisations with user authorities.
- Intuitive icons and a smartphone style interface on the 10.1-inch colour LCD control panel make operating the MFP smooth and easy
- Single sign-on lets you securely print from or scan to public cloud storage services quickly and easily
- Keep up-to-date and compliant with automatic online firmware and application updates via the Sharp Application Portal

[1] Microsoft® Teams connector requires BP-AM10., [2] Bitdefender anti-malware protection software requires BP-VD10



## Specifications

General	
Engine speed: A4 Colour (ppm)	26
Engine speed: A4 B/W (ppm)	26
Engine speed: SRA3 Colour (ppm)	15
Engine speed: SRA3 B/W (ppm)	15
Paper size: Min.	A6R
Paper size: Max.	SRA3
Paper weight: Min. (g/m²)	52
Paper weight: Max. (g/m²)	300
Paper capacity: Std. (sheets)	650
Paper capacity: Max. (sheets)	6300
Warm-up time (sec.)	16
Memory general: Max. (GB)	5
Storage: Std.	SSD
Storage: Opt.	SSD
SSD capacity: Std. (GB)	128
SSD capacity: Opt. (GB)	512
Duplex	Std.
Power requirements: frequency min.	50
(Hz)	
Power requirements: frequency	60
max. (Hz)	
Power requirements: voltage min.	200
(V)	
Power requirements: voltage max.	240
(V)	
Power consumption (kW)	1.84
Base Unit: Width (mm)	608
Base Unit: Depth (mm)	653
Base Unit: Height (mm)	829
Weight (kg)	77

#### Fax

Fax	Opt.
Compression method	MH, MR, MMR, JBIO
Communication protocol	Super G3, G3
Transmission time (sec.)	2
Modem speed: Min. (bps)	2400
Modem speed: Max. (bps)	33600
Transmission resolution: Std (dpi)	203.2 x 97.8 dpi
Transmission resolution: Ultra Fine	406.4 x 391 dpi
(dpi)	
Document size: Min.	A5
Document size: Max.	A3
Memory: Max. (GB)	4
Grey scale (levels)	256
Dial registration: rapid/speed dial	2000

#### Wireless LAN

destinations)

Broadcast transmission (Max.

WIII CIC33 LAIN	Opt.
Compliant regulation	IEEE802.11a/ac/b/g/n
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA/WPA2-mixed PSK,
	WPA/WPA2-mixed EAP, WPA2 PSK,
	WPA2 EAP, WPA2 EAP/WPA3-mixed,
	PSK/SAE, WPA3 SAE, WPA2/WPA3-

#### **Print**

Resolution (dpi)	1200 x 1200, 600 x 600, 9600 x 600
Interface: Std.	USB 2.0, USB 3.0, 10Base-T, 100Base-TX
	1000Base-T

Supported OS: Std. Windows 10, Windows 11, Windows Server 2016. Windows Server 2019. Windows Server 2022, Windows Server 2025, Mac OS X 10.15, Mac OS X 11, Mac

OS X 12, Mac OS X 13, Mac OS X 14, Mac

**Network protocols** TCP/IP (IPv4, IPv6)

LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading **Printing protocols** 

print files, IPP, SMB, WSD 80 PCL, 139 PostScript 3

#### Copy

Available Fonts

A3
7.6
6.5
Opt.
9999
600 x 600, 600 x 400
600 x 600
1200 x 1200, 600 x 600, 9600 x 600

Gradation: Colour (equivalent levels) Zoom range: Min. (%) 25 Zoom range: Max. (%) Preset copy ratios

#### Scan

Network scanner	Std.
Scan method	Push scan, Pull scan
Push scan resolution (dpi)	100, 150, 200, 300, 400, 600
Pull scan resolution (dpi)	75, 100, 150, 200, 300, 400, 600, 50-9600
File formats: Std.	TIFF, PDF, PDF/A-1a, PDF/A-1b,

Encrypted PDF, Compact PDF, JPEG, XPS, Searchable PDF, Microsoft Office (pptx, xlsx, docx), Text (TXT), Rich Text

Desktop, FTP, Email, Network Folder, Scan destinations

### File

Document filing	Std.
Stored jobs	Copy, Print, Scan, Fax transmission
Storage folders	Quick file, Main, Custom (Max 1000)
Confidential storage	False

#### **Finish**

Output capacity: Min. (sheets)	500
Output capacity: Max. (sheets)	3250
Staple capacity: Max. (sheets)	65
Saddle stitch	Opt.
Off-set shifting	Std.
Hole punch	Opt.

#### **Toner Yield**

Black (pages at 5% coverage)	40000
Cyan (pages at 5% coverage)	24000
Magenta (pages at 5% coverage)	24000
Yellow (pages at 5% coverage)	24000







500

mixed, EAP, WPA3 EAP





