

Value Projector

NEC V281W



Get the Ultimate 3D Experience with the V281W DLP® Projector.

The compact size in combination with light weight makes it easy to place it wherever you need it. With 2800 ANSI lumens brightness and higher contrast this compact projector is recommended for screen sizes of up to 110" diagonal.

The V281W is the perfect solution for small meeting rooms as well as classrooms.

Benefits

Control and Monitoring – via RS-232.

Green EcoMode Button – on remote.

Higher Efficiency, Lower Power Consumption – full ErP compliance.

Long Lamp Life – up to 5000 hrs.

Virtual Remote – for direct PC control.

Specifications

Product Information

Product Name

NEC V281W

Product Group

Value Projector

Order Code

60003635

Image

Projection Technology

1-chip DLP™ Technology

Native Resolution

1280 x 800 (WXGA)

Contrast Ratio

3000:1

Brightness

2800 Lumen

Lamp

225 W AC

Light Source Life [hrs]

3000 (5000 Eco Mode)

Projection Factor

1.55 – 1.7 : 1

Projection Distance [m]

1 – 11

Screen Size (diagonal) [cm] / [inch]

Maximum: 762; Minimum: 76

Zoom

Manual

Focus Adjustment

Manual

Supported Resolutions

Up to 1920x1080

Frequency

Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz

Connectivity

RGB (analog)

Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr)
Output: 1 x Mini D-sub 15 pin

Digital

Input: 1 x HDMI™ (Deep Color, Lip sync)

Video

Input: 1 x RCA

S-Video

Input: 1 x Mini DIN 4-pin

Audio

Input: 1 x RCA Stereo for Video and S-Video; 2 x 3.5 mm Stereo Mini Jack
Output: 1 x 3.5 mm Stereo Mini Jack

Control

Input: 1 x D-Sub 9 pin (RS-232) (male)

LAN

1 x RJ45

Video Signals

NTSC; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Remote Control

Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freeze-function; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select

Electrical

Power Supply

100-240 V AC; 50 - 60 Hz

Power Consumption [W]

0.5 Power Savings Mode; 210 Eco Mode; 268 max.

Mechanical

Dimensions (W x H x D) [mm]

310 x 95 x 247 (without lens and feet)

Weight [kg]

2.5

Fan Noise [dB (A)]

33 / 37 (Eco / Normal)

Ergonomics

Safety and Ergonomics

CE; ErP; RoHS; TUEV Type Approved

Speakers [W]

1 x 7 (mono)

Additional Features

Special Characteristics

3D ready DLP®-Link™, 120 Hz and Top/Bottom, 60 Hz; 6-segment Colour Wheel; Auto Power Start; BrilliantColor™ and VIDi technology; Carbon Savings Meter; Crestron RoomView; Long Life Lamp; Manual vertical Keystone Correction (V= ±40°); NaViSet Administrator 2; Off-Timer; Plug & Play; Quick-Start-/Direct-Power-Off Function; Virtual Remote for direct PC control

Green Features

Energy Efficiency

Intelligent Power Management

Ecological Materials

100% recyclable packaging; Downloadable manuals

Ecological Standards

ErP compliant; RoHS compliant; WEEE

Warranty

Projectors

3 years pan-European service

Light Source

6 months, max. 1000 hrs

Shipping Content

Shipping Content

IR Remote Control (RD-448E); Lens Cap; Mini D-SUB Signal Cable (1.8 m); Power Cord; Projector; Quick Setup Guide; User Manual on CD-ROM (Russian Manual in Hardcopy)

Optional Accessories

Optional Accessories

3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP01GL/ NP02GL); Lamp (NP18LP); Mouse Receiver (NP01MR); Universal Ceiling Mounts (NP01/02/03/04/05UCM)



TUEV Type Approved



CE



ErP



RoHS

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 24.09.2026