BP-50M55

Future proofed by design with stringent security features and superior functionality for hybrid working



- 55ppm black & white MFP with seamless integration and connection to cloud based business process applications
- Built-in Microsoft® Teams connector strengthens collaboration by enabling direct and secure access for printing to or scanning from your Microsoft® Teams channels
- Keep your data, device and network secure with optional Bitdefender anti-malware protection software
- Securely print from or scan to public cloud storage services quickly and easily with single sign-on
- Extensive finishing options including a folding unit bring even more flexibility to your print output
- Keep up-to-date and compliant with remote firmware and application updates via the Sharp Application Portal

- Feature rich hardware and solutions platform that supports the hybrid working environment
- Industry leading system and data protection features including BIOS based security and standard Trusted Platform Module ensure that confidential data is kept secure
- Interact with the MFP directly from your mobile device via WiFi, AirPrint, Bluetooth, NFC and QR Code
- 10.1-inch colour LCD operation panel offers a smartphone style user interface making everything easy to access and use
- Superior environmental performance delivers lower standby power consumption and low TEC value
- 100-sheet Reversing Single Pass Feeder scans one or two-sided originals at speeds of up to 80ipm for completing large jobs with ease and efficiency



Specifications

GENERAL

Engine speed: A4 B/W (ppm) 55 Engine speed: A3 B/W (ppm) 26 Paper size: Min.-Max. A6R - A3W Paper weight (g/m²) 60 - 300 Paper capacity: Std. (sheets) 650 Paper capacity: Max. (sheets) 6300 Warm Up Time (sec.) 15 Memory general: Min./Max. (GB) STD / OPT

 SSD
 STD/OPT

 SSD Capacity (GB)
 128/512

 Duplex
 STD

Power requirements - rated local AC voltage

(Hz)

Power consumption (kW) 1.84

Dimensions (mm) 608 x 653 x 829

Weight (kg) 63

DOCUMENT FEEDER

Original capacity (sheets) 100

DOCUMENT FILING

 Document filing (Standard / Option)
 STD

 Document filing capacity: main & custom
 20000

 folders (pages)

Document filing capacity: quick file folder

(pages)

 Stored jobs
 Copy, print, scan, fax transmission

 Storage folders
 Quick file folder, main folder, custom folder (max. 1000)

10000

220 - 240V, 50 / 60Hz

FAX

Fax (Standard / Option) OP1

Compression method MH / MR / MMR / JBIG Communication protocol Super G3 / G3

 Transmission time (sec.)
 2

 Modem speed (bps)
 33600 - 2400

Transmission resolution (dpi) STD 203.2 x 97.8 dpi / Ultra Fine

406.4 x 391 dpi

Document size: Min.A5Document size: Max.A3Memory (GB)4Grey scale (levels)256Dial registration: rapid/speed dial2000Broadcast transmission (Max. destinations)500

WIRELESS LAN

Wireless LAN (Standard / Option) OPT

 Compliant regulation
 IEEE802.11 a / b / g / n / ac

 Access mode
 Infrastructure mode, Software AP

mode

Security WEP, WPA / WPA2-mixed PSK, WPA

/ WPA2-mixed EAP, WPA2-PSK, WPA2-EAP, WPA2 / WPA3-mixed PSK / SAE, WPA3 SAE, WPA2 / WPA3-mixed EAP, WPA3 EAP COPIER

Original paper size: Max. A3
First copy out time: B/W (sec.) 3.5
E-sort Std. •
Continuous copy (Max. copies) 9,999

Scan resolution: B/W (dpi) 600 x 600, 600 x 400

 Scan resolution: Colour (dpi)
 600 x 600

 Print resolution (dpi)
 600 x 600, 9600 x 600

Gradation: B/W (equivalent levels)2Gradation: Colour (equivalent levels)256Zoom range (%)25 - 400Preset copy ratios10

SCANNER

Network Scanner (Standard / Option) STD Scan method Push scan and Pull scan •

Push scan resolution (dpi) 100, 150, 200, 300, 400, 600

Pull scan resolution (dpi) 75, 100, 150, 200, 300, 400, 600, 50 -

9600

File formats TIFF, PDF, PDF / A-1a, PDF / A-1b, encrypted PDF, compact PDF,

JPEG, XPS, searchable PDF, Microsoft Office (pptx, xlsx, docx),

TXT (UTF-8), RTF

Scan destination: Desktop
Scan destination: FTP, Email
Scan destination: Network folder
Scan destination: USB memory

PRINTER

Resolution (dpi) 600 x 600, 9600 x 600

Network Printer (Standard / Option) STD Ethernet

Network Printer (Standard / Option) STD Ethernet Interface: Std./Opt. USB 2.0, USB 3.0, 10Base-T /

100Base-TX / 1000Base-T **Supported OS: Std.**Windows 8.1, 10, 11. Windows
Server 2012, 2012R2, 2016, 2019

 Supported OS: Opt.
 Mac OS X 10.10, 10.11, 10.12, 10.13, 10.14, 10.15, 11, 12

 Network protocols
 TCP / IP (IPv4, IPv6)

 Printing protocols
 LPR, Raw TCP (port 9100), POP3 (e

mail printing), HTTP, FTP for downloading print files, IPP, SMB,

WSD

PDL: Std./Opt. STD PCL 6. OPT Adobe® PostScript®

3™

Available fonts 80 (PCL), 139 (Adobe PostScript 3)

FINISHING

 Output capacity: Max. (sheets)
 500 - 3000

 Staple capacity: Max. (sheets)
 65

 Saddle stitch
 OPT

 Off-set shifting
 STD

 Hole punch
 OPT

TONER YIELD

Black (pages at 6% coverage) 40000















Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks of Adobe Systems Incorporated in the US and/or other countries. Coogle LrU. The Google Drive, Grain, Service mark, s