

NEC MultiSync C981Q



- Future Ready with Open Modular Intelligence Expansion – upgrade the power of your display by integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute modules or signal interfaces.
- Ease of use and operation – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.
- Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.
- Mission-critical 24/7 ready operation – the selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.
- Future-proof signal connectivity and processing – numerous native UHD resolution inputs with 60Hz refresh rate, plus automatic upscaling to UHD for other signals, provide "pixel-free viewing".

Specifications

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	98 / 248
Brightness (cd/m ²)	350, 250 (shipment setting)
Contrast Ratio	1300:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V) @ CR > 10	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	28

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	240 shipping
Operating Temperature (oC)	0 to 40
Humidity (%)	20 to 80

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 400 (FDMI); 600 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Shipping Content	CD-ROM (User Guides / Manuals); Display; DisplayPort Cable; Remote Control; USB cable
Remote Control Transmitter	Yes
Operation Manual	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

KEY SPECIFICATIONS

24/7 Operation Certified	•
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	•
Built in Speakers (W)	10W + 10W
Power Management	•
Cabinet Colour	Black
Colour Versions	Optional coloured overframes
Temperature Sensor	•
Brightness Sensor	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	15.9
Bezel Size (U/L) mm	15.9
Product Dimensions (W/H/D) mm	2,194 x 1,249 x 93
Shipping Carton Dimensions (W/H/D) mm	2,355 x 1,454 x 414
Product Weight With Stand (Kg)	90
Shipping Weight (Kg)	116

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DisplayPort	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

